

Package ‘MsBackendRawFileReader’

May 30, 2024

Type Package

Title Mass Spectrometry Backend for Reading Thermo Fisher Scientific raw Files

Version 1.10.0

Depends R (>= 4.1), methods, Spectra (>= 1.5.8)

Imports ProtGenerics (>= 1.35.3), MsCoreUtils, S4Vectors, IRanges, rawrr (>= 1.10.1), utils, BiocParallel

Suggests BiocStyle (>= 2.5), ExperimentHub, MsBackendMgf, knitr, lattice, mzR, protViz (>= 0.7), rmarkdown, tartare (>= 1.5), testthat

Description implements a MsBackend for the Spectra package using Thermo Fisher Scientific's NewRawFileReader .Net libraries. The package is generalizing the functionality introduced by the rawrr package. Methods defined in this package are supposed to extend the Spectra Bioconductor package.

URL <https://github.com/fgcz/MsBackendRawFileReader>

BugReports <https://github.com/fgcz/MsBackendRawFileReader/issues>

Encoding UTF-8

NeedsCompilation yes

biocViews MassSpectrometry, Proteomics, Metabolomics

RoxygenNote 7.3.1

License GPL-3

SystemRequirements mono-runtime 4.x or higher (including System.Data library) on Linux/macOS, .Net Framework (>= 4.5.1) on Microsoft Windows.

VignetteBuilder knitr

Collate 'hidden_aliases.R' 'AllGenerics.R'
'MsBackendRawFileReader-functions.R' 'MsBackendRawFileReader.R'
'benchmark.R' 'zzz.R'

git_url <https://git.bioconductor.org/packages/MsBackendRawFileReader>

git_branch RELEASE_3_19

git_last_commit 20a8ce8

git_last_commit_date 2024-04-30

Repository Bioconductor 3.19

Date/Publication 2024-05-29

Author Christian Panse [aut, cre] (<<https://orcid.org/0000-0003-1975-3064>>),
 Tobias Kockmann [aut] (<<https://orcid.org/0000-0002-1847-885X>>),
 Roger Gine Bertomeu [ctb] (<<https://orcid.org/0000-0003-0288-9619>>)

Maintainer Christian Panse <cp@fgcz.ethz.ch>

Contents

hidden_aliases	2
ioBenchmark	3
MsBackendRawFileReader	4
MsBackendRawFileReader-class	5
Index	6

hidden_aliases	<i>Internal page for hidden aliases</i>
----------------	---

Description

For S4 methods that require a documentation entry but only clutter the index.

Usage

```
filterScan(object, filter, ...)
```

```
scanType(object, ...)
```

```
## S4 method for signature 'MsBackendRawFileReader'
backendInitialize(object, files, ..., BPPARAM = bpparam())
```

```
## S4 method for signature 'MsBackendRawFileReader'
show(object)
```

```
## S4 method for signature 'MsBackendRawFileReader'
peaksData(object, ..., BPPARAM = bpparam())
```

```
## S4 method for signature 'MsBackendRawFileReader'
intensity(object, ..., BPPARAM = bpparam())
```

Examples

```
beRaw <- Spectra::backendInitialize(MsBackendRawFileReader::MsBackendRawFileReader(),
  files = rawrr::sampleFilePath())
beRaw
```

ioBenchmark

RawFileReader_read_peaks benchmark

Description

derives numbers to evaluate time performance for reading a single spectrum in dependency from the chunk size (how many spectra are read in one function call) for reading different numbers of overall spectra.

Usage

```
ioBenchmark(
  nv = c(1000, 5000, 10000),
  sizev = c(8, 16, 32, 64, 128, 256, 8, 16, 32, 64, 128, 256, 8, 16, 32, 64, 128, 256, 8,
    16, 32, 64, 128, 256, 8, 16, 32, 64, 128, 256, 8, 16, 32, 64, 128, 256),
  rawfile
)
```

Arguments

nv number of spectra to be read.
sizev number of spectra write and parsed in one single junk.
rawfile the Thermo Fisher Scientific raw file.

Value

data.frame

Examples

```
eh <- ExperimentHub::ExperimentHub()
EH4547 <- normalizePath(eh[["EH4547"]])
(rawfileEH4547 <- paste0(EH4547 , ".raw"))
if (!file.exists(rawfileEH4547 )){
  file.link(EH4547 , rawfileEH4547)
}
S <- ioBenchmark(1000, c(128, 256, 128, 256), rawfile=rawfileEH4547)
```

MsBackendRawFileReader

MsBackendRawFileReader

Description

MsBackendRawFileReader

Usage

```
MsBackendRawFileReader()
```

```
## S4 method for signature 'MsBackendRawFileReader'  
filterScan(object, filter = character(), ...)
```

```
## S4 method for signature 'MsBackendRawFileReader'  
scanType(object, ...)
```

Arguments

object	MsBackendRawFileReader object
filter	filter string
...	Arguments to be passed to methods.

Value

a MsBackendRawFileReader object.

a character vector of scan types.

Examples

```
beRaw <- Spectra::backendInitialize(MsBackendRawFileReader::MsBackendRawFileReader(),  
  files = rawrr::sampleFilePath())  
beRaw |> MsBackendRawFileReader::filterScan('Ms')  
beRaw <- Spectra::backendInitialize(MsBackendRawFileReader::MsBackendRawFileReader(),  
  files = rawrr::sampleFilePath())  
scanType(beRaw) |> head()
```

MsBackendRawFileReader-class

RawFileReader-based backend

Description

The ‘MsBackendRawFileReader’ inherits all slots and methods from the base ‘MsBackendDataFrame’ (in-memory) backend. It overrides the base ‘mz’ and ‘intensity’ methods as well as ‘peaksData’ to read the respective data from the original raw data files.

The validator function has to ensure that the files exist and that required column names are present.

The ‘backendInitialize’ method reads the header data from the raw files and hence fills the ‘spectra-Data’ slot.

Author(s)

Christian Panse (2019-2021)

Examples

```
beRaw <- Spectra::backendInitialize(MsBackendRawFileReader::MsBackendRawFileReader(),
  files = rawrr::sampleFilePath())
beRaw
Spectra::msLevel(beRaw)
```

Index

* **internal**

- hidden_aliases, [2](#)
- [,MsBackendRawFileReader-method
(hidden_aliases), [2](#)
- backendInitialize,MsBackendRawFileReader-method
(hidden_aliases), [2](#)
- filterScan (hidden_aliases), [2](#)
- filterScan,MsBackendRawFileReader-method
(MsBackendRawFileReader), [4](#)
- hidden_aliases, [2](#)
- intensity,MsBackendRawFileReader-method
(hidden_aliases), [2](#)
- ioBenchmark, [3](#)
- MsBackendRawFileReader, [4](#)
- MsBackendRawFileReader-class, [5](#)
- peaksData,MsBackendRawFileReader-method
(hidden_aliases), [2](#)
- scanType (hidden_aliases), [2](#)
- scanType,MsBackendRawFileReader-method
(MsBackendRawFileReader), [4](#)
- show,MsBackendRawFileReader-method
(hidden_aliases), [2](#)