

# Package ‘pRoloc’

April 23, 2016

**Type** Package

**Title** A unifying bioinformatics framework for spatial proteomics

**Version** 1.10.3

**Author** Laurent Gatto and Lisa M. Breckels with contributions from  
Thomas Burger and Samuel Wiczorek

**Maintainer** Laurent Gatto <lg390@cam.ac.uk>

**Description** This package implements pattern recognition techniques on  
quantitative mass spectrometry data to infer protein  
sub-cellular localisation.

**Depends** R (>= 2.15), MSnbase (>= 1.17.1), MLInterfaces (>= 1.37.1),  
methods, Rcpp (>= 0.10.3), BiocParallel

**Imports** Biobase, mclust (>= 4.3), caret, e1071, sampling, class,  
kernlab, lattice, nnet, randomForest, proxy, FNN, BiocGenerics,  
stats, RColorBrewer, scales, MASS, knitr, mvtnorm, gtools,  
plyr, ggplot2, biomaRt

**Suggests** testthat, pRolocdata (>= 1.5.8), roxygen2, synapter, xtable,  
tsne, BiocStyle, hpar, dplyr, GO.db, AnnotationDbi

**LinkingTo** Rcpp, RcppArmadillo

**License** GPL-2

**VignetteBuilder** knitr

**Video** <https://www.youtube.com/playlist?list=PLvIXxpatSLA2loV5Srs2VBpJIYUIVJ4ow>

**URL** <https://github.com/lgatto/pRoloc>

**BugReports** <https://github.com/lgatto/pRoloc/issues>

**biocViews** Proteomics, MassSpectrometry, Classification, Clustering,  
QualityControl

**Collate** AllGenerics.R machinelearning-framework.R  
machinelearning-framework-theta.R machinelearning-utils.R  
machinelearning-functions-knn.R  
machinelearning-functions-ksvm.R machinelearning-functions-nb.R  
machinelearning-functions-nnet.R

machinelearning-functions-PerTurbo.R  
 machinelearning-functions-plsda.R  
 machinelearning-functions-rf.R machinelearning-functions-svm.R  
 machinelearning-functions-knntl.R belief.R distances.R  
 markers.R pRolocmarkers.R chi2.R MLInterfaces.R  
 clustering-framework.R MSnSet.R clustering-kmeans.R  
 perTurbo-algorithm.R data.R phenodisco.R plotting.R plotting2.R  
 environment.R utils.R lopims.R annotation.R goenv.R go.R  
 makeGoSet.R vis.R MartInterface.R zzz.R

**NeedsCompilation** yes

## R topics documented:

pRoloc-package . . . . .	3
addLegend . . . . .	4
addMarkers . . . . .	5
AnnotationParams-class . . . . .	6
checkFeatureNamesOverlap . . . . .	8
checkFvarOverlap . . . . .	9
chi2-methods . . . . .	10
empPvalues . . . . .	11
exprsToRatios-methods . . . . .	12
filterBinMSnSet . . . . .	12
filterZeroCols . . . . .	13
GenRegRes-class . . . . .	14
getGOFromFeatures . . . . .	16
getMarkerClasses . . . . .	17
getMarkers . . . . .	18
getPredictions . . . . .	19
goldToTerm . . . . .	20
highlightOnPlot . . . . .	21
knnClassification . . . . .	22
knnOptimisation . . . . .	23
knntlClassification . . . . .	24
knntlOptimisation . . . . .	25
ksvmClassification . . . . .	26
ksvmOptimisation . . . . .	27
lopims . . . . .	29
makeGoSet . . . . .	30
makeNaData . . . . .	31
markerMSnSet . . . . .	33
MartInstance-class . . . . .	34
minClassScore . . . . .	35
minMarkers . . . . .	36
MLearn-methods . . . . .	37
move2Ds . . . . .	37
mrkVecToMat . . . . .	39

nbClassification . . . . .	40
nbOptimisation . . . . .	41
ndist-methods . . . . .	42
nnetClassification . . . . .	43
nnetOptimisation . . . . .	44
perTurboClassification . . . . .	45
perTurboOptimisation . . . . .	47
phenoDisco . . . . .	48
plot2D . . . . .	50
plot2Ds . . . . .	52
plotDist . . . . .	54
plsdaClassification . . . . .	55
plsdaOptimisation . . . . .	56
pRolocmarkers . . . . .	57
rfClassification . . . . .	58
rfOptimisation . . . . .	59
sampleMSnSet . . . . .	60
setLisacol . . . . .	61
showGOEvidenceCodes . . . . .	62
SpatProtVis-class . . . . .	63
svmClassification . . . . .	65
svmOptimisation . . . . .	66
testMarkers . . . . .	67
testMSnSet . . . . .	68
thetas . . . . .	69
undocumented . . . . .	70
<b>Index</b>	<b>71</b>

---

pRoloc-package      *A unifying bioinformatics framework for spatial proteomics*

---

## Description

This package implements pattern recognition techniques on quantitative mass spectrometry data to infer protein sub-cellular localisation.

## Details

More details about the package are provided in the following vignettes

**pRoloc-ml** An overview of the machine learning techniques available in the pRoloc package.

**pRoloc-tutorial** The main pRoloc tutorial, providing a hands-on introduction to the package, including data requirements, visualisation, clustering, classification and the application of semi-supervised machine learning.

**pRoloc-transfer-learning** Description of a transfer learning algorithm for spatial proteomics.

**HUPO\_2011\_poster** HUPO 2011 poster: pRoloc - A unifying bioinformatics framework for organelle proteomics.

**HUPO\_2014\_poster** HUPO 2014 poster: A state-of-the-art machine learning pipeline for the analysis of spatial proteomics data.

If you have questions, want to report a bug or share suggestions, please file an issue at <https://github.com/lgatto/MSnbase/issues>, contact me directly or ask a question on the Bioconductor support forum <https://support.bioconductor.org/>.

### Author(s)

Laurent Gatto and Lisa M. Breckels with contributions from Thomas Burger and Samuel Wieczorek  
Maintainer: Laurent Gatto <lg390@cam.ac.uk>

### References

Gatto L, Breckels LM, Wieczorek S, Burger T, Lilley KS. Mass-spectrometry-based spatial proteomics data analysis using pRoloc and pRolocdata. *Bioinformatics*. 2014 May 1;30(9):1322-4. doi:10.1093/bioinformatics/btu013. Epub 2014 Jan 11. PubMed PMID: 24413670; PubMed Central PMCID: PMC3998135.

Breckels LM, Gatto L, Christoforou A, Groen AJ, Lilley KS, Trotter MW. The effect of organelle discovery upon sub-cellular protein localisation. *J Proteomics*. 2013 Mar 21. doi:pii: S1874-3919(13)00094-8. 10.1016/j.jprot.2013.02.019. PubMed PMID: 23523639.

Gatto L., Breckels L.M., Burger T, Nightingale D.J.H., Groen A.J., Campbell C., Mulvey C.M., Christoforou A., Ferro M., Lilley K.S. 'A foundation for reliable spatial proteomics data analysis' *Mol Cell Proteomics*. 2014 May 20.

### See Also

The underlying infrastructure to store and manipulate the quantitative data is implemented in the MSnbase package. See [MSnbase](#) to get started.

---

addLegend

*Adds a legend*

---

### Description

Adds a legend to a [plot2D](#) figure.

### Usage

```
addLegend(object, fcol = "markers", where = c("other", "bottomright",  
      "bottom", "bottomleft", "left", "topleft", "top", "topright", "right",  
      "center"), col, bty = "n", ...)
```

**Arguments**

object	An instance of class MSnSet
fcol	Feature meta-data label (fData column name) defining the groups to be differentiated using different colours. Default is markers.
where	One of "other", "bottomleft", "bottomright", "topleft" or "topright" defining the location of the legend. "other" opens a new graphics device, while the other locations are passed to <a href="#">legend</a> .
col	A character defining point colours.
bty	Box type, as in legend. Default is set to "n".
...	Additional parameters passed to <a href="#">legend</a> .

**Details**

The function has been updated in version 1.3.6 to recycle the default colours when more organelle classes are provided. See [plot2D](#) for details.

**Value**

Invisibly returns NULL

**Author(s)**

Laurent Gatto

---

addMarkers	<i>Adds markers to the data</i>
------------	---------------------------------

---

**Description**

The function adds a 'markers' feature variable. These markers are read from a comma separated values (csv) spreadsheet file. This markers file is expected to have 2 columns (others are ignored) where the first is the name of the marker features and the second the group label. Alternatively, a markers named vector as provided by the [pRolocmarkers](#) function can also be used.

**Usage**

```
addMarkers(object, markers, mcol = "markers", fcol, verbose = TRUE)
```

**Arguments**

object	An instance of class MSnSet.
markers	A character with the name the markers' csv file or a named character of markers as provided by <a href="#">pRolocmarkers</a> .
mcol	A character of length 1 defining the feature variable label for the newly added markers. Default is "markers".

fcol	An optional feature variable to be used to match against the markers. If missing, the feature names are used.
verbose	A logical indicating if number of markers and marker table should be printed to the console.

### Details

It is essential to assure that `featureNames(object)` (or `fcol`, see below) and marker names (first column) match, i.e. the same feature identifiers and case fold are used.

### Value

A new instance of class `MSnSet` with an additional markers feature variable.

### Author(s)

Laurent Gatto

### See Also

See [pRolocmarkers](#) for a list of spatial markers and [markers](#) for details about markers encoding.

### Examples

```
library("pRolocdata")
data(dunkley2006)
atha <- pRolocmarkers("atha")
try(addMarkers(dunkley2006, atha)) ## markers already exists
fData(dunkley2006)$markers.org <- fData(dunkley2006)$markers
fData(dunkley2006)$markers <- NULL
marked <- addMarkers(dunkley2006, atha)
fvarLabels(marked)
## if 'makers' already exists
marked <- addMarkers(marked, atha, mcol = "markers2")
fvarLabels(marked)
stopifnot(all.equal(fData(marked)$markers, fData(marked)$markers2))
plot2D(marked)
addLegend(marked, where = "topleft", cex = .7)
```

---

AnnotationParams-class

*Class "AnnotationParams"*

---

### Description

Class to store annotation parameters to automatically query a Biomart server, retrieve relevant annotation for a set of features of interest using, for example [getGOFromFeatures](#) and [makeGoSet](#).

## Objects from the Class

Objects can be created and set with the `setAnnotationParams` function. Object are created by calling without any arguments `setAnnotationParams()`, which will open an interactive interface. Depending on the value of `"many.graphics"` option, a graphical of a text-based menu will open (the text interface can be forced by setting the `graphics` argument to `FALSE`: `setAnnotationParams(graphics = FALSE)`). The menu will allow to select the species of interest first and the type of features (ENSEMBL gene identifier, Entrez id, ...) second.

The species that are available are those for which ENSEMBL data is available in Biomart and have a set of attributes of interest available. The compatible identifiers for downstream queries are then automatically filtered and displayed for user selection.

It is also possible to pass a parameter `inputs`, a character vector of length 2 containing a pattern uniquely matching the species of interest (in position 1) and a patterns uniquely matching the feature types (in position 2). If the matches are not unique, an error will be thrown.

A new instance of the `AnnotationParams` will be created to enable easy and automatic query of the `Mart` instance. The instance is invisibly returned and stored in a global variable in the **pRoloc** package's private environment for automatic retrieval. If a variable containing an `AnnotationParams` instance is already available, it can be set globally by passing it as argument to the `setAnnotationParams` function. Globally set `AnnotationParams` instances can be accessed with the `getAnnotationParams` function.

See the `pRoloc-theta` vignette for details.

## Slots

`mart`: Object of class "Mart" from the **biomaRt** package.

`martname`: Object of class "character" with the name of the `mart` instance.

`dataset`: Object of class "character" with the data set of the `mart` instance.

`filter`: Object of class "character" with the filter to be used when querying the `mart` instance.

`date`: Object of class "character" indicating when the current instance was created.

`biomaRtVersion`: Object of class "character" with the **biomaRt** version used to create the `AnnotationParams` instance.

`.__classVersion__`: Object of class "Versions" with the version of the `AnnotationParams` class of the current instance.

## Methods

`show` `signature(object = "AnnotationParams")`: to display objects.

## Author(s)

Laurent Gatto <lg390@cam.ac.uk>

## See Also

[getGOFromFeatures](#), [makeGoSet](#) and the `pRoloc-theta` vignette.

## Examples

```
data(andy2011params)
andy2011params
data(dunkley2006params)
dunkley2006params

try(setAnnotationParams(inputs = c("nomatch1", "nomatch2")))
setAnnotationParams(inputs = c("Homo sapiens",
                               "UniProt/Swissprot Accession"))
getAnnotationParams()
```

---

```
checkFeatureNamesOverlap
      Check feature names overlap
```

---

## Description

Checks the marker and unknown feature overlap of two MSnSet instances.

## Usage

```
checkFeatureNamesOverlap(x, y, fcolx = "markers", fcoly, verbose = TRUE)
```

## Arguments

x	An MSnSet instance.
y	An MSnSet instance.
fcolx	The feature variable to separate unknown (fData(y)\$fcoly == "unknown") from the marker features in the x object.
fcoly	As fcolx, for the y object. If missing, the value of fcolx is used.
verbose	If TRUE (default), the overlap is printed out on the console.

## Value

Invisibly returns a named list of common markers, unique x markers, unique y markers in, common unknowns, unique x unknowns and unique y unknowns.

## Author(s)

Laurent Gatto





## Description

In the original protein correlation profiling (PCP), Andersen et al. use the peptide normalised profiles along gradient fractions and compared them with the reference profiles (or set of profiles) by computing  $Chi^2$  values,  $\frac{\sum(x_i - x_p)^2}{x_p}$ , where  $x_i$  is the normalised value of the peptide in fraction  $i$  and  $x_p$  is the value of the marker (from Wiese et al., 2007). The protein  $Chi^2$  is then computed as the median of the peptide  $Chi^2$  values. Peptides and proteins with similar profiles to the markers will have small  $Chi^2$  values.

The chi2 methods implement this idea and compute such  $Chi^2$  values for sets of proteins.

## Methods

signature(x = "matrix", y = "matrix", method = "character", fun = "NULL", na.rm = "logical")

Compute nrow(x) times nrow(y)  $Chi^2$  values, for each x, y feature pair. Method is one of "Andersen2003" or "Wiese2007"; the former (default) computed the  $Chi^2$  as  $\sum(y-x)^2/\text{length}(x)$ , while the latter uses  $\sum((y-x)^2/x)$ . na.rm defines if missing values (NA and NaN) should be removed prior to summation. fun defines how to summarise the  $Chi^2$  values; default, NULL, does not combine the  $Chi^2$  values.

signature(x = "matrix", y = "numeric", method = "character", na.rm = "logical")

Computes nrow(x)  $Chi^2$  values, for all the  $(x_i, y)$  pairs. See above for the other arguments.

signature(x = "numeric", y = "matrix", method = "character", na.rm = "logical")

Computes nrow(y)  $Chi^2$  values, for all the  $(x, y_i)$  pairs. See above for the other arguments.

signature(x = "numeric", y = "numeric", method = "character", na.rm = "logical")

Computes the  $Chi^2$  value for the  $(x, y)$  pairs. See above for the other arguments.

## Author(s)

Laurent Gatto <lg390@cam.ac.uk>

## References

Andersen, J. S., Wilkinson, C. J., Mayor, T., Mortensen, P. et al., Proteomic characterization of the human centrosome by protein correlation profiling. *Nature* 2003, 426, 570 - 574.

Wiese, S., Gronemeyer, T., Ofman, R., Kunze, M. et al., Proteomics characterization of mouse kidney peroxisomes by tandem mass spectrometry and protein correlation profiling. *Mol. Cell. Proteomics* 2007, 6, 2045 - 2057.

## See Also

[empPvalues](#)

## Examples

```
mrk <- rnorm(6)
prot <- matrix(rnorm(60), ncol = 6)
chi2(mrk, prot, method = "Andersen2003")
chi2(mrk, prot, method = "Wiese2007")

pepmark <- matrix(rnorm(18), ncol = 6)
pepprot <- matrix(rnorm(60), ncol = 6)
chi2(pepmark, pepprot)
chi2(pepmark, pepprot, fun = sum)
```

---

empPvalues

*Estimate empirical p-values for  $Chi^2$  protein correlations.*

---

## Description

Andersen et al. (2003) used a fixed  $Chi^2$  threshold of 0.05 to identify organelle-specific candidates. This function computes empirical p-values by permutation the markers relative intensities and computed null  $Chi^2$  values.

## Usage

```
empPvalues(marker, corMatrix, n = 100, ...)
```

## Arguments

marker	A numerics with markers relative intensities.
corMatrix	A matrix of <code>nrow(corMatrix)</code> protein relative intensities to be compares against the marker.
n	The number of iterations.
...	Additional parameters to be passed to <code>chi2</code> .

## Value

A numeric of length `nrow(corMatrix)`.

## Author(s)

Laurent Gatto <lg390@cam.ac.uk>

## References

Andersen, J. S., Wilkinson, C. J., Mayor, T., Mortensen, P. et al., Proteomic characterization of the human centrosome by protein correlation profiling. Nature 2003, 426, 570 - 574.

## See Also

[chi2](#) for  $Chi^2$  calculation.

**Examples**

```

set.seed(1)
mrk <- rnorm(6, 5, 1)
prot <- rbind(matrix(rnorm(120, 5, 1), ncol = 6),
               mrk + rnorm(6))
mrk <- mrk/sum(mrk)
prot <- prot/rowSums(prot)
empPvalues(mrk, prot)

```

---

exprsToRatios-methods *Calculate all ratio pairs*

---

**Description**

Calculations all possible ratios for the assayData columns in an "MSnSet".

**Methods**

signature(object = "MSnSet", log = "logical") If log is FALSE (default) the ratios for all the assayData columns are computed; otherwise, log ratios (differences) are calculated.

**Examples**

```

library("pRolocdata")
data(dunkley2006)
x <- dunkley2006[, 1:3]
head(exprs(x))
r <- exprsToRatios(x)
head(exprs(r))
pData(r)

```

---

filterBinMSnSet *Filter a binary MSnSet*

---

**Description**

Removes columns or rows that have a certain proportion or absolute number of 0 values.

**Usage**

```
filterBinMSnSet(object, MARGIN = 2, t, q, verbose = TRUE)
```

**Arguments**

object	An MSnSet
MARGIN	1 or 2. Default is 2.
t	Rows/columns that have t or less 1s, it will be filtered out. When t and q are missing, default is to use t = 1.
q	If a row has a higher quantile than defined by q, it will be filtered out.
verbose	A logical defining of a message is to be printed. Default is TRUE.

**Value**

A filtered MSnSet.

**Author(s)**

Laurent Gatto

**Examples**

```
set.seed(1)
m <- matrix(sample(0:1, 25, replace=TRUE), 5)
m[1, ] <- 0
m[, 1] <- 0
rownames(m) <- colnames(m) <- letters[1:5]
fd <- data.frame(row.names = letters[1:5])
x <- MSnSet(exprs = m, fData = fd, pData = fd)
exprs(x)
## Remove columns with no 1s
exprs(filterBinMSnSet(x, MARGIN = 2, t = 0))
## Remove columns with one 1 or less
exprs(filterBinMSnSet(x, MARGIN = 2, t = 1))
## Remove columns with two 1s or less
exprs(filterBinMSnSet(x, MARGIN = 2, t = 2))
## Remove columns with three 1s
exprs(filterBinMSnSet(x, MARGIN = 2, t = 3))
## Remove columns that have half or less of 1s
exprs(filterBinMSnSet(x, MARGIN = 2, q = 0.5))
```

---

filterZeroCols

*Remove 0 columns/rows*

---

**Description**

Removes all assay data columns/rows that are composed of only 0, i.e. have a colSum/rowSum of 0.

**Usage**

```
filterZeroCols(object, verbose = TRUE)
```

```
filterZeroRows(object, verbose = TRUE)
```

**Arguments**

object            A MSnSet object.  
 verbose          Print a message with the number of filtered out columns/row (if any).

**Value**

An MSnSet.

**Author(s)**

Laurent Gatto

**Examples**

```
library("pRolocdata")
data(andy2011goCC)
any(colSums(exprs(andy2011goCC)) == 0)
exprs(andy2011goCC)[, 1:5] <- 0
ncol(andy2011goCC)
ncol(filterZeroCols(andy2011goCC))
```

---

GenRegRes-class

*Class "GenRegRes" and "ThetaRegRes"*

---

**Description**

Regularisation framework containers.

**Objects from the Class**

Object of this class are created with the respective regularisation function: [knnOptimisation](#), [svmOptimisation](#), [plsdaOptimisation](#), [knnt1Optimisation](#), ...

**Slots**

**algorithm:** Object of class "character" storing the machine learning algorithm name.  
**hyperparameters:** Object of class "list" with the respective algorithm hyper-parameters tested.  
**design:** Object of class "numeric" describing the cross-validation design, the test data size and the number of replications.  
**log:** Object of class "list" with warnings thrown during the hyper-parameters regularisation.  
**seed:** Object of class "integer" with the random number generation seed.  
**results:** Object of class "matrix" of dimensions times (see design) by number of hyper-parameters + 1 storing the macro F1 values for the respective best hyper-parameters for each replication.  
**f1Matrices:** Object of class "list" with respective times cross-validation F1 matrices.

**cmMatrices:** Object of class "list" with respective times contingency matrices.

**testPartitions:** Object of class "list" with respective times test partitions.

**datasize:** Object of class "list" with details about the respective inner and outer training and testing data sizes.

Only in ThetaRegRes:

**predictions:** A list of predictions for the optimisation iterations.

**otherWeights:** Alternative best theta weights: a vector per iterations, NULL if no other best weights were found.

## Methods

**getF1Scores** Returns a matrix of F1 scores for the optimisation parameters.

**f1Count** signature(object = "GenRegRes", t = "numeric") and signature(object = "ThetaRegRes", t = "numeric"): Constructs a table of all possible parameter combination and count how many have an F1 scores greater or equal than t. When t is missing (default), the best F1 score is used. This method is useful in conjunctin with plot.

**getParams** Returns the *best* parameters. It is however strongly recommended to inspect the optimisation results. For a ThetaRegRes optimisation result, the method to chose the best parameters can be "median" (default) or "mean" (the median or mean of the best weights is chosen), "max" (the first weights with the highest macro-F1 score, considering that multiple max scoring combinations are possible) or "count" (the observed weight that get the maximum number of observations, see f1Count). The favourP argument can be used to prioritise weights that favour the primary data (i.e. heigh weights). See favourPrimary below.

**getSeed** Returns the seed used for the optimisation run.

**getWarnings** signature(object = "GenRegRes"): Returns a vector of recorded warnings.

**levelPlot** signature(object = "GenRegRes"): Plots a heatmap of of the optimisation results. Only for "GenRegRes" instances.

**plot** Plots the optimisation results.

**show** Shows the object.

## Other functions

Only for ThetaRegRes:

**combineThetaRegRes(object)** Takes a list of ThetaRegRes instances to be combined and returns a new ThetaRegRes instance.

**favourPrimary(primary, auxiliary, object, verbose = TRUE)** Takes the primary and auxiliary data sources (two [MSnSet](#) instances) and a ThetaRegRes object and returns and updated ThetaRegRes instance containing best parameters/weights (see the `getParams` function) favouring the primary data when multiple best theta weights are available.

## Author(s)

Laurent Gatto <lg390@cam.ac.uk>

**Examples**

```
showClass("GenRegRes")
showClass("ThetaRegRes")
```

---

getGOFromFeatures	<i>Retrieve GO terms for feature names</i>
-------------------	--

---

**Description**

The function pulls the gene ontology (GO) terms for a set of feature names.

**Usage**

```
getGOFromFeatures(id, namespace = "cellular_component", evidence = NULL,
  params = NULL, verbose = FALSE)
```

**Arguments**

id	An character with feature names to be pulled from biomart. If and MSnSet is provided, then featureNames(id) is used.
namespace	The GO namespace. One of biological_process, cellular_component (default) or molecular_function.
evidence	The GO evidence code. See showGOEvidenceCodes for details. If NULL (default), no filtering based on the evidence code is performed.
params	An instance of class " <a href="#">AnnotationParams</a> ".
verbose	A logical defining verbosity of the function. Default is FALSE.

**Value**

A data.frame with relevant GO terms.

**Author(s)**

Laurent Gatto

**Examples**

```
library(pRolocdata)
data(dunkley2006)
data(dunkley2006params)
dunkley2006params
fn <- featureNames(dunkley2006)[1:5]
getGOFromFeatures(fn, params = dunkley2006params)
```



---

getMarkerClasses	<i>Returns the organelle classes in an 'MSnSet'</i>
------------------	---

---

## Description

Convenience accessor to the organelle classes in an 'MSnSet'. This function returns the organelle classes of an MSnSet instance. As a side effect, it prints out the classes.

## Usage

```
getMarkerClasses(object, fcol = "markers", verbose = TRUE, ...)
```

## Arguments

object	An instance of class " <a href="#">MSnSet</a> ".
fcol	The name of the markers column in the featureData slot. Default is markers.
verbose	If TRUE, a character vector of the organelle classes is printed and the classes are returned invisibly. If FALSE, the markers are returned.
...	Additional parameters passed to sort from the base package.

## Value

A character vector of the organelle classes in the data.

## Author(s)

Lisa Breckels and Laurent Gatto

## See Also

[getMarkers](#) to extract the marker proteins. See [markers](#) for details about spatial markers storage and encoding.

## Examples

```
library("pRolocdata")
data(dunkley2006)
organelles <- getMarkerClasses(dunkley2006)
## same if markers encoded as a matrix
dunkley2006 <- mrkVecToMat(dunkley2006, mfcol = "Markers")
organelles2 <- getMarkerClasses(dunkley2006, fcol = "Markers")
stopifnot(all.equal(organelles, organelles2))
```

---

getMarkers	<i>Get the organelle markers in an MSnSet</i>
------------	---

---

### Description

Convenience accessor to the organelle markers in an MSnSet. This function returns the organelle markers of an MSnSet instance. As a side effect, it print out a marker table.

### Usage

```
getMarkers(object, fcol = "markers", names = TRUE, verbose = TRUE)
```

### Arguments

object	An instance of class "MSnSet".
fcol	The name of the markers column in the featureData slot. Default is "markers".
names	A logical indicating if the markers vector should be named. Ignored if markers are encoded as a matrix.
verbose	If TRUE, a marker table is printed and the markers are returned invisibly. If FALSE, the markers are returned.

### Value

A character (matrix) of length (ncol) ncol(object), depending on the vector or matrix encoding of the markers.

### Author(s)

Laurent Gatto

### See Also

See [getMarkerClasses](#) to get the classes only. See [markers](#) for details about spatial markers storage and encoding.

### Examples

```
library("pRolocdata")
data(dunkley2006)
## marker vectors
myVmarkers <- getMarkers(dunkley2006)
head(myVmarkers)
## marker matrix
dunkley2006 <- mrkVecToMat(dunkley2006, mfcol = "Markers")
myMmarkers <- getMarkers(dunkley2006, fcol = "Markers")
head(myMmarkers)
```

---

getPredictions	Returns the predictions in an 'MSnSet'
----------------	--

---

## Description

Convenience accessor to the predicted feature localisation in an 'MSnSet'. This function returns the predictions of an MSnSet instance. As a side effect, it prints out a prediction table.

## Usage

```
getPredictions(object, fcol, scol, t = 0, verbose = TRUE)
```

## Arguments

object	An instance of class "MSnSet".
fcol	The name of the prediction column in the featureData slot.
scol	The name of the prediction score column in the featureData slot. If missing, created by pasting '.scores' after fcol.
t	The score threshold. Predictions with score < t are set to 'unknown'. Default is 0. It is also possible to define thresholds for each prediction class, in which case, t is a named numeric with names exactly matching the unique prediction class names.
verbose	If TRUE, a prediction table is printed and the predictions are returned invisibly. If FALSE, the predictions are returned.

## Value

A character of length ncol(object).

## Author(s)

Laurent Gatto

## Examples

```
library("pRolocdata")
data(dunkley2006)
res <- svmClassification(dunkley2006, fcol = "pd.markers",
                        sigma = 0.1, cost = 0.5)
fData(res)$svm[500:510]
fData(res)$svm.scores[500:510]
getPredictions(res, fcol = "svm", t = 0) ## all predictions
getPredictions(res, fcol = "svm", t = .9) ## single threshold
## 50% top predictions per class
(ts <- tapply(fData(res)$svm.scores, fData(res)$svm, median))
getPredictions(res, fcol = "svm", t = ts)
## 50% top predictions per class, ignoring marker scores
```

```
ts <- tapply(fData(res)$svm.scores, fData(res)$svm,
            function(x) {
              scr <- median(x[x != 1])
              ifelse(is.na(scr), 1, scr)
            })
ts
getPredictions(res, fcol = "svm", t = ts)
```

---

goIdToTerm

*Convert GO ids to/from terms*


---

### Description

Converts GO identifiers to/from GO terms, either explicitly or by checking if (any items in) the input contains "GO:".

### Usage

```
goIdToTerm(x, names = TRUE)
```

```
goTermToId(x, names = TRUE)
```

```
flipGoTermId(x, names = TRUE)
```

```
prettyGoTermId(x)
```

### Arguments

x                    A character of GO ids or terms.  
names                Should a named character be returned? Default is TRUE.

### Value

A character of GO terms (ids) if x were ids (terms).

### Author(s)

Laurent Gatto

### Examples

```
goIdToTerm("GO:0000001")
goIdToTerm("GO:0000001", names = FALSE)
goIdToTerm(c("GO:0000001", "novalid"))
goIdToTerm(c("GO:0000001", "GO:0000002", "notvalid"))
goTermToId("mitochondrion inheritance")
goTermToId("mitochondrion inheritance", name = FALSE)
goTermToId(c("mitochondrion inheritance", "notvalid"))
prettyGoTermId("mitochondrion inheritance")
```

```
prettyGoTermId("GO:0000001")
flipGoTermId("mitochondrion inheritance")
flipGoTermId("GO:0000001")
flipGoTermId("GO:0000001", names = FALSE)
```

---

highlightOnPlot	<i>Highlight features of interest on a plot2D figure</i>
-----------------	--

---

## Description

Highlights a set of features of interest given as a `FeaturesOfInterest` instance on a PCA plot produced by `codeplot2D`. If none of the features of interest are found in the `MSnset`'s `featureNames`, an error is thrown.

## Usage

```
highlightOnPlot(object, foi, labels, args = list(),...)
```

## Arguments

<code>object</code>	The main dataset described as an <code>MSnSet</code> or a matrix with the coordinates of the features on the PCA plot produced (and invisibly returned) by <code>plot2D</code> .
<code>foi</code>	An instance of <code>FeaturesOfInterest</code> .
<code>labels</code>	A character of length 1 with a feature variable name to be used to label the features of interest. Default is missing.
<code>args</code>	A named list of arguments to be passed to <code>plot2D</code> if the PCA coordinates are to be calculated. Ignored if the PCA coordinates are passed directly, i.e. <code>object</code> is a matrix.
<code>...</code>	Additional parameters passed to <code>points</code> .

## Value

NULL; used for its side effects.

## Author(s)

Laurent Gatto

## Examples

```
library("pRolocdata")
data("tan2009r1")
x <- FeaturesOfInterest(description = "A test set of features of interest",
                        fnames = featureNames(tan2009r1)[1:10],
                        object = tan2009r1)
.pca <- plot2D(tan2009r1)
highlightOnPlot(.pca, x, col = "red")
```

```

highlightOnPlot(tan2009r1, x, col = "red", cex = 1.5)

.pca <- plot2D(tan2009r1, dims = c(1, 3))
head(.pca)
highlightOnPlot(.pca, x, pch = "+")
highlightOnPlot(tan2009r1, x, args = list(dims = c(1, 3)))

plot2D(tan2009r1, mirrorX = TRUE)
highlightOnPlot(.pca, x, pch = "+", args = list(mirrorX = TRUE))
## regenerate without recomputing
plot2D(tan2009r1, method = .pca)

```

---

knnClassification      *knn classification*

---

## Description

Classification using for the k-nearest neighbours algorithm.

## Usage

```
knnClassification(object, assessRes, scores = c("prediction", "all", "none"),
  k, fcol = "markers", ...)
```

## Arguments

object	An instance of class " <a href="#">MSnSet</a> ".
assessRes	An instance of class " <a href="#">GenRegRes</a> ", as generated by <a href="#">knnOptimisation</a> .
scores	One of "prediction", "all" or "none" to report the score for the predicted class only, for all cluster or none.
k	If assessRes is missing, a k must be provided.
fcol	The feature meta-data containing marker definitions. Default is markers.
...	Additional parameters passed to <a href="#">knn</a> from package <a href="#">class</a> .

## Value

An instance of class "[MSnSet](#)" with `knn` and `knn.scores` feature variables storing the classification results and scores respectively.

## Author(s)

Laurent Gatto

**Examples**

```

library(pRolocdata)
data(dunkley2006)
## reducing parameter search space and iterations
params <- knnOptimisation(dunkley2006, k = c(3, 10), times = 3)
params
plot(params)
f1Count(params)
levelPlot(params)
getParams(params)
res <- knnClassification(dunkley2006, params)
getPredictions(res, fcol = "knn")
getPredictions(res, fcol = "knn", t = 0.75)
plot2D(res, fcol = "knn")

```

---

knnOptimisation	<i>knn parameter optimisation</i>
-----------------	-----------------------------------

---

**Description**

Classification parameter optimisation for the k-nearest neighbours algorithm.

**Usage**

```

knnOptimisation(object, fcol = "markers", k = seq(3, 15, 2), times = 100,
  test.size = 0.2, xval = 5, fun = mean, seed, verbose = TRUE, ...)

```

**Arguments**

object	An instance of class " <a href="#">MSnSet</a> ".
fcol	The feature meta-data containing marker definitions. Default is markers.
k	The hyper-parameter. Default values are seq(3, 15, 2).
times	The number of times internal cross-validation is performed. Default is 100.
test.size	The size of test data. Default is 0.2 (20 percent).
xval	The n-cross validation. Default is 5.
fun	The function used to summarise the xval macro F1 matrices.
seed	The optional random number generator seed.
verbose	A logical defining whether a progress bar is displayed.
...	Additional parameters passed to <a href="#">knn</a> from package <a href="#">class</a> .

**Details**

Note that when performance scores precision, recall and (macro) F1 are calculated, any NA values are replaced by 0. This decision is motivated by the fact that any class that would have either a NA precision or recall would result in an NA F1 score and, eventually, a NA macro F1 (i.e. mean(F1)). Replacing NAs by 0s leads to F1 values of 0 and a reduced yet defined final macro F1 score.

**Value**

An instance of class "[GenRegRes](#)".

**Author(s)**

Laurent Gatto

**See Also**

[knnClassification](#) and example therein.

---

knnt1Classification    *knn transfer learning classification*

---

**Description**

Classification using a variation of the KNN implementation of Wu and Dietterich's transfer learning schema

**Usage**

```
knnt1Classification(primary, auxiliary, fcol = "markers", bestTheta, k,
  scores = c("prediction", "all", "none"))
```

**Arguments**

primary	An instance of class " <a href="#">MSnSet</a> ".
auxiliary	An instance of class " <a href="#">MSnSet</a> ".
fcol	The feature meta-data containing marker definitions. Default is markers.
bestTheta	Best theta vector as output from <a href="#">knnt1Optimisation</a> , see <a href="#">knnt1Optimisation</a> for details
k	Numeric vector of length 2, containing the best k parameters to use for the primary and auxiliary datasets. If k k is not specified it will be calculated internally.
scores	One of "prediction", "all" or "none" to report the score for the predicted class only, for all cluster or none.

**Value**

A character vector of the classifications for the unknowns

**Author(s)**

Lisa Breckels

**See Also**

[knnt1Optimisation](#)



**Examples**

```

library(pRoclocdata)
data(andy2011)
data(andy2011goCC)
## reducing calculation time of k by pre-running knnOptimisation
x <- c(andy2011, andy2011goCC)
k <- lapply(x, function(z)
            knnOptimisation(z, times=5,
                           fcol = "markers.orig",
                           verbose = FALSE))
k <- sapply(k, function(z) getParams(z))
k
## reducing parameter search with theta = 1,
## weights of only 1 or 0 will be considered
opt <- knnt1Optimisation(andy2011, andy2011goCC,
                        fcol = "markers.orig",
                        times = 2,
                        by = 1, k = k)

opt
th <- getParams(opt)
plot(opt)
res <- knnt1Classification(andy2011, andy2011goCC,
                           fcol = "markers.orig", th, k)

res

```

---

knnt1Optimisation      *theta parameter optimisation*

---

**Description**

Classification parameter optimisation for the KNN implementation of Wu and Dietterich's transfer learning schema

**Usage**

```

knnt1Optimisation(primary, auxiliary, fcol = "markers", k, times = 50,
                  test.size = 0.2, xval = 5, by = 0.5, length.out, th, xfolds,
                  BPPARAM = BiocParallel::bpparam())

```

**Arguments**

primary	An instance of class "MSnSet".
auxiliary	An instance of class "MSnSet".
fcol	The feature meta-data containing marker definitions. Default is markers.

<code>k</code>	Numeric vector of length 2, containing the best k parameters to use for the primary ( <code>k[1]</code> ) and auxiliary ( <code>k[2]</code> ) datasets. See <code>knnOptimisation</code> for generating best k.
<code>times</code>	The number of times cross-validation is performed. Default is 50.
<code>test.size</code>	The size of test (validation) data. Default is 0.2 (20 percent).
<code>xval</code>	The number of rounds of cross-validation to perform.
<code>by</code>	The increment for theta, must be one of <code>c(1, 0.5, 0.25, 0.2, 0.15, 0.1, 0.05)</code>
<code>length.out</code>	Alternative to using <code>by</code> parameter. Specifies the desired length of the sequence of theta to test.
<code>th</code>	A matrix of theta values to test for each class as generated from the function <a href="#">thetas</a> , the number of columns should be equal to the number of classes contained in <code>fcol</code> . Note: columns will be ordered according to <code>getMarkerClasses(primary, fcol)</code> .
<code>xfolds</code>	Option to pass specific folds for the cross validation.
<code>BPPARAM</code>	Required for parallelisation. If not specified selects a default <code>BiocParallelParam</code> , from global options or, if that fails, the most recently registered() back-end.

### Details

`knnt1Optimisation` implements a variation of Wu and Dietterich's transfer learning schema: P. Wu and T. G. Dietterich. Improving SVM accuracy by training on auxiliary data sources. In Proceedings of the Twenty-First International Conference on Machine Learning, pages 871 - 878. Morgan Kaufmann, 2004. A grid search for the best theta is performed.

### Value

A list of containing the theta combinations tested, associated macro F1 score and accuracy for each combination over each round (specified by `times`).

### Author(s)

Lisa Breckels

### See Also

[knnt1Classification](#) and example therein.

---

`ksvmClassification`      *ksvm classification*

---

### Description

Classification using the support vector machine algorithm.

**Usage**

```
ksvmClassification(object, assessRes, scores = c("prediction", "all", "none"),
  cost, fcol = "markers", ...)
```

**Arguments**

object	An instance of class "MSnSet".
assessRes	An instance of class "GenRegRes", as generated by <code>ksvmOptimisation</code> .
scores	One of "prediction", "all" or "none" to report the score for the predicted class only, for all cluster or none.
cost	If assessRes is missing, a cost must be provided.
fcol	The feature meta-data containing marker definitions. Default is markers.
...	Additional parameters passed to <code>ksvm</code> from package kernlab.

**Value**

An instance of class "MSnSet" with `ksvm` and `ksvm.scores` feature variables storing the classification results and scores respectively.

**Author(s)**

Laurent Gatto

**Examples**

```
library(pRoclocdata)
data(dunkley2006)
## reducing parameter search space and iterations
params <- ksvmOptimisation(dunkley2006, cost = 2^seq(-1,4,5), times = 3)
params
plot(params)
f1Count(params)
levelPlot(params)
getParams(params)
res <- ksvmClassification(dunkley2006, params)
getPredictions(res, fcol = "ksvm")
getPredictions(res, fcol = "ksvm", t = 0.75)
plot2D(res, fcol = "ksvm")
```

---

ksvmOptimisation

*ksvm parameter optimisation*

---

**Description**

Classification parameter optimisation for the support vector machine algorithm.

**Usage**

```
ksvmOptimisation(object, fcol = "markers", cost = 2^(-4:4), times = 100,  
  test.size = 0.2, xval = 5, fun = mean, seed, verbose = TRUE, ...)
```

**Arguments**

object	An instance of class " <a href="#">MSnSet</a> ".
fcol	The feature meta-data containing marker definitions. Default is markers.
cost	The hyper-parameter. Default values are $2^{-4:4}$ .
times	The number of times internal cross-validation is performed. Default is 100.
test.size	The size of test data. Default is 0.2 (20 percent).
xval	The n-cross validation. Default is 5.
fun	The function used to summarise the xval macro F1 matrices.
seed	The optional random number generator seed.
verbose	A logical defining whether a progress bar is displayed.
...	Additional parameters passed to <a href="#">ksvm</a> from package kernlab.

**Details**

Note that when performance scores precision, recall and (macro) F1 are calculated, any NA values are replaced by 0. This decision is motivated by the fact that any class that would have either a NA precision or recall would result in an NA F1 score and, eventually, a NA macro F1 (i.e.  $\text{mean}(F1)$ ). Replacing NAs by 0s leads to F1 values of 0 and a reduced yet defined final macro F1 score.

**Value**

An instance of class "[GenRegRes](#)".

**Author(s)**

Laurent Gatto

**See Also**

[ksvmClassification](#) and example therein.

---

lopims	<i>A complete LOPIMS pipeline</i>
--------	-----------------------------------

---

### Description

The function processes MSe data using the [synergise](#) function of the [synapter](#) package and combines resulting [Synapter](#) instances into one "MSnSet" and organelle marker data is added as a feature-level annotation variable.

### Usage

```
lopims(hdmsedir = "HDMSE", msedir = "MSE", pep3ddir = "pep3D", fastafile,  
markerfile, mfdR = 0.025, ...)
```

### Arguments

hdmsedir	A character identifying the directory containing the HDMSe final peptide files. Default is HDMSe.
msedir	A character identifying the directory containing the MSe final peptide files. Default is MSe.
pep3ddir	A character identifying the directory containing the MSe pep 3D files. Default is pep3D.
fastafile	A character identifying the protein fasta database. Default is to use the fasta file in the current directory. If several such files exist, the function reports an error.
markerfile	A character identifying the marker file (see details for format). Default is to use a csv file starting with marker in the current directory. If several such files exist, the function reports an error.
mfdR	The master FDR value. Default is 0.025.
...	Additional parameters passed to <a href="#">synergise</a> .

### Details

The LOPIMS pipeline is composed of 5 steps:

1. The HDMSe final peptide files are used to compute false discovery rates upon all possible combinations of HDMSe final peptides files and the best combination smaller or equal to mfdR is chosen. See [estimateMasterFdr](#) for details. The corresponding master run is then created as described in [makeMaster](#). (function `lopims1`)
2. Each MSe/pep3D pair is processed using the HDMSe master file using [synergise](#). (function `lopims2`)
3. The respective peptide-level synergise output objects are converted and combined into an single "MSnSet" instance. (function `lopims3`)

4. Protein-level quantitation is inferred as follows. For each protein, a reference sample/fraction is chosen based on the number of missing values (NA). If several samples have a same minimal number of NAs, ties are broken using the sum of counts. The peptides that do not display any missing values for each (frac\_i, frac\_ref) pair are summed and the ratio is reported (see `pRoloc:::refNormMeanOfNonNAPepSum` for details). (function `lopims4`)
5. The markers defined in the markerfile are collated as feature meta-data in the markers variable. See `addMarkers` for details. (function `lopims5`)

Intermediate synergise reports as well as resulting objects are stored in a `LOPIMS_pipeline` directory. For details, please refer to the synapter vignette and reference papers.

### Value

An instance of class "`MSnSet`" with protein level quantitation and respective organelle markers.

### Author(s)

Laurent Gatto

### References

Improving qualitative and quantitative performance for MSE-based label free proteomics N.J. Bond, P.V. Shliaha, K.S. Lilley and L. Gatto *Journal of Proteome Research*, 2013;12(6):2340-53. PMID: 23510225.

The Effects of Travelling Wave Ion Mobility Separation on Data Independent Acquisition in Proteomics Studies P.V. Shliaha, N.J. Bond, L. Gatto and K.S. Lilley *Journal of Proteome Research*, 2013;12(6):2323-39. PMID: 23514362.

MSnbase-an R/Bioconductor package for isobaric tagged mass spectrometry data visualization, processing and quantitation. L. Gatto and KS. Lilley. *Bioinformatics*. 2012 Jan 15;28(2):288-9. doi: 10.1093/bioinformatics/btr645. Epub 2011 Nov 22. PubMed PMID: 22113085.

---

makeGoSet

*Creates a GO feature MSnSet*

---

### Description

Creates a new "`MSnSet`" instance populated with a GO term binary matrix based on an original object.

### Usage

```
makeGoSet(object, params, namespace = "cellular_component", evidence = NULL)
```

**Arguments**

object	An instance of class "MSnSet" or a character of feature names.
params	An instance of class "AnnotationParams", compatible with featureNames(object)'s format.
namespace	The ontology name space. One or several of "biological_process", "cellular_component" or "molecular_function".
evidence	GO evidence filtering.

**Value**

A new "MSnSet" with the GO terms for the respective features in the original object.

**Author(s)**

Laurent Gatto

**Examples**

```
library("pRolocdata")
data(dunkley2006)
data(dunkley2006params)
goset <- makeGoSet(dunkley2006[1:10, ],
                  dunkley2006params)
goset
exprs(goset)[1:10, 1:5]
image(goset)
```

---

makeNaData

*Create a data with missing values*

---

**Description**

These functions take an instance of class "MSnSet" and sets randomly selected values to NA.

**Usage**

```
makeNaData(object, nNA, pNA, exclude)

makeNaData2(object, nRows, nNAs, exclude)

whichNA(x)
```

**Arguments**

object	An instance of class MSnSet.
nNA	The absolute number of missing values to be assigned.
pNA	The proportion of missing values to be assigned.
exclude	A vector to be used to subset object, defining rows that should not be used to set NAs.
nRows	The number of rows for each set.
nNAs	The number of missing values for each set.
x	A matrix or an instance of class MSnSet.

**Details**

makeNaData randomly selects a number nNA (or a proportion pNA) of cells in the expression matrix to be set to NA.

makeNaData2 will select length(nRows) sets of rows from object, each with nRows[i] rows respectively. The first set will be assigned nNAs[1] missing values, the second nNAs[2], ... As opposed to makeNaData, this permits to control the number of NAs per rows.

The whichNA can be used to extract the indices of the missing values, as illustrated in the example.

**Value**

An instance of class MSnSet, as object, but with the appropriate number/proportion of missing values. The returned object has an additional feature meta-data columns, nNA

**Author(s)**

Laurent Gatto

**Examples**

```
## Example 1
library(pRolocdata)
data(dunkley2006)
sum(is.na(dunkley2006))
dunkleyNA <- makeNaData(dunkley2006, nNA = 150)
processingData(dunkleyNA)
sum(is.na(dunkleyNA))
table(fData(dunkleyNA)$nNA)
naIdx <- whichNA(dunkleyNA)
head(naIdx)
## Example 2
dunkleyNA <- makeNaData(dunkley2006, nNA = 150, exclude = 1:10)
processingData(dunkleyNA)
table(fData(dunkleyNA)$nNA[1:10])
table(fData(dunkleyNA)$nNA)
## Example 3
nr <- rep(10, 5)
na <- 1:5
```



```

x <- makeNaData2(dunkley2006[1:100, 1:5],
                 nRows = nr,
                 nNAs = na)
processingData(x)
(res <- table(fData(x)$nNA))
stopifnot(as.numeric(names(res)[-1]) == na)
stopifnot(res[-1] == nr)
## Example 2
nr2 <- c(5, 12, 11, 8)
na2 <- c(3, 8, 1, 4)
x2 <- makeNaData2(dunkley2006[1:100, 1:10],
                  nRows = nr2,
                  nNAs = na2)
processingData(x2)
(res2 <- table(fData(x2)$nNA))
stopifnot(as.numeric(names(res2)[-1]) == sort(na2))
stopifnot(res2[-1] == nr2[order(na2)])
## Example 5
nr3 <- c(5, 12, 11, 8)
na3 <- c(3, 8, 1, 3)
x3 <- makeNaData2(dunkley2006[1:100, 1:10],
                  nRows = nr3,
                  nNAs = na3)
processingData(x3)
(res3 <- table(fData(x3)$nNA))

```

---

markerMSnSet

*Extract marker/unknown subsets*


---

## Description

These function extract the marker or unknown proteins into a new MSnSet.

## Usage

```
markerMSnSet(object, fcol = "markers")
```

```
unknownMSnSet(object, fcol = "markers")
```

## Arguments

object	An instance of class MSnSet
fcol	The name of the feature data column, that will be used to separate the markers from the proteins of unknown localisation. When the markers are encoded as vectors, features of unknown localisation are defined as <code>fData(object)[, fcol] == "unknown"</code> . For matrix-encoded markers, unlabelled proteins are defined as <code>rowSums(fData(object)[, fcol]) == 0</code> . Default is "markers".

**Value**

An new MSnSet with marker/unknown proteins only.

**Author(s)**

Laurent Gatto

**See Also**

[sampleMSnSet](#) [testMSnSet](#) and [markers](#) for markers encoding.

**Examples**

```
library("pRolocdata")
data(dunkley2006)
mrk <- markerMSnSet(dunkley2006)
unk <- unknownMSnSet(dunkley2006)
dim(dunkley2006)
dim(mrk)
dim(unk)
table(fData(dunkley2006)$markers)
table(fData(mrk)$markers)
table(fData(unk)$markers)
## matrix-encoded markers
dunkley2006 <- mrkVecToMat(dunkley2006)
dim(markerMSnSet(dunkley2006, "Markers"))
stopifnot(all.equal(featureNames(markerMSnSet(dunkley2006, "Markers")),
                    featureNames(markerMSnSet(dunkley2006, "markers"))))
dim(unknownMSnSet(dunkley2006, "Markers"))
stopifnot(all.equal(featureNames(unknownMSnSet(dunkley2006, "Markers")),
                    featureNames(unknownMSnSet(dunkley2006, "markers"))))
```

---

MartInstance-class      *Class "MartInstance"*

---

**Description**

Internal infrastructure to query/handle several individual mart instance. See `MartInterface.R` for details.

**Author(s)**

Laurent Gatto <lg390@cam.ac.uk>

---

minClassScore	<i>Updates classes based on prediction scores</i>
---------------	---

---

### Description

This function updates the classification results in an "MSnSet" based on a prediction score threshold  $t$ . All features with a score  $< t$  are set to 'unknown'. Note that the original levels are preserved while 'unknown' is added.

### Usage

```
minClassScore(object, fcol, scol, t = 0)
```

### Arguments

object	An instance of class "MSnSet".
fcol	The name of the markers column in the featureData slot.
scol	The name of the prediction score column in the featureData slot. If missing, created by pasting '.scores' after fcol.
t	The score threshold. Predictions with score $< t$ are set to 'unknown'. Default is 0.

### Value

The original object with a modified `fData(object)[, fcol]` feature variable.

### Author(s)

Laurent Gatto

### See Also

`link{minMarkers}` to filter based on the number of markers per class.

### Examples

```
library(pRocdata)
data(dunkley2006)
## random scores
fData(dunkley2006)$assigned.scores <- runif(nrow(dunkley2006))
getPredictions(dunkley2006, fcol = "assigned")
getPredictions(dunkley2006, fcol = "assigned", t = 0.5)
x <- minClassScore(dunkley2006, fcol = "assigned", t = 0.5)
getPredictions(x, fcol = "assigned")
all.equal(getPredictions(dunkley2006, fcol = "assigned", t = 0.5),
          getPredictions(x, fcol = "assigned"))
```

---

minMarkers	<i>Creates a reduced marker variable</i>
------------	--

---

### Description

This function updates an MSnSet instances and sets markers class to unknown if there are less than n instances.

### Usage

```
minMarkers(object, n = 10, fcol = "markers")
```

### Arguments

object	An instance of class "MSnSet".
n	Minumum of marker instances per class.
fcol	The name of the markers column in the featureData slot. Default is markers.

### Value

An instance of class "MSnSet" with a new feature variables, named after the original fcol variable and the n value.

### Author(s)

Laurent Gatto

### See Also

[minClassScore](#) to filter based on classification scores.

### Examples

```
library(pRocdata)
data(dunkley2006)
d2 <- minMarkers(dunkley2006, 20)
getMarkers(dunkley2006)
getMarkers(d2, fcol = "markers20")
```

---

MLearn-methods	<i>The MLearn interface for machine learning</i>
----------------	--

---

**Description**

This method implements MLInterfaces' MLearn method for instances of the class "MSnSet".

**Methods**

```
signature(formula = "formula", data = "MSnSet", .method = "learnerSchema", trainInd = "numeric")
```

The learning problem is stated with the formula and applies the .method schema on the MSnSet data input using the trainInd numeric indices as train data.

```
signature(formula = "formula", data = "MSnSet", .method = "learnerSchema", trainInd = "xvalSpec")
```

In this case, an instance of `xvalSpec` is used for cross-validation.

```
signature(formula = "formula", data = "MSnSet", .method = "clusteringSchema", trainInd = "missing")
```

Hierarchical (`hclustI`), k-means (`kmeansI`) and partitioning around medoids (`pamI`) clustering algorithms using MLInterface's MLearn interface.

**See Also**

The MLInterfaces package documentation, in particular [MLearn](#).

---

move2Ds	<i>Displays a spatial proteomics animation</i>
---------	--

---

**Description**

Given two MSnSet instances of one MSnSetList with at least two items, this function produces an animation that shows the transition from the first data to the second.

**Usage**

```
move2Ds(object, pcol, fcol = "markers", n = 25, h1)
```

**Arguments**

object	An <code>linkS4class{MSnSet}</code> or a <code>MSnSetList</code> . In the latter case, only the two first elements of the list will be used for plotting and the others will be silently ignored.
pcol	If object is an <code>MSnSet</code> , a factor or the name of a phenotype variable ( <code>phenoData</code> slot) defining how to split the single <code>MSnSet</code> into two or more data sets. Ignored if object is a <code>MSnSetList</code> .
fcol	Feature meta-data label ( <code>fData</code> column name) defining the groups to be differentiated using different colours. Default is <code>markers</code> . Use <code>NULL</code> to suppress any colouring.

**n** Number of frames, Default is 25.

**hl** An optional instance of class `linkS4class{FeaturesOfInterest}` to track features of interest.

### Value

Used for its side effect of producing a short animation.

### Author(s)

Laurent Gatto

### See Also

[plot2Ds](#) to a single figure with the two datasets.

### Examples

```
library("pRolocdata")
data(dunkley2006)

## Create a relevant MSnSetList using the dunkley2006 data
xx <- split(dunkley2006, "replicate")
xx1 <- xx[[1]]
xx2 <- xx[[2]]
fData(xx1)$markers[374] <- "Golgi"
fData(xx2)$markers[412] <- "unknown"
xx@x[[1]] <- xx1
xx@x[[2]] <- xx2

## The features we want to track
foi <- FeaturesOfInterest(description = "test",
                          fnames = featureNames(xx[[1]])[c(374, 412)])

## (1) visualise each experiment separately
par(mfrow = c(2, 1))
plot2D(xx[[1]], main = "condition A")
highlightOnPlot(xx[[1]], foi)
plot2D(xx[[2]], mirrorY = TRUE, main = "condition B")
highlightOnPlot(xx[[2]], foi, args = list(mirrorY = TRUE))

## (2) plot both data on the same plot
par(mfrow = c(1, 1))
tmp <- plot2Ds(xx)
highlightOnPlot(data1(tmp), foi, lwd = 2)
highlightOnPlot(data2(tmp), foi, pch = 5, lwd = 2)

## (3) create an animation
move2Ds(xx, pcol = "replicate")
move2Ds(xx, pcol = "replicate", hl = foi)
```

---

mrkVecToMat	<i>Create a marker vector or matrix.</i>
-------------	--

---

### Description

Functions producing a new vector (matrix) marker vector set from an existing matrix (vector) marker set.

### Usage

```
mrkVecToMat(object, vfcoll = "markers", mfcoll = "Markers")
mrkMatToVec(object, mfcoll = "Markers", vfcoll = "markers")
mrkMatAndVec(object, vfcoll = "markers", mfcoll = "Markers")
showMrkMat(object, mfcoll = "Markers")
isMrkMat(object, fcoll = "Markers")
isMrkVec(object, fcoll = "markers")
mrkEncoding(object, fcoll = "markers")
```

### Arguments

object	An MSnSet object
vfcoll	The name of the <i>vector</i> marker feature variable. Default is "markers".
mfcoll	The name of the <i>matrix</i> marker feature variable. Default is "Markers".
fcoll	A marker feature variable name.

### Details

Sub-cellular markers can be encoded in two different ways. Sets of spatial markers can be represented as character *vectors* (character or factor, to be accurate), stored as feature metadata, and proteins of unknown or uncertain localisation (unlabelled, to be classified) are marked with the "unknown" character. While very handy, this encoding suffers from some drawbacks, in particular the difficulty to label proteins that reside in multiple (possible or actual) localisations. The markers vector feature data is typically named markers. A new *matrix* encoding is also supported. Each spatial compartment is defined in a column in a binary markers matrix and the resident proteins are encoded with 1s. The markers matrix feature data is typically named Markers. If proteins are assigned unique localisations only (i.e. no multi-localisation) or their localisation is unknown (unlabelled), then both encodings are equivalent. When the markers are encoded as vectors, features of unknown localisation are defined as `fData(object)[, fcoll] == "unknown"`. For matrix-encoded markers, unlabelled proteins are defined as `rowSums(fData(object)[, fcoll]) == 0`.

The `mrkMatToVec` and `mrkVecToMat` functions enable the conversion from matrix (vector) to vector (matrix). The `mrkMatAndVec` function generates the missing encoding from the existing one. If the destination encoding already exists, or, more accurately, if the feature variable of the destination encoding exists, an error is thrown. During the conversion from matrix to vector, if multiple possible label exists, they are dropped, i.e. they are converted to "unknown". Function `isMrkVec` and `isMrkMat` can be used to test if a marker set is encoded as a vector or a matrix. `mrkEncoding` returns either "vector" or "matrix" depending on the nature of the markers.

**Value**

An updated `MSnSet` with a new vector (matrix) marker set.

**Author(s)**

Laurent Gatto and Lisa Breckels

**See Also**

Other functions that operate on markers are [getMarkers](#), [getMarkerClasses](#) and [markerMSnSet](#). To add markers to an existing `MSnSet`, see the [addMarkers](#) function and [pRolocmarkers](#), for a list of suggested markers.

**Examples**

```
library("pRolocdata")
data(dunkley2006)
dunk <- mrkVecToMat(dunkley2006)
head(fData(dunk)$Markers)
fData(dunk)$markers <- NULL
dunk <- mrkMatToVec(dunk)
stopifnot(all.equal(fData(dunkley2006)$markers,
                    fData(dunk)$markers))
```

---

nbClassification      *nb classification*

---

**Description**

Classification using the naive Bayes algorithm.

**Usage**

```
nbClassification(object, assessRes, scores = c("prediction", "all", "none"),
                 laplace, fcol = "markers", ...)
```



**Arguments**

object	An instance of class "MSnSet".
assessRes	An instance of class "GenRegRes", as generated by <code>nbOptimisation</code> .
scores	One of "prediction", "all" or "none" to report the score for the predicted class only, for all cluster or none.
laplace	If assessRes is missing, a laplace must be provided.
fcol	The feature meta-data containing marker definitions. Default is markers.
...	Additional parameters passed to <code>naiveBayes</code> from package <code>e1071</code> .

**Value**

An instance of class "MSnSet" with `nb` and `nb.scores` feature variables storing the classification results and scores respectively.

**Author(s)**

Laurent Gatto

**Examples**

```
library(pRocdata)
data(dunkley2006)
## reducing parameter search space and iterations
params <- nbOptimisation(dunkley2006, laplace = c(0, 5), times = 3)
params
plot(params)
f1Count(params)
levelPlot(params)
getParams(params)
res <- nbClassification(dunkley2006, params)
getPredictions(res, fcol = "naiveBayes")
getPredictions(res, fcol = "naiveBayes", t = 1)
plot2D(res, fcol = "naiveBayes")
```

---

nbOptimisation

*nb paramter optimisation*

---

**Description**

Classification algorithm parameter for the naive Bayes algorithm.

**Usage**

```
nbOptimisation(object, fcol = "markers", laplace = seq(0, 5, 0.5),
  times = 100, test.size = 0.2, xval = 5, fun = mean, seed,
  verbose = TRUE, ...)
```

**Arguments**

object	An instance of class " <a href="#">MSnSet</a> ".
fcol	The feature meta-data containing marker definitions. Default is markers.
laplace	The hyper-parameter. Default values are seq(0, 5, 0.5).
times	The number of times internal cross-validation is performed. Default is 100.
test.size	The size of test data. Default is 0.2 (20 percent).
xval	The n-cross validation. Default is 5.
fun	The function used to summarise the xval macro F1 matrices.
seed	The optional random number generator seed.
verbose	A logical defining whether a progress bar is displayed.
...	Additional parameters passed to <a href="#">naiveBayes</a> from package e1071.

**Details**

Note that when performance scores precision, recall and (macro) F1 are calculated, any NA values are replaced by 0. This decision is motivated by the fact that any class that would have either a NA precision or recall would result in an NA F1 score and, eventually, a NA macro F1 (i.e. mean(F1)). Replacing NAs by 0s leads to F1 values of 0 and a reduced yet defined final macro F1 score.

**Value**

An instance of class "[GenRegRes](#)".

**Author(s)**

Laurent Gatto

**See Also**

[nbClassification](#) and example therein.

---

nndist-methods

*Nearest neighbour distances*

---

**Description**

Methods computing the nearest neighbour indices and distances for `matrix` and `MSnSet` instances.

**Methods**

signature(object = "matrix", k = "numeric", dist = "character", ...) Calculates indices and distances to the k (default is 3) nearest neighbours of each feature (row) in the input matrix object. The distance dist can be either of "euclidean" or "mahalanobis". Additional parameters can be passed to the internal function `FNN::get.knn`. Output is a matrix with  $2 * k$  columns and `nrow(object)` rows.

signature(object = "MSnSet", k = "numeric", dist = "character", ...) As above, but for an MSnSet input. The indices and distances to the k nearest neighbours are added to the object's feature metadata.

signature(object = "matrix", query = "matrix", k = "numeric", ...) If two matrix instances are provided as input, the k (default is 3) indices and distances of the nearest neighbours of query in object are returned as a matrix of dimensions  $2 * k$  by `nrow(query)`. Additional parameters are passed to `FNN::get.knnx`. Only euclidean distance is available.

**Examples**

```
library("pRolocdata")
data(dunkley2006)

## Using a matrix as input
m <- exprs(dunkley2006)
m[1:4, 1:3]
head(nndist(m, k = 5))
tail(nndist(m[1:100, ], k = 2, dist = "mahalanobis"))

## Same as above for MSnSet
d <- nndist(dunkley2006, k = 5)
head(fData(d))

d <- nndist(dunkley2006[1:100, ], k = 2, dist = "mahalanobis")
tail(fData(d))

## Using a query
nndist(m[1:100, ], m[101:110, ], k = 2)
```

---

nnetClassification      *nnet classification*

---

**Description**

Classification using the artificial neural network algorithm.

**Usage**

```
nnetClassification(object, assessRes, scores = c("prediction", "all", "none"),
  decay, size, fcol = "markers", ...)
```

**Arguments**

object	An instance of class "MSnSet".
assessRes	An instance of class "GenRegRes", as generated by <code>nnetOptimisation</code> .
scores	One of "prediction", "all" or "none" to report the score for the predicted class only, for all cluster or none.
decay	If assessRes is missing, a decay must be provided.
size	If assessRes is missing, a size must be provided.
fcol	The feature meta-data containing marker definitions. Default is markers.
...	Additional parameters passed to <code>nnet</code> from package <code>nnet</code> .

**Value**

An instance of class "MSnSet" with `nnet` and `nnet.scores` feature variables storing the classification results and scores respectively.

**Author(s)**

Laurent Gatto

**Examples**

```
library(pRoclocdata)
data(dunkley2006)
## reducing parameter search space and iterations
params <- nnetOptimisation(dunkley2006, decay = 10^(c(-1, -5)), size = c(5, 10), times = 3)
params
plot(params)
f1Count(params)
levelPlot(params)
getParams(params)
res <- nnetClassification(dunkley2006, params)
getPredictions(res, fcol = "nnet")
getPredictions(res, fcol = "nnet", t = 0.75)
plot2D(res, fcol = "nnet")
```

---

nnetOptimisation      *nnet parameter optimisation*

---

**Description**

Classification parameter optimisation for artificial neural network algorithm.

**Usage**

```
nnetOptimisation(object, fcol = "markers", decay = c(0, 10^(-1:-5)),
  size = seq(1, 10, 2), times = 100, test.size = 0.2, xval = 5,
  fun = mean, seed, verbose = TRUE, ...)
```

**Arguments**

object	An instance of class " <a href="#">MSnSet</a> ".
fcol	The feature meta-data containing marker definitions. Default is markers.
decay	The hyper-parameter. Default values are $c(0, 10^{(-1:-5)})$ .
size	The hyper-parameter. Default values are $seq(1, 10, 2)$ .
times	The number of times internal cross-validation is performed. Default is 100.
test.size	The size of test data. Default is 0.2 (20 percent).
xval	The n-cross validation. Default is 5.
fun	The function used to summarise the xval macro F1 matrices.
seed	The optional random number generator seed.
verbose	A logical defining whether a progress bar is displayed.
...	Additional parameters passed to <a href="#">nnet</a> from package <code>nnet</code> .

**Details**

Note that when performance scores precision, recall and (macro) F1 are calculated, any NA values are replaced by 0. This decision is motivated by the fact that any class that would have either a NA precision or recall would result in an NA F1 score and, eventually, a NA macro F1 (i.e.  $mean(F1)$ ). Replacing NAs by 0s leads to F1 values of 0 and a reduced yet defined final macro F1 score.

**Value**

An instance of class "[GenRegRes](#)".

**Author(s)**

Laurent Gatto

**See Also**

[nnetClassification](#) and example therein.

---

perTurboClassification

*perTurbo classification*

---

**Description**

Classification using the PerTurbo algorithm.

**Usage**

```
perTurboClassification(object, assessRes, scores = c("prediction", "all",
  "none"), pRegul, sigma, inv, reg, fcol = "markers")
```

**Arguments**

object	An instance of class "MSnSet".
assessRes	An instance of class "GenRegRes", as generated by <code>svmRegularisation</code> .
scores	One of "prediction", "all" or "none" to report the score for the predicted class only, for all cluster or none.
pRegul	If assessRes is missing, a pRegul must be provided. See <a href="#">perTurboOptimisation</a> for details.
sigma	If assessRes is missing, a sigma must be provided. See <a href="#">perTurboOptimisation</a> for details.
inv	The type of algorithm used to invert the matrix. Values are : "Inversion Cholesky" ( <code>chol2inv</code> ), "Moore Penrose" ( <code>ginv</code> ), "solve" ( <code>solve</code> ), "svd" ( <code>svd</code> ). Default value is "Inversion Cholesky".
reg	The type of regularisation of matrix. Values are "none", "trunc" or "tikhonov". Default value is "tikhonov".
fcol	The feature meta-data containing marker definitions. Default is markers.

**Value**

An instance of class "MSnSet" with `perTurbo` and `perTurbo.scores` feature variables storing the classification results and scores respectively.

**Author(s)**

Thomas Burger and Samuel Wieczorek

**References**

N. Courty, T. Burger, J. Laurent. "PerTurbo: a new classification algorithm based on the spectrum perturbations of the Laplace-Beltrami operator", The European Conference on Machine Learning and Principles and Practice of Knowledge Discovery in Databases (ECML-PKDD 2011), D. Gunopulos et al. (Eds.): ECML PKDD 2011, Part I, LNAI 6911, pp. 359 - 374, Athens, Greece, September 2011.

**Examples**

```
library(pRolocdata)
data(dunkley2006)
## reducing parameter search space
params <- perTurboOptimisation(dunkley2006,
                              pRegul = 2^seq(-2,2,2),
                              sigma = 10^seq(-1, 1, 1),
                              inv = "Inversion Cholesky",
                              reg = "tikhonov",
                              times = 3)

params
plot(params)
f1Count(params)
levelPlot(params)
```

```

getParams(params)
res <- perTurboClassification(dunkley2006, params)
getPredictions(res, fcol = "perTurbo")
getPredictions(res, fcol = "perTurbo", t = 0.75)
plot2D(res, fcol = "perTurbo")

```

---

perTurboOptimisation *PerTurbo parameter optimisation*

---

## Description

Classification parameter optimisation for the PerTurbo algorithm

## Usage

```

perTurboOptimisation(object, fcol = "markers", pRegul = 10^(seq(from = -1,
  to = 0, by = 0.2)), sigma = 10^(seq(from = -1, to = 1, by = 0.5)),
  inv = c("Inversion Cholesky", "Moore Penrose", "solve", "svd"),
  reg = c("tikhonov", "none", "trunc"), times = 1, test.size = 0.2,
  xval = 5, fun = mean, seed, verbose = TRUE)

```

## Arguments

object	An instance of class "MSnSet".
fcol	The feature meta-data containing marker definitions. Default is markers.
pRegul	The hyper-parameter for the regularisation (values are in ]0,1]). If reg=="trunc", pRegul is for the percentage of eigen values in matrix. If reg=="tikhonov", then 'pRegul' is the parameter for the tikhonov regularisation. Available configurations are : "Inversion Cholesky" - ("tikhonov" / "none"), "Moore Penrose" - ("tikhonov" / "none"), "solve" - ("tikhonov" / "none"), "svd" - ("tikhonov" / "none" / "trunc").
sigma	The hyper-parameter.
inv	The type of algorithm used to invert the matrix. Values are : "Inversion Cholesky" ( <a href="#">chol2inv</a> ), "Moore Penrose" ( <a href="#">ginv</a> ), "solve" ( <a href="#">solve</a> ), "svd" ( <a href="#">svd</a> ). Default value is "Inversion Cholesky".
reg	The type of regularisation of matrix. Values are "none", "trunc" or "tikhonov". Default value is "tikhonov".
times	The number of times internal cross-validation is performed. Default is 100.
test.size	The size of test data. Default is 0.2 (20 percent).
xval	The n-cross validation. Default is 5.
fun	The function used to summarise the times macro F1 matrices.
seed	The optional random number generator seed.
verbose	A logical defining whether a progress bar is displayed.

**Details**

Note that when performance scores precision, recall and (macro) F1 are calculated, any NA values are replaced by 0. This decision is motivated by the fact that any class that would have either a NA precision or recall would result in an NA F1 score and, eventually, a NA macro F1 (i.e. mean(F1)). Replacing NAs by 0s leads to F1 values of 0 and a reduced yet defined final macro F1 score.

**Value**

An instance of class "[GenRegRes](#)".

**Author(s)**

Thomas Burger and Samuel Wieczorek

**See Also**

[perTurboClassification](#) and example therein.

---

phenoDisco

*Runs the phenoDisco algorithm.*

---

**Description**

phenoDisco is a semi-supervised iterative approach to detect new protein clusters.

**Usage**

```
phenoDisco(object, fcol = "markers", times = 100, GS = 10,
  allIter = FALSE, p = 0.05, ndims = 2,
  modelNames = mclust.options("emModelNames"), G = 1:9, BPPARAM, tmpfile,
  seed, verbose = TRUE)
```

**Arguments**

object	An instance of class MSnSet.
fcol	A character indicating the organellar markers column name in feature meta-data. Default is markers.
times	Number of runs of tracking. Default is 100.
GS	Group size, i.e how many proteins make a group. Default is 10 (the minimum group size is 4).
allIter	logical, defining if predictions for all iterations should be saved. Default is FALSE.
p	Significance level for outlier detection. Default is 0.05.
ndims	Number of principal components to use as input for the discovery analysis. Default is 2. Added in version 1.3.9.



modelName	A vector of characters indicating the models to be fitted in the EM phase of clustering using Mclust. The help file for <code>mclustModelNames</code> describes the available models. Default model names are <code>c("EII", "VII", "EEI", "VEI", "EVI", "VVI", "EEE", "EEV", "EEV", "VEV", "VVV")</code> , i.e. only ellipsoidal models.
G	An integer vector specifying the numbers of mixture components (clusters) for which the BIC is to be calculated. The default is <code>G=1:9</code> (as in Mclust).
BPPARAM	Support for parallel processing using the BiocParallel infrastructure. When missing (default), the default registered BiocParallelParam parameters are used. Alternatively, one can pass a valid BiocParallelParam parameter instance: <code>SnowParam</code> , <code>MulticoreParam</code> , <code>DoparParam</code> , ... see the BiocParallel package for details. To revert to the original serial implementation, use <code>NULL</code> .
tmpfile	An optional character to save a temporary MSnSet after each iteration. Ignored if missing. This is useful for long runs to track phenotypes and possibly kill the run when convergence is observed. If the run completes, the temporary file is deleted before returning the final result.
seed	An optional numeric of length 1 specifying the random number generator seed to be used. Only relevant when executed in serialised mode with <code>BPPARAM = NULL</code> . See <code>BPPARAM</code> for details.
verbose	Logical, indicating if messages are to be printed out during execution of the algorithm.

## Details

The algorithm performs a phenotype discovery analysis as described in Breckels et al. Using this approach one can identify putative subcellular groupings in organelle proteomics experiments for more comprehensive validation in an unbiased fashion. The method is based on the work of Yin et al. and used iterated rounds of Gaussian Mixture Modelling using the Expectation Maximisation algorithm combined with a non-parametric outlier detection test to identify new phenotype clusters.

One requires 2 or more classes to be labelled in the data and at a very minimum of 6 markers per class to run the algorithm. The function will check and remove features with missing values using the `filterNA` method.

A parallel implementation, relying on the BiocParallel package, has been added in version 1.3.9. See the `BPPARAM` argument for details.

Important: Prior to version 1.1.2 the row order in the output was different from the row order in the input. This has now been fixed and row ordering is now the same in both input and output objects.

## Value

An instance of class `MSnSet` containing the `phenoDisco` predictions.

## Author(s)

Lisa M. Breckels <lms79@cam.ac.uk>

## References

Yin Z, Zhou X, Bakal C, Li F, Sun Y, Perrimon N, Wong ST. Using iterative cluster merging with improved gap statistics to perform online phenotype discovery in the context of high-throughput RNAi screens. *BMC Bioinformatics*. 2008 Jun 5;9:264. PubMed PMID: 18534020.

Breckels LM, Gatto L, Christoforou A, Groen AJ, Lilley KS and Trotter MWB. The Effect of Organelle Discovery upon Sub-Cellular Protein Localisation. *J Proteomics*. 2013 Aug 2;88:129-40. doi: 10.1016/j.jprot.2013.02.019. Epub 2013 Mar 21. PubMed PMID: 23523639.

## Examples

```
## Not run:
library(pRolocdata)
data(tan2009r1)
pdres <- phenoDisco(tan2009r1, fcol = "PLSDA")
getPredictions(pdres, fcol = "pd", scol = NULL)
plot2D(pdres, fcol = "pd")

## End(Not run)
```

---

plot2D

*Plot organelle assignment data and results.*

---

## Description

Generate 2 dimensional or feature distribution plots to illustrate localisation clusters. In plot2D, rows containing NA values are removed prior to dimension reduction.

## Usage

```
plot2D(object, fcol = "markers", fpch, unknown = "unknown", dims = 1:2,
       score = 1, method = "PCA", methargs, axsSwitch = FALSE,
       mirrorX = FALSE, mirrorY = FALSE, col, pch, cex, index = FALSE,
       idx.cex = 0.75, identify = FALSE, plot = TRUE, ...)
```

## Arguments

object	An instance of class MSnSet.
fcol	Feature meta-data label (fData column name) defining the groups to be differentiated using different colours. Default is markers. Use NULL to suppress any colouring.
fpch	Feature meta-data label (fData column name) defining the groups to be differentiated using different point symbols.
unknown	A character (default is "unknown") defining how proteins of unknown/unlabelled localisation are labelled.
dims	A numeric of length 2 defining the dimensions to be plotted. Always 1:2 for MDS.

score	A numeric specifying the minimum organelle assignment score to consider features to be assigned an organelle. (not yet implemented).
method	Either a character or a matrix. When the former, one of "PCA" (default), "MDS", "kpca" or "t-SNE", defining if dimensionality reduction is done using principal component analysis (see <a href="#">prcomp</a> ), classical multidimensional scaling (see <a href="#">cmdscale</a> ), kernel PCA (see <code>kernlab::kpca</code> ) or t-SNE (see <code>tsne::tsne</code> ). "scree" can also be used to produce a scree plot. If a matrix is passed, its rownames must match object's feature names and represent a projection of the data in object in two dimensions, as produced (and invisibly returned) by <code>plot2D</code> . This enables to re-generate the figure without computing the dimensionality reduction over and over again, which can be time consuming for certain methods. Available methods are listed in <code>plot2Dmethods</code> .
methargs	A list of arguments to be passed when method is called. If missing, the data will be scaled and centred prior to PCA.
axsSwitch	A logical indicating whether the axes should be switched.
mirrorX	A logical indicating whether the x axis should be mirrored?
mirrorY	A logical indicating whether the y axis should be mirrored?
col	A character of appropriate length defining colours.
pch	A character of appropriate length defining point character.
cex	Character expansion.
index	A logical (default is FALSE, indicating of the feature indices should be plotted on top of the symbols).
idx.cex	A numeric specifying the character expansion (default is 0.75) for the feature indices. Only relevant when index is TRUE.
identify	A logical (default is TRUE) defining if user interaction will be expected to identify individual data points on the plot. See also <a href="#">identify</a> .
plot	A logical defining if the figure should be plotted. Useful when retrieving data only. Default is TRUE.
...	Additional parameters passed to plot and points.

### Details

Note that `plot2D` has been update in version 1.3.6 to support more more orgnalle classes than colours defined in [getStockcol](#). In such cases, the defauly colours are recycled using the default plotting characters defined in [getStockpch](#). See the example for an illustration. The alpha argument is also depreciated in version 1.3.6. Use `setStockcol` to set colours with transparency instead. See example below.

### Value

Used for its side effects of generating a plot. Invisibly returns the 2d data.

### Author(s)

Laurent Gatto <lg390@cam.ac.uk>

**See Also**

[addLegend](#) to add a legend to plot2D figures and [plotDist](#) for alternative graphical representation of quantitative organelle proteomics data. [plot2Ds](#) to overlay 2 data sets on the same PCA plot.

**Examples**

```
library("pRolocdata")
data(dunkley2006)
plot2D(dunkley2006, fcol = NULL)
## available methods
plot2Dmethods
plot2D(dunkley2006, fcol = NULL, method = "kpca")
plot2D(dunkley2006, fcol = NULL, method = "kpca",
       methargs = list(kpar = list(sigma = 1)))
plot2D(dunkley2006, fcol = "markers")
addLegend(dunkley2006,
          fcol = "markers",
          where = "topright",
          cex = 0.5, bty = "n", ncol = 3)
title(main = "plot2D example")
## Using transparent colours
setStockcol(paste0(getStockcol(), "80"))
plot2D(dunkley2006, fcol = "markers")
## New behaviour in 1.3.6 when not enough colours
setStockcol(c("blue", "red", "green"))
getStockcol() ## only 3 colours to be recycled
getMarkers(dunkley2006)
plot2D(dunkley2006)
```

---

plot2Ds

---

*Draw 2 data sets on one PCA plot*


---

**Description**

Takes 2 `linkS4class{MSnSet}` instances as input to plot the two data sets on the same PCA plot. The second data points are projected on the PC1 and PC2 dimensions calculated for the first data set.

**Usage**

```
plot2Ds(object, pcol, fcol = "markers", cex.x = 1, cex.y = 1,
        pch.x = 21, pch.y = 23, col, mirrorX = FALSE, mirrorY = FALSE,
        plot = TRUE, ...)
```

**Arguments**

`object` An `linkS4class{MSnSet}` or a `MSnSetList`. In the latter case, only the two first elements of the list will be used for plotting and the others will be silently ignored.

pcol	If object is an MSnSet, a factor or the name of a phenotype variable (phenoData slot) defining how to split the single MSnSet into two or more data sets. Ignored if object is a <a href="#">MSnSetList</a> .
fcol	Feature meta-data label (fData column name) defining the groups to be differentiated using different colours. Default is markers. Use NULL to suppress any colouring.
cex.x	Character expansion for the first data set. Default is 1.
cex.y	Character expansion for the second data set. Default is 1.
pch.x	Plotting character for the first data set. Default is 21.
pch.y	Plotting character for the second data set. Default is 23.
col	A vector of colours to highlight the different classes defined by fcol. If missing (default), default colours are used (see <a href="#">getStockcol</a> ).
mirrorX	A logical indicating whether the x axis should be mirrored?
mirrorY	A logical indicating whether the y axis should be mirrored?
plot	If TRUE (default), a plot is produced.
...	Additional parameters passed to plot and points.

### Value

Used for its side effects of producing a plot. Invisibly returns an object of class plot2Ds, which is a list with the PCA analys results (see [prcomp](#)) of the first data set and the new coordinates of the second data sets, as used to produce the plot and the respective point colours. Each of these elements can be accessed with data1, data2, col1 and code2 respectively.

### Author(s)

Laurent Gatto

### See Also

See [plot2D](#) to plot a single data set and [move2Ds](#) for a animation.

### Examples

```
library("pRolocdata")
data(tan2009r1)
data(tan2009r2)
msnl <- MSnSetList(list(tan2009r1, tan2009r2))
plot2Ds(msnl)
## tweaking the parameters
plot2Ds(list(tan2009r1, tan2009r2),
        fcol = NULL, cex.x = 1.5)
## input is 1 MSnSet containing 2 data sets
data(dunkley2006)
plot2Ds(dunkley2006, pcol = "replicate")
## no plot, just the data
res <- plot2Ds(dunkley2006, pcol = "replicate",
```

```

                                plot = FALSE)
res
head(data1(res))
head(col1(res))

```

---

plotDist	<i>Plots the distribution of features across fractions</i>
----------	--

---

### Description

Produces a line plot showing the feature abundances across the fractions.

### Usage

```

plotDist(object, markers, mcol = "steelblue", pcol = "grey90",
         alpha = 0.3, lty = 1, fractions, ylim, ...)

```

### Arguments

object	An instance of class MSnSet.
markers	A character, numeric or logical of appropriate length and or content used to subset object and define the organelle markers.
mcol	A character define the colour of the marker features. Default is "steelblue".
pcol	A character define the colour of the non-markers features. Default is "grey90".
alpha	A numeric defining the alpha channel (transparency) of the points, where $0 \leq \alpha \leq 1$ , 0 and 1 being completely transparent and opaque.
lty	Vector of line types for the marker profiles. Default is 1 (solid). See <a href="#">par</a> for details.
fractions	An optional character defining the phenoData variable to be used to label the fraction along the x axis. If missing, the phenoData variables are searched for a match to fraction. If no match is found, the fractions are labelled as numericals.
ylim	A numeric vector of length 2, giving the y coordinates range.
...	Additional parameters passed to <a href="#">plot</a> .

### Value

Used for its side effect of producing a feature distribution plot. Invisibly returns the data matrix.

### Author(s)

Laurent Gatto

## Examples

```
library("pRolocdata")
data(tan2009r1)
j <- which(fData(tan2009r1)$markers == "mitochondrion")
i <- which(fData(tan2009r1)$PLSDA == "mitochondrion")
plotDist(tan2009r1[i, ],
         markers = featureNames(tan2009r1)[j])
title("Mitochondrion")
```

---

plsdaClassification    *plsda classification*

---

## Description

Classification using the partial least square discriminant analysis algorithm.

## Usage

```
plsdaClassification(object, assessRes, scores = c("prediction", "all",
"none"), ncomp, fcol = "markers", ...)
```

## Arguments

object	An instance of class <code>"MSnSet"</code> .
assessRes	An instance of class <code>"GenRegRes"</code> , as generated by <code>plsdaOptimisation</code> .
scores	One of <code>"prediction"</code> , <code>"all"</code> or <code>"none"</code> to report the score for the predicted class only, for all cluster or none.
ncomp	If <code>assessRes</code> is missing, a <code>ncomp</code> must be provided.
fcol	The feature meta-data containing marker definitions. Default is <code>markers</code> .
...	Additional parameters passed to <code>plsda</code> from package <code>caret</code> .

## Value

An instance of class `"MSnSet"` with `plsda` and `plsda.scores` feature variables storing the classification results and scores respectively.

## Author(s)

Laurent Gatto

**Examples**

```
## not running this one for time considerations
library(pRolocdata)
data(dunkley2006)
## reducing parameter search space and iterations
params <- plsdaOptimisation(dunkley2006, ncomp = c(3, 10), times = 2)
params
plot(params)
f1Count(params)
levelPlot(params)
getParams(params)
res <- plsdaClassification(dunkley2006, params)
getPredictions(res, fcol = "plsda")
getPredictions(res, fcol = "plsda", t = 0.9)
plot2D(res, fcol = "plsda")
```

---

plsdaOptimisation      *plsda parameter optimisation*

---

**Description**

Classification parameter optimisation for the partial least square discriminant analysis algorithm.

**Usage**

```
plsdaOptimisation(object, fcol = "markers", ncomp = 2:6, times = 100,
  test.size = 0.2, xval = 5, fun = mean, seed, verbose = TRUE, ...)
```

**Arguments**

object	An instance of class " <i>MSnSet</i> ".
fcol	The feature meta-data containing marker definitions. Default is markers.
ncomp	The hyper-parameter. Default values are 2:6.
times	The number of times internal cross-validation is performed. Default is 100.
test.size	The size of test data. Default is 0.2 (20 percent).
xval	The n-cross validation. Default is 5.
fun	The function used to summarise the xval macro F1 matrices.
seed	The optional random number generator seed.
verbose	A logical defining whether a progress bar is displayed.
...	Additional parameters passed to <i>plsda</i> from package <i>caret</i> .



**Details**

Note that when performance scores precision, recall and (macro) F1 are calculated, any NA values are replaced by 0. This decision is motivated by the fact that any class that would have either a NA precision or recall would result in an NA F1 score and, eventually, a NA macro F1 (i.e. mean(F1)). Replacing NAs by 0s leads to F1 values of 0 and a reduced yet defined final macro F1 score.

**Value**

An instance of class "[GenRegRes](#)".

**Author(s)**

Laurent Gatto

**See Also**

[plsdaClassification](#) and example therein.

---

pRolocmarkers

*Organelle markers*

---

**Description**

This function retrieves a list of organelle markers or, if no species is provided, prints a description of available marker sets. The markers can be added to an MSnSet using the [addMarkers](#) function.

**Usage**

```
pRolocmarkers(species)
```

**Arguments**

species      The species of interest.

**Details**

The markers have been contributed by various members of the Cambridge Centre for Proteomics, in particular Dan Nightingale for yeast, Dr Andy Christoforou for human, Dr Arnoud Groen for Arabodopsis and Dr Claire Mulvey for mouse. In addition, original (curated) markers from the pRolocdata datasets have been extracted (see pRolocdata for details and references). Curation involved verification of publicly available subcellular localisation annotation based on the curators knowledge of the organelles/proteins considered and tracing the original statement in the literature.

These markers are provided as a starting point to generate reliable sets of organelle markers but still need to be verified against any new data in the light of the quantitative data and the study conditions.

**Value**

Prints a description of the available marker lists if species is missing or a named character with organelle markers.

**Author(s)**

Laurent Gatto

**See Also**

[addMarkers](#) to add markers to an MSnSet and [markers](#) for more information about marker encoding.

**Examples**

```
pRolocmarkers()
table(pRolocmarkers("atha"))
table(pRolocmarkers("hsap"))
```

---

rfClassification      *rf classification*

---

**Description**

Classification using the random forest algorithm.

**Usage**

```
rfClassification(object, assessRes, scores = c("prediction", "all", "none"),
  mtry, fcol = "markers", ...)
```

**Arguments**

object	An instance of class "MSnSet".
assessRes	An instance of class "GenRegRes", as generated by <a href="#">rfOptimisation</a> .
scores	One of "prediction", "all" or "none" to report the score for the predicted class only, for all cluster or none.
mtry	If assessRes is missing, a mtry must be provided.
fcol	The feature meta-data containing marker definitions. Default is markers.
...	Additional parameters passed to <a href="#">randomForest</a> from package randomForest.

**Value**

An instance of class "MSnSet" with rf and rf.scores feature variables storing the classification results and scores respectively.

**Author(s)**

Laurent Gatto

**Examples**

```

library(pRolocdata)
data(dunkley2006)
## reducing parameter search space and iterations
params <- rfOptimisation(dunkley2006, mtry = c(2, 5, 10), times = 3)
params
plot(params)
f1Count(params)
levelPlot(params)
getParams(params)
res <- rfClassification(dunkley2006, params)
getPredictions(res, fcol = "rf")
getPredictions(res, fcol = "rf", t = 0.75)
plot2D(res, fcol = "rf")

```

---

rfOptimisation

*svm parameter optimisation*


---

**Description**

Classification parameter optimisation for the random forest algorithm.

**Usage**

```

rfOptimisation(object, fcol = "markers", mtry = NULL, times = 100,
  test.size = 0.2, xval = 5, fun = mean, seed, verbose = TRUE, ...)

```

**Arguments**

object	An instance of class " <a href="#">MSnSet</a> ".
fcol	The feature meta-data containing marker definitions. Default is markers.
mtry	The hyper-parameter. Default value is NULL.
times	The number of times internal cross-validation is performed. Default is 100.
test.size	The size of test data. Default is 0.2 (20 percent).
xval	The n-cross validation. Default is 5.
fun	The function used to summarise the xval macro F1 matrices.
seed	The optional random number generator seed.
verbose	A logical defining whether a progress bar is displayed.
...	Additional parameters passed to <a href="#">randomForest</a> from package randomForest.

**Details**

Note that when performance scores precision, recall and (macro) F1 are calculated, any NA values are replaced by 0. This decision is motivated by the fact that any class that would have either a NA precision or recall would result in an NA F1 score and, eventually, a NA macro F1 (i.e.  $\text{mean}(F1)$ ). Replacing NAs by 0s leads to F1 values of 0 and a reduced yet defined final macro F1 score.

**Value**

An instance of class "[GenRegRes](#)".

**Author(s)**

Laurent Gatto

**See Also**

[rfClassification](#) and example therein.

---

sampleMSnSet

*Extract a stratified sample of an MSnSet*

---

**Description**

This function extracts a stratified sample of an MSnSet.

**Usage**

```
sampleMSnSet(object, fcol = "markers", size = 0.2, seed)
```

**Arguments**

object	An instance of class <a href="#">MSnSet</a>
fcol	The feature meta-data column name containing the marker (vector or matrix) definitions on which the MSnSet will be stratified. Default is markers.
size	The size of the stratified sample to be extracted. Default is 0.2 (20 percent).
seed	The optional random number generator seed.

**Value**

A stratified sample (according to the defined fcol) which is an instance of class "[MSnSet](#)".

**Author(s)**

Lisa Breckels

**See Also**

[testMSnSet](#) [unknownMSnSet](#) [markerMSnSet](#). See [markers](#) for details about markers encoding.

**Examples**

```
library(pRolocdata)
data(tan2009r1)
dim(tan2009r1)
smp <- sampleMSnSet(tan2009r1, fcol = "markers")
dim(smp)
getMarkers(tan2009r1)
getMarkers(smp)
```

---

setLisacol

*Manage default colours and point characters*

---

**Description**

These functions allow to get/set the default colours and point character that are used when plotting organelle clusters and unknown features. These values are parametrised at the session level. Two palettes are available: the default and Lisa's colours.

**Usage**

```
setLisacol()
getLisacol()
getStockcol()
setStockcol(cols)
getStockpch()
setStockpch(pchs)
getUnknowncol()
setUnknowncol(col)
getUnknownpch()
setUnknownpch(pch)
setStockcolGui()
```

**Arguments**

cols	A vector of colour characters or NULL, which sets the colours to the default values.
pchs	A vector of numeric or NULL, which sets the point characters to the default values.
col	A colour character or NULL, which sets the colour to #E7E7E7 (grey91), the default colour for unknown features.
pch	A numeric vector of length 1 or NULL, which sets the point character to 21, the default.

**Value**

The set functions set (and invisibly returns) colours. The get functions returns a character vector of colours. For the pch functions, numerics rather than characters.

**Author(s)**

Laurent Gatto

**Examples**

```
## defaults for clusters
getStockcol()
getStockpch()
## unknown features
getUnknownpch()
getUnknowncol()
## an example
library(pRolocdata)
data(dunkley2006)
par(mfrow = c(2, 1))
plot2D(dunkley2006, fcol = "markers", main = 'Default colours')
setUnknowncol("black")
plot2D(dunkley2006, fcol = "markers", main = 'setUnknowncol("black"')
getUnknowncol()
setUnknowncol(NULL)
getUnknowncol()
getLisacol()
setLisacol()
## now default colours are Lisa's
getStockcol()
```

---

showGOEvidenceCodes    *GO Evidence Codes*

---

**Description**

This function prints a textual description of the Gene Ontology evidence codes.

**Usage**

```
showGOEvidenceCodes()

getGOEvidenceCodes()
```

**Value**

These functions are used for their side effects of printing evidence codes and their description.

**Author(s)**

Laurent Gatto

**Examples**

```
showGOEvidenceCodes()
getGOEvidenceCodes()
```

---

SpatProtVis-class      *Class* SpatProtVis

---

**Description**

A class for spatial proteomics visualisation, that upon instantiation, pre-computes all defined visualisations. Objects can be created with the SpatProtVis constructor and visualised with the plot method.

The class is essentially a wrapper around several calls to [plot2D](#) that stores the dimensionality reduction outputs, and is likely to be updated in the future.

**Usage**

```
SpatProtVis(x, methods, dims, methargs, ...)
```

**Arguments**

x	An instance of class <a href="#">MSnSet</a> to visualise.
methods	Dimensionality reduction methods to be used to visualise the data. Must be contained in <a href="#">plot2Dmethods</a> (except "screen"). See <a href="#">plot2D</a> for details.
dims	A list of numerics defining dimensions used for plotting. Default are 1 and 2. If provided, the length of this list must be identical to the length of methods.
methargs	A list of additional arguments to be passed for each visualisation method. If provided, the length of this list must be identical to the length of methods.
...	Additional arguments. Currently ignored.

**Slots**

vismats: A "list" of matrices containing the feature projections in 2 dimensions.

data: The original spatial proteomics data stored as an "MSnSet".

methargs: A "list" of additional plotting arguments.

objname: A "character" defining how to name the dataset. By default, this is set using the variable name used at object creation.

**Methods**

plot: Generates the figures for the respective methods and additional arguments defined in the constructor. If used in an interactive session, the user is prompted to press 'Return' before new figures are displayed.

show: A simple textual summary of the object.

**Author(s)**

Laurent Gatto <lg390@cam.ac.uk>

**See Also**

The data for the individual visualisations is created by [plot2D](#).

**Examples**

```
library("pRolocdata")
data(dunkley2006)
## Default parameters for a set of methods
## (in the interest of time, don't use t-SNE)
m <- c("PCA", "MDS", "kpca")
vis <- SpatProtVis(dunkley2006, methods = m)
vis
plot(vis)
plot(vis, legend = "topleft")

## Setting method arguments
margs <- c(list(kpar = list(sigma = 0.1)),
           list(kpar = list(sigma = 1.0)),
           list(kpar = list(sigma = 10)),
           list(kpar = list(sigma = 100)))
vis <- SpatProtVis(dunkley2006,
                  methods = rep("kpca", 4),
                  methargs = margs)
par(mfrow = c(2, 2))
plot(vis)

## Multiple PCA plots but different PCs
dims <- list(c(1, 2), c(3, 4))
vis <- SpatProtVis(dunkley2006, methods = c("PCA", "PCA"), dims = dims)
plot(vis)
```



---

svmClassification      *svm classification*

---

## Description

Classification using the support vector machine algorithm.

## Usage

```
svmClassification(object, assessRes, scores = c("prediction", "all", "none"),  
  cost, sigma, fcol = "markers", ...)
```

## Arguments

object	An instance of class "MSnSet".
assessRes	An instance of class "GenRegRes", as generated by <a href="#">svmOptimisation</a> .
scores	One of "prediction", "all" or "none" to report the score for the predicted class only, for all cluster or none.
cost	If assessRes is missing, a cost must be provided.
sigma	If assessRes is missing, a sigma must be provided.
fcol	The feature meta-data containing marker definitions. Default is markers.
...	Additional parameters passed to <a href="#">svm</a> from package e1071.

## Value

An instance of class "MSnSet" with svm and svm.scores feature variables storing the classification results and scores respectively.

## Author(s)

Laurent Gatto

## Examples

```
library(pRolocdata)  
data(dunkley2006)  
## reducing parameter search space and iterations  
params <- svmOptimisation(dunkley2006, cost = 2^seq(-2,2,2), sigma = 10^seq(-1, 1, 1), times = 3)  
params  
plot(params)  
f1Count(params)  
levelPlot(params)  
getParams(params)  
res <- svmClassification(dunkley2006, params)  
getPredictions(res, fcol = "svm")  
getPredictions(res, fcol = "svm", t = 0.75)  
plot2D(res, fcol = "svm")
```

---

 svmOptimisation      *svm parameter optimisation*


---

### Description

Classification parameter optimisation for the support vector machine algorithm.

### Usage

```
svmOptimisation(object, fcol = "markers", cost = 2^(-4:4),
  sigma = 10^(-3:2), times = 100, test.size = 0.2, xval = 5,
  fun = mean, seed, verbose = TRUE, ...)
```

### Arguments

object	An instance of class " <a href="#">MSnSet</a> ".
fcol	The feature meta-data containing marker definitions. Default is markers.
cost	The hyper-parameter. Default values are $2^{-4:4}$ .
sigma	The hyper-parameter. Default values are $10^{-2:3}$ .
times	The number of times internal cross-validation is performed. Default is 100.
test.size	The size of test data. Default is 0.2 (20 percent).
xval	The n-cross validation. Default is 5.
fun	The function used to summarise the xval macro F1 matrices.
seed	The optional random number generator seed.
verbose	A logical defining whether a progress bar is displayed.
...	Additional parameters passed to <a href="#">svm</a> from package <a href="#">e1071</a> .

### Details

Note that when performance scores precision, recall and (macro) F1 are calculated, any NA values are replaced by 0. This decision is motivated by the fact that any class that would have either a NA precision or recall would result in an NA F1 score and, eventually, a NA macro F1 (i.e. `mean(F1)`). Replacing NAs by 0s leads to F1 values of 0 and a reduced yet defined final macro F1 score.

### Value

An instance of class "[GenRegRes](#)".

### Author(s)

Laurent Gatto

### See Also

[svmClassification](#) and example therein.

---

testMarkers	<i>Tests marker class sizes</i>
-------------	---------------------------------

---

### Description

Tests if the marker class sizes are large enough for the parameter optimisation scheme, i.e. the size is greater than  $xval + n$ , where the default  $xval$  is 5 and  $n$  is 2. If the test is unsuccessful, a warning is thrown.

### Usage

```
testMarkers(object, xval = 5, n = 2, fcol = "markers", error = FALSE)
```

### Arguments

object	An instance of class " <a href="#">MSnSet</a> ".
xval	The number cross-validation partitions. See the <code>xval</code> argument in the parameter optimisation function(s). Default is 5.
n	Number of additional examples.
fcol	The name of the prediction column in the <code>featureData</code> slot. Default is "markers".
error	A logical specifying if an error should be thrown, instead of a warning.

### Details

In case the test indicates that a class contains too few examples, it is advised to either add some or, if not possible, to remove the class altogether (see [minMarkers](#)) as the parameter optimisation is likely to fail or, at least, produce unreliable results for that class.

### Value

If successful, the test invisibly returns NULL. Else, it invisibly returns the names of the classes that have too few examples.

### Author(s)

Laurent Gatto

### See Also

[getMarkers](#) and [minMarkers](#)

## Examples

```
library("pRolocdata")
data(dunkley2006)
getMarkers(dunkley2006)
testMarkers(dunkley2006)
toosmall <- testMarkers(dunkley2006, xval = 15)
toosmall
try(testMarkers(dunkley2006, xval = 15, error = TRUE))
```

---

testMSnSet

*Create a stratified 'test' MSnSet*

---

## Description

This function creates a stratified 'test' MSnSet which can be used for algorithmic development. A "MSnSet" containing only the marker proteins, as defined in `fcol`, is returned with a new feature data column appended called `test` in which a stratified subset of these markers has been relabelled as 'unknowns'.

## Usage

```
testMSnSet(object, fcol = "markers", size = 0.2, seed)
```

## Arguments

<code>object</code>	An instance of class "MSnSet"
<code>fcol</code>	The feature meta-data column name containing the marker definitions on which the data will be stratified. Default is <code>markers</code> .
<code>size</code>	The size of the data set to be extracted. Default is 0.2 (20 percent).
<code>seed</code>	The optional random number generator seed.

## Value

An instance of class "MSnSet" which contains only the proteins that have a labelled localisation i.e. the marker proteins, as defined in `fcol` and a new column in the feature data slot called `test` which has part of the labels relabelled as "unknown" class (the number of proteins renamed as "unknown" is according to the parameter `size`).

## Author(s)

Lisa Breckels

## See Also

[sampleMSnSet](#) [unknownMSnSet](#) [markerMSnSet](#)

**Examples**

```
library(pRolocdata)
data(tan2009r1)
sample <- testMSnSet(tan2009r1)
getMarkers(sample, "test")
all(dim(sample) == dim(markerMSnSet(tan2009r1)))
```

---

thetas

*Draw matrix of thetas to test*

---

**Description**

The possible weights to be considered is a sequence from 0 (favour auxiliary data) to 1 (favour primary data). Each possible combination of weights for `nclass` classes must be tested. The `thetas` function produces a weight matrix for `nclass` columns (one for each class) with all possible weight combinations (number of rows).

**Usage**

```
thetas(nclass, by = 0.5, length.out, verbose = TRUE)
```

**Arguments**

<code>nclass</code>	Number of marker classes
<code>by</code>	The increment of the weights. One of 1, 0.5, 0.25, 2, 0.1 or 0.05.
<code>length.out</code>	The desired length of the weight sequence.
<code>verbose</code>	A logical indicating if the weight sequences should be printed out. Default is TRUE.

**Value**

A matrix with all possible theta weight combinations.

**Author(s)**

Lisa Breckels

**Examples**

```
dim(thetas(4, by = 0.5))
dim(thetas(4, by = 0.2))
dim(thetas(5, by = 0.2))
dim(thetas(5, length.out = 5))
dim(thetas(6, by = 0.2))
```

---

undocumented

*Undocumented/unexported entries*

---

**Description**

This is just a dummy entry for methods from unexported classes that generate warnings during package checking.

**Author(s)**

Laurent Gatto <lg390@cam.ac.uk>

# Index

## \*Topic **classes**

AnnotationParams-class, 6  
GenRegRes-class, 14  
SpatProtVis-class, 63

## \*Topic **methods**

chi2-methods, 10  
exprsToRatios-methods, 12  
MLearn-methods, 37  
nndist-methods, 42

## \*Topic **package**

pRoLoc-package, 3

[,MartInstanceList,ANY,ANY,ANY-method  
(MartInstance-class), 34

[,MartInstanceList,ANY,ANY-method  
(MartInstance-class), 34

[,MartInstanceList-method  
(MartInstance-class), 34

[[,MartInstanceList,ANY,ANY-method  
(MartInstance-class), 34

[[,MartInstanceList-method  
(MartInstance-class), 34

addLegend, 4, 52

addMarkers, 5, 30, 40, 57, 58

andy2011params  
(AnnotationParams-class), 6

AnnotationParams, 16, 31

AnnotationParams  
(AnnotationParams-class), 6

AnnotationParams-class, 6

as.data.frame.MartInstance  
(MartInstance-class), 34

as.data.frame.MartInstanceList  
(MartInstance-class), 34

checkFeatureNamesOverlap, 8

checkFvarOverlap, 9

chi2, 11

chi2 (chi2-methods), 10

chi2,matrix,matrix-method  
(chi2-methods), 10

chi2,matrix,numeric-method  
(chi2-methods), 10

chi2,numeric,matrix-method  
(chi2-methods), 10

chi2,numeric,numeric-method  
(chi2-methods), 10

chi2-methods, 10

chol2inv, 46, 47

class:AnnotationParams  
(AnnotationParams-class), 6

class:GenRegRes (GenRegRes-class), 14

class:SpatProtVis (SpatProtVis-class),  
63

class:ThetaRegRes (GenRegRes-class), 14

cmdscale, 51

col1 (plot2Ds), 52

col2 (plot2Ds), 52

combineThetaRegRes (GenRegRes-class), 14

data1 (plot2Ds), 52

data2 (plot2Ds), 52

dunkley2006params  
(AnnotationParams-class), 6

empPvalues, 10, 11

estimateMasterFdr, 29

exprsToRatios (exprsToRatios-methods),  
12

exprsToRatios,MSnSet-method  
(exprsToRatios-methods), 12

exprsToRatios-methods, 12

f1Count (GenRegRes-class), 14

f1Count,GenRegRes-method  
(GenRegRes-class), 14

f1Count,ThetaRegRes-method  
(GenRegRes-class), 14

favourPrimary (GenRegRes-class), 14

- FeaturesOfInterest, [21](#)
- filterAttrs (MartInstance-class), [34](#)
- filterBinMSnSet, [12](#)
- filterNA, [49](#)
- filterZeroCols, [13](#)
- filterZeroRows (filterZeroCols), [13](#)
- flipGoTermId (goIdToTerm), [20](#)
- GenRegRes, [22](#), [24](#), [27](#), [28](#), [41](#), [42](#), [44–46](#), [48](#), [55](#), [57](#), [58](#), [60](#), [65](#), [66](#)
- GenRegRes (GenRegRes-class), [14](#)
- GenRegRes-class, [14](#)
- getAnnotationParams (AnnotationParams-class), [6](#)
- getF1Scores (GenRegRes-class), [14](#)
- getF1Scores, GenRegRes-method (GenRegRes-class), [14](#)
- getF1Scores, ThetaRegRes-method (GenRegRes-class), [14](#)
- getFilterList (MartInstance-class), [34](#)
- getGOEvidenceCodes (showGOEvidenceCodes), [62](#)
- getGOFromFeatures, [6](#), [7](#), [16](#)
- getLisacol (setLisacol), [61](#)
- getMarkerClasses, [17](#), [18](#), [40](#)
- getMarkers, [17](#), [18](#), [40](#), [67](#)
- getMartInstanceList (MartInstance-class), [34](#)
- getMartTab (MartInstance-class), [34](#)
- getParams (GenRegRes-class), [14](#)
- getParams, ClustRegRes-method (undocumented), [70](#)
- getParams, GenRegRes-method (GenRegRes-class), [14](#)
- getParams, ThetaRegRes-method (GenRegRes-class), [14](#)
- getPredictions, [19](#)
- getRegularisedParams (GenRegRes-class), [14](#)
- getRegularisedParams, GenRegRes-method (GenRegRes-class), [14](#)
- getRegularizedParams (GenRegRes-class), [14](#)
- getRegularizedParams, GenRegRes-method (GenRegRes-class), [14](#)
- getSeed (GenRegRes-class), [14](#)
- getSeed, GenRegRes-method (GenRegRes-class), [14](#)
- getStockcol, [51](#), [53](#)
- getStockcol (setLisacol), [61](#)
- getStockpch, [51](#)
- getStockpch (setLisacol), [61](#)
- getUnknowncol (setLisacol), [61](#)
- getUnknownpch (setLisacol), [61](#)
- getWarnings (GenRegRes-class), [14](#)
- getWarnings, GenRegRes-method (GenRegRes-class), [14](#)
- ginv, [46](#), [47](#)
- goIdToTerm, [20](#)
- goTermToId (goIdToTerm), [20](#)
- highlightOnPlot, [21](#)
- identify, [51](#)
- isMrkMat (mrkVecToMat), [39](#)
- isMrkVec (mrkVecToMat), [39](#)
- knn, [22](#), [23](#)
- knnClassification, [22](#), [24](#)
- knnOptimisation, [14](#), [22](#), [23](#)
- knnOptimization (knnOptimisation), [23](#)
- knnPrediction (knnClassification), [22](#)
- knnRegularisation (knnOptimisation), [23](#)
- knnt1Classification, [24](#), [26](#)
- knnt1Optimisation, [14](#), [24](#), [25](#)
- ksvm, [27](#), [28](#)
- ksvmClassification, [26](#), [28](#)
- ksvmOptimisation, [27](#), [27](#)
- ksvmOptimization (ksvmOptimisation), [27](#)
- ksvmPrediction (ksvmClassification), [26](#)
- ksvmRegularisation (ksvmOptimisation), [27](#)
- lapply, MartInstancelist, ANY-method (MartInstance-class), [34](#)
- lapply, MartInstancelist-method (MartInstance-class), [34](#)
- legend, [5](#)
- levelPlot (GenRegRes-class), [14](#)
- levelPlot, ClustRegRes-method (undocumented), [70](#)
- levelPlot, GenRegRes-method (GenRegRes-class), [14](#)
- lopims, [29](#)
- lopims1 (lopims), [29](#)
- lopims2 (lopims), [29](#)
- lopims3 (lopims), [29](#)
- lopims4 (lopims), [29](#)



- lopims5 (lopims), 29
- makeGoSet, 6, 7, 30
- makeMaster, 29
- makeNaData, 31
- makeNaData2 (makeNaData), 31
- markerMSnSet, 33, 40, 61, 68
- markers, 6, 17, 18, 34, 58, 61
- markers (mrkVecToMat), 39
- MartInstance (MartInstance-class), 34
- MartInstance-class, 34
- MartInstanceList (MartInstance-class), 34
- MartInstanceList-class (MartInstance-class), 34
- minClassScore, 35, 36
- minMarkers, 36, 67
- MLearn, 37
- MLearn, formula, MSnSet, clusteringSchema, missing-method (MLearn-methods), 37
- MLearn, formula, MSnSet, learnerSchema, numeric-method (MLearn-methods), 37
- MLearn, formula, MSnSet, learnerSchema, xvalSpec-method (MLearn-methods), 37
- MLearn-methods, 37
- MLearnMSnSet (MLearn-methods), 37
- move2Ds, 37, 53
- mrkEncoding (mrkVecToMat), 39
- mrkMatAndVec (mrkVecToMat), 39
- mrkMatToVec (mrkVecToMat), 39
- mrkVecToMat, 39
- MSnbase, 4
- MSnSet, 12, 15, 17–19, 22–25, 27–31, 35–37, 41, 42, 44–47, 55, 56, 58–60, 63, 65–68
- MSnSetList, 37, 53
- MSnSetMLean (MLearn-methods), 37
- naiveBayes, 41, 42
- nbClassification, 40, 42
- nbOptimisation, 41, 41
- nbOptimization (nbOptimisation), 41
- nbPrediction (nbClassification), 40
- nbRegularisation (nbOptimisation), 41
- nDatasets (MartInstance-class), 34
- nndist (nndist-methods), 42
- nndist, matrix, matrix-method (nndist-methods), 42
- nndist, matrix, missing-method (nndist-methods), 42
- nndist, MSnSet, missing-method (nndist-methods), 42
- nndist-methods, 42
- nnet, 44, 45
- nnetClassification, 43, 45
- nnetOptimisation, 44, 44
- nnetOptimization (nnetOptimisation), 44
- nnetPrediction (nnetClassification), 43
- nnetRegularisation (nnetOptimisation), 44
- par, 54
- perTurboClassification, 45, 48
- perTurboOptimisation, 46, 47
- perTurboOptimization (perTurboOptimisation), 47
- phenoDisco, 48
- plot, 54
- plot, ClustRegRes, missing-method (undocumented), 70
- plot, GenRegRes, missing-method (GenRegRes-class), 14
- plot, SpatProtVis, missing-method (SpatProtVis-class), 63
- plot, ThetaRegRes, missing-method (GenRegRes-class), 14
- plot2D, 4, 5, 50, 53, 63, 64
- plot2Dmethods, 63
- plot2Dmethods (plot2D), 50
- plot2Ds, 38, 52, 52
- plotDist, 52, 54
- plsda, 55, 56
- plsdaClassification, 55, 57
- plsdaOptimisation, 14, 55, 56
- plsdaOptimization (plsdaOptimisation), 56
- plsdaPrediction (plsdaClassification), 55
- plsdaRegularisation (plsdaOptimisation), 56
- prcomp, 51, 53
- prettyGoTermId (goIdToTerm), 20
- pRoloc (pRoloc-package), 3
- pRoloc-package, 3
- pRolocmarkers, 5, 6, 40, 57
- randomForest, 58, 59

- rfClassification, [58, 60](#)
- rfOptimisation, [58, 59](#)
- rfOptimization (rfOptimisation), [59](#)
- rfPrediction (rfClassification), [58](#)
- rfRegularisation (rfOptimisation), [59](#)
  
- sampleMSnSet, [34, 60, 68](#)
- sapply, MartInstanceList, ANY-method  
(MartInstance-class), [34](#)
- sapply, MartInstanceList-method  
(MartInstance-class), [34](#)
- setAnnotationParams  
(AnnotationParams-class), [6](#)
- setLisacol, [61](#)
- setStockcol (setLisacol), [61](#)
- setStockcolGui (setLisacol), [61](#)
- setStockpch (setLisacol), [61](#)
- setUnknowncol (setLisacol), [61](#)
- setUnknownpch (setLisacol), [61](#)
- show, AnnotationParams-method  
(AnnotationParams-class), [6](#)
- show, ClustRegRes-method (undocumented),  
[70](#)
- show, GenRegRes-method  
(GenRegRes-class), [14](#)
- show, MartInstance-method  
(MartInstance-class), [34](#)
- show, SpatProtVis-method  
(SpatProtVis-class), [63](#)
- show, ThetaRegRes-method  
(GenRegRes-class), [14](#)
- showGOEvidenceCodes, [62](#)
- showMrkMat (mrkVecToMat), [39](#)
- solve, [46, 47](#)
- SpatProtVis (SpatProtVis-class), [63](#)
- SpatProtVis-class, [63](#)
- svd, [46, 47](#)
- svm, [65, 66](#)
- svmClassification, [65, 66](#)
- svmOptimisation, [14, 65, 66](#)
- svmOptimization (svmOptimisation), [66](#)
- svmPrediction (svmClassification), [65](#)
- svmRegularisation, [46](#)
- svmRegularisation (svmOptimisation), [66](#)
- Synapter, [29](#)
- synapter, [29](#)
- synergise, [29](#)
  
- testMarkers, [67](#)
- testMSnSet, [34, 61, 68](#)
- ThetaRegRes (GenRegRes-class), [14](#)
- ThetaRegRes-class (GenRegRes-class), [14](#)
- thetas, [26, 69](#)
  
- undocumented, [70](#)
- unknownMSnSet, [61, 68](#)
- unknownMSnSet (markerMSnSet), [33](#)
  
- whichNA (makeNaData), [31](#)
  
- xvalSpec, [37](#)