

Package ‘epiNEM’

October 17, 2017

Type Package

Title epiNEM

Version 1.0.1

Author Madeline Diekmann & Martin Pirkl

Maintainer Martin Pirkl <martin.pirkl@bsse.ethz.ch>

Description epiNEM is an extension of the original Nested Effects Models (NEM). EpiNEM is able to take into account double knockouts and infer more complex network signalling pathways.

Depends R (>= 3.4)

License GPL-3

Encoding UTF-8

LazyData true

biocViews Pathways, SystemsBiology, NetworkInference, Network

RoxygenNote 6.0.1

Imports BoolNet, e1071, gtools, stats, igraph, nem, utils, lattice, latticeExtra, RColorBrewer, pcalg, minet, grDevices, graph

VignetteBuilder knitr

Suggests knitr, RUnit, BiocGenerics, STRINGdb, devtools, rmarkdown, GOSemSim, AnnotationHub, org.Sc.sgd.db

NeedsCompilation no

R topics documented:

AddLogicGates	2
CreateExtendedAdjacency	3
CreateRandomGraph	3
CreateTopology	4
epiAnno	4
epiNEM	5
epiScreen	6
ExtendTopology	7
GenerateData	7
HeatmapOP	8
MII	10
plot.epiNEM	10

plot.epiScreen	11
plot.epiSim	12
sameith_GO	12
sameith_string	13
samscreen	13
sim	14
SimEpiNEM	14
wageningen_GO	15
wageningen_string	15
wagscreen	16

Index	17
--------------	-----------

AddLogicGates	<i>extend model with node representing logic gate</i>
---------------	---

Description

extend model with node representing logic gate

Usage

```
AddLogicGates(child, logic, model)
```

Arguments

child	define the child
logic	define the logical gate
model	normal model

Value

model list with additional logic gate

Examples

```
model <- CreateRandomGraph(c("Ikk1", "Ikk2", "RelA"))
model2 <- AddLogicGates("RelA", "OR", model)
```

`CreateExtendedAdjacency`*Create an extended adjacency matrix*

Description

extend adjacency matrices taking cycles and logics into account. For every given start state, the final state is computed yu using BoolNet.

Usage

```
CreateExtendedAdjacency(network, mutants, experiments)
```

Arguments

network	network created by BoolNet from file
mutants	vector of single knockouts
experiments	vector of all knockouts

Value

extended adjacency matrix

Examples

```
library(BoolNet)
data(cellcycle)
extModel <- CreateExtendedAdjacency(cellcycle,
c(cellcycle$genes, "CycD.Rb"), cellcycle$genes)
```

`CreateRandomGraph`*Create a random graph*

Description

Returns a model graph with randomly sampled edges. Every possible edge has a probability to exist in the graph.

Usage

```
CreateRandomGraph(pathwayGenes, edgeProb = 0.5)
```

Arguments

pathwayGenes	vector of genes in the pathway
edgeProb	probability of random edge

Value

adjacency matrix

Examples

```
graph <- CreateRandomGraph(c("Ikk1", "Ikk2", "RelA"))
```

CreateTopology	<i>create topology for a randomly generated pathway topology</i>
----------------	--

Description

create topology for a randomly generated pathway topology

Usage

```
CreateTopology(single, double, force = TRUE)
```

Arguments

single	number of single knockouts
double	number of double knockouts
force	if true the random model will have a sophisticated logical gate

Value

adjacency matrix

Examples

```
model <- CreateTopology(3, 1)
```

epiAnno	<i>Plots logical gate data annotation. The 8 heatmaps visualize what perfect data would look like in respective to each logical gate. Perfect data is equivalent to Boolean truth tables.</i>
---------	---

Description

Plots logical gate data annotation. The 8 heatmaps visualize what perfect data would look like in respective to each logical gate. Perfect data is equivalent to Boolean truth tables.

Usage

```
epiAnno()
```

Value

plot of heatmaps showing the silencing scheme (=expected data, truth tables)

Author(s)

Martin Pirkl

References

https://en.wikipedia.org/wiki/Boolean_algebra

Examples

```
epiAnno()
```

epiNEM	<i>Epistatic NEMs - main function. This function contains the inference algorithm to learn logical networks from knock-down data including double knock-downs.</i>
--------	--

Description

Epistatic NEMs - main function. This function contains the inference algorithm to learn logical networks from knock-down data including double knock-downs.

Usage

```
epiNEM(filename = "random", method = "greedy", nIterations = 10,
        nModels = 0, random = list(single = 4, double = 1, reporters = 100, FPrate
        = 0.1, FNrate = 0.1, replicates = 1), ltype = "marginal", para = c(0.13,
        0.05), init = NULL)
```

Arguments

filename	A binary, tab-delimited matrix. Columns: single and double knockdowns. Rows: genes showing effect or not? Default: random; artificial data is generated to 'random' specifications
method	greedy or exhaustive search. Default: greedy
nIterations	number of iterations. Default: 10
nModels	number of Models. Default: 0
random	list specifying how the data should be generated: no. of single mutants, no. of double mutants, no. of reporterGenes, FP-rate, FN-rate, no. of replicates
ltype	likelihood either "marginal" or "maximum"
para	false positive and false negative rates
init	adjacency matrix to initialise the greedy search

Value

List object with an adjacency matrix denoting the network, the model of the silencing scheme (rows are knock-downs, columns are signalling genes), a string with the inferred logical gates, a column indices denoting position of logical gates, the log transformed likelihood and the effect reporter distribution (rows are the signalling genes including the null node).

Author(s)

Madeline Diekmann

See Also

nem

Examples

```
data <- matrix(sample(c(0,1), 100*4, replace = TRUE), 100, 4)
colnames(data) <- c("A", "A.B", "B", "C")
rownames(data) <- paste("E", 1:100, sep = "_")
res <- epiNEM(data, method = "exhaustive")
plot(res)
```

epiScreen

This function is used to analyse knock-out screens with multiple double and single knock-outs combined in one data set.

Description

This function is used to analyse knock-out screens with multiple double and single knock-outs combined in one data set.

Usage

```
epiScreen(data, ...)
```

Arguments

data	data matrix containing multiple single and double knock-downs in columns and effect reporters in the rows
...	additional parameters, e.g. for the main epiNEM function

Value

list object with vectors of double knock-downs, single knock-downs and two matrices with doubles in the columns and singles in the rows. The first matrix denotes the respective logical gate for the triple and the second matrix the log-likelihood

Author(s)

Martin Pirkl

Examples

```
data <- matrix(sample(c(0,1), 100*9, replace = TRUE), 100, 9)
colnames(data) <- c("A.B", "A.C", "B.C", "A", "B", "C", "D", "E", "G")
rownames(data) <- paste("E", 1:100, sep = "_")
res <- epiScreen(data)
```

ExtendTopology	<i>Extending topology of normal "nem"</i>
----------------	---

Description

Extending topology of normal "nem"

Usage

```
ExtendTopology(topology, nReporters)
```

Arguments

topology	model of a topology from CreateTopology
nReporters	number of effects reporters

Value

extended topology in which reporters are linked to pathway genes

Author(s)

Madeline Diekmann

See Also

CreateTopology

Examples

```
topology <- CreateTopology(3, 1, force = TRUE)
topology <- unlist(unique(topology), recursive = FALSE)
extTopology <- ExtendTopology(topology$model, 100)
```

GenerateData	<i>Generate data from extended model. Given a model created from CreateTopology and ExtendTopology, this function creates a corresponding artificial data matrix, which is used as a ground truth for simulation studies.</i>
--------------	---

Description

Generate data from extended model. Given a model created from CreateTopology and ExtendTopology, this function creates a corresponding artificial data matrix, which is used as a ground truth for simulation studies.

Usage

```
GenerateData(model, extTopology, FPrate, FNrate, replicates)
```

Arguments

model	model of a topology from CreateTopology
extTopology	extended topology
FPrate	false positive rate
FNrate	false negative rate
replicates	number of replicates

Value

data matrix with effect reporters as rows and knock-downs (including double knock-downs) as columns.

Author(s)

Madeline Diekmann

See Also

CreateTopology

Examples

```
topology <-
CreateTopology(3, 1, force = TRUE)
topology <-
unlist(unique(topology), recursive = FALSE)
extTopology <-
ExtendTopology(topology$model, 100)
sortedData <-
GenerateData(topology$model, extTopology, 0.05, 0.13, 3)
```

HeatmapOP

heatmap function based on the lattice package more information: ?xyplot

Description

heatmap function based on the lattice package more information: ?xyplot

Usage

```
HeatmapOP(x, col = "RdYlGn", colNA = "grey", coln = 11,
bordercol = "grey", borderwidth = 0.1, breaks = "sym", main = "",
sub = "", dendrogram = "none", colorkey = list(space = "right"),
Colv = TRUE, Rowv = TRUE, xrot = 90, yrot = 0, shrink = c(1, 1),
cexCol = 1, cexRow = 1, cexMain = 1, cexSub = 1,
colSideColors = NULL, aspect = "fill", contour = FALSE,
useRaster = FALSE, xlab = NULL, ylab = NULL, colSideColorsPos = "top",
clust = NULL, clusterx = NULL, ...)
```


Arguments

<code>x</code>	Matrix.
<code>col</code>	Color. See <code>brewer.pal.info</code> for all available color schemes.
<code>colNA</code>	color for NAs; default is grey
<code>coln</code>	Number of colors.
<code>bordercol</code>	Border color.
<code>borderwidth</code>	Border width.
<code>breaks</code>	Defines the breaks in the color range. "sym" makes the breaks symmetric around 0.
<code>main</code>	Main title.
<code>sub</code>	Subtitle.
<code>dendrogram</code>	Draw dendrogram with "both", "col" or "row", or do not draw with "none".
<code>colorkey</code>	Draw colorkey list(space="left") or list(space="right").
<code>Colv</code>	Cluster columns (TRUE) or not (FALSE).
<code>Rowv</code>	Cluster rows (TRUE) or not (FALSE).
<code>xrot</code>	Rotate the column names by degree.
<code>yrot</code>	Rotate the row names by degree.
<code>shrink</code>	<code>c(x,y)</code> defines a range of size for the data boxes from low to high.
<code>cexCol</code>	Font size of column names.
<code>cexRow</code>	Font size of row names.
<code>cexMain</code>	Font size of main title.
<code>cexSub</code>	Font size of subtitle.
<code>colSideColors</code>	Defines a numeric vector to annotate columns with different colors.
<code>aspect</code>	"iso" for quadratic boxes or "fill" for stretched boxes.
<code>contour</code>	TRUE adds a contour plot.
<code>useRaster</code>	TRUE to add raster visuals
<code>xlab</code>	Label for the x-axis.
<code>ylab</code>	Label for the y-axis.
<code>colSideColorsPos</code>	Place <code>colSideColors</code> at the "top" or "bottom".
<code>clust</code>	p, s, or k for correlation clustering
<code>clusterx</code>	Optional data matrix y with the same dimensions as x. x is columns or rows are sorted by the cluster information of y.
<code>...</code>	Optional arguments.

Value

lattice object/matrix

Author(s)

Martin Pirkl & Oscar Perpinan at <http://oscarperpinan.github.io/rastervis/>

Examples

```
x <- matrix(rnorm(50), 10, 5)
HeatmapOP(x, dendrogram = "both", aspect = "iso", xrot = 45)
```

Mll *Evaluation of graphs*

Description

Computes marginal log-likelihood for model Phi given observed data matrix D1

Usage

```
Mll(Phi, D1, D0, ltype = "marginal", para = c(0.13, 0.05))
```

Arguments

Phi	model to be evaluated
D1	observed data matrix
D0	complementary D1
ltype	likelihood type either "marginal" or "maximum"
para	false positive and false negative rates

Value

list with likelihood poster probability, egene positions

Examples

```
Phi <- matrix(sample(c(0,1), 9, replace = TRUE), 3, 3)
data <- matrix(sample(c(0,1), 3*10, replace = TRUE), 10, 3)
rownames(Phi) <- colnames(Phi) <- colnames(data) <- c("Ikk1", "Ikk2", "RelA")
score <- Mll(Phi, D1 <- data, D0 <- 1 - data)
```

plot.epiNEM *Plots the winning pathway structure*

Description

Plots the winning pathway structure

Usage

```
## S3 method for class 'epiNEM'
plot(x, ...)
```

Arguments

x	object of class epiNEM
...	other arguments

Value

plot of the logical network

Examples

```
data <- matrix(sample(c(0,1), 100*4, replace = TRUE), 100, 4)
colnames(data) <- c("A", "A.B", "B", "C")
rownames(data) <- paste("E", 1:100, sep = "_")
res <- epiNEM(data, method = "exhaustive")
plot(res)
```

plot.epiScreen

Plots the sresults of a systematic knock-out screen

Description

Plots the sresults of a systematic knock-out screen

Usage

```
## S3 method for class 'epiScreen'
plot(x, global = TRUE, ind = NULL, colorkey = TRUE,
     cexGene = 1, off = 0.05, cexLegend = 1, ...)
```

Arguments

x	object of class epiScreen
global	plot global distribution or for each pair (FALSE)
ind	index of pairs to plot
colorkey	if TRUE prints colorkey
cexGene	size of modulator annotation
off	relative distance from the gene names to the respective likelihoods
cexLegend	font size of the legend
...	other arguments

Value

plot(s) of an epiNEM screen analysis

Examples

```
data <- matrix(sample(c(0,1), 100*9, replace = TRUE), 100, 9)
colnames(data) <- c("A.B", "A.C", "B.C", "A", "B", "C", "D", "E", "G")
rownames(data) <- paste("E", 1:100, sep = "_")
res <- epiScreen(data)
plot(res)
plot(res, global = FALSE, ind = 1:3)
```

plot.epiSim	<i>Plots the simulation results</i>
-------------	-------------------------------------

Description

Plots the simulation results

Usage

```
## S3 method for class 'epiSim'  
plot(x, ...)
```

Arguments

x	object of class epiSim
...	other arguments

Value

plot(s) of an epiNEM simulation analysis

Examples

```
res <- SimEpiNEM(runs = 1)  
plot(res)
```

sameith_GO	<i>graph-based GO similarity scores, string GO annotations for Sameith et al., 2015 data The data consists of lists including epiNEM identified and general similarity scores and GO annotations for each triple. For details see the vignette.</i>
------------	---

Description

graph-based GO similarity scores, string GO annotations for Sameith et al., 2015 data The data consists of lists including epiNEM identified and general similarity scores and GO annotations for each triple. For details see the vignette.

Examples

```
data(sameith_GO)
```

sameith_string	<i>sig. of string interaction scores for Sameith et al., 2015 data The data consists of a list including a vectors of pairs (for interactions) and a corresponding list of interaction scores derived form the string database. For details see the vignette.</i>
----------------	---

Description

sig. of string interaction scores for Sameith et al., 2015 data The data consists of a list including a vectors of pairs (for interactions) and a corresponding list of interaction scores derived form the string database. For details see the vignette.

Examples

```
data(sameith_string)
```

samscreen	<i>Example data: epiNEM results for the Sameith et al., 2015 knock-out screen The result of the epiNEM analysis of the data from "http://www.holstegelab.nl/publications/sv/signaling_redundancy/downloads/DataS1.txt". The data consists of a list of matrices with the likelihoods (ll) for each analysed triple of signalling genes and the inferred logic (logic) for each triple. The signalling genes or modulators C are the rows and the signalling genes from the double knock-downs are in the columns. For details see the vignette.</i>
-----------	---

Description

Example data: epiNEM results for the Sameith et al., 2015 knock-out screen The result of the epiNEM analysis of the data from "http://www.holstegelab.nl/publications/sv/signaling_redundancy/downloads/DataS1.txt". The data consists of a list of matrices with the likelihoods (ll) for each analysed triple of signalling genes and the inferred logic (logic) for each triple. The signalling genes or modulators C are the rows and the signalling genes from the double knock-downs are in the columns. For details see the vignette.

Examples

```
data(samscreen)
```

<code>sim</code>	<i>Example data: simulation results Contains simulation results. How they were aquired is explained in the vignette. The data consists of a list of data matrices holding sensitivity and specificity (spec, sens) of network edges for the variious methods compared to the ground truth, sensitivity and specificity (sens2, spec2) of the expected data for epiNEM and Boolean NEMs and accuracy of the inferred logics for both. The different methods are in the rows and the columns denote the different independent simulation runs.</i>
------------------	--

Description

Example data: simulation results Contains simulation results. How they were aquired is explained in the vignette. The data consists of a list of data matrices holding sensitivity and specificity (spec, sens) of network edges for the variious methods compared to the ground truth, sensitivity and specificity (sens2, spec2) of the expected data for epiNEM and Boolean NEMs and accuracy of the inferred logics for both. The different methods are in the rows and the columns denote the different independent simulation runs.

Examples

```
data(sim)
```

<code>SimEpiNEM</code>	<i>Compares different network reconstruction algorithm on simulated data.</i>
------------------------	---

Description

Compares different network reconstruction algorithm on simulated data.

Usage

```
SimEpiNEM(runs = 10, do = c("n", "e"), random = list(FPrate = 0.1, FNrate
  = c(0.1, 0.5), single = 3, double = 1, reporters = 10, replicates = 2),
  maxTime = FALSE, forcelogic = TRUE, epinemsearch = "greedy",
  bnemsearch = "genetic", ...)
```

Arguments

<code>runs</code>	number simulation runs
<code>do</code>	string vector of algorithms to compare: e (epiNEM), n (Nested Effects Models), b (B-NEM), p (PC algorithm), a (Aracne), e.g. c("e", "n", "p")
<code>random</code>	list of false poitive rate FPrate, false negative rates FNrate, number of single knock-downs single, number of double knock-downs double, number of effect reporters reporters and number of replicates replicates
<code>maxTime</code>	TRUE if the algorithms are bound to a maximum running time in respect to epiNEM

forcelogic	if TRUE the randomly sampled ground truth network includes a complex logic with probability 1
epinemsearch	greedy or exhaustive search for epiNEM
bnemsearch	genetic or greedy search for B-NEM
...	additional parameters

Value

returns list of specificity and sensitivity of inferred edges (spec, sens) and inferred expected data (spec2, sens2) and accuracy of logics (logics) and running time (time)

Author(s)

Martin Pirkl

Examples

```
res <- SimEpiNEM(runs = 1)
```

wageningen_GO	<i>graph-based GO similarity scores, string GO annotations for van Wageningen et al., 2015 data The data consists of lists including epiNEM identified and general similarity scores and GO annotations for each triple. For details see the vignette.</i>
---------------	--

Description

graph-based GO similarity scores, string GO annotations for van Wageningen et al., 2015 data The data consists of lists including epiNEM identified and general similarity scores and GO annotations for each triple. For details see the vignette.

Examples

```
data(wageningen_GO)
```

wageningen_string	<i>sig. of string interaction scores for van Wageningen et al., 2010 data The data consists of a list including a vectors of pairs (for interactions) and a corresponding list of interaction scores derived from the string database. For details see the vignette.</i>
-------------------	--

Description

sig. of string interaction scores for van Wageningen et al., 2010 data The data consists of a list including a vectors of pairs (for interactions) and a corresponding list of interaction scores derived from the string database. For details see the vignette.

Examples

```
data(wageningen_string)
```

wagscreen

Example data: epiNEM results for the Wageningen et al., 2010 knock-out screen "http://www.holstegelab.nl/publications/GSTF_geneticinteractions/downloads/del_mutants_limma.txt" The data consists of a list of matrices with the likelihoods (ll) for each analysed triple of signalling genes and the inferred logic (logic) for each triple. The signalling genes or modulators C are the rows and the signalling genes from the double knock-downs are in the columns. For details see the vignette.

Description

Example data: epiNEM results for the Wageningen et al., 2010 knock-out screen "http://www.holstegelab.nl/publications/downloads/del_mutants_limma.txt" The data consists of a list of matrices with the likelihoods (ll) for each analysed triple of signalling genes and the inferred logic (logic) for each triple. The signalling genes or modulators C are the rows and the signalling genes from the double knock-downs are in the columns. For details see the vignette.

Examples

```
data(wagscreen)
```


Index

AddLogicGates, [2](#)

CreateExtendedAdjacency, [3](#)
CreateRandomGraph, [3](#)
CreateTopology, [4](#)

epiAnno, [4](#)
epiNEM, [5](#)
epiScreen, [6](#)
ExtendTopology, [7](#)

GenerateData, [7](#)

HeatmapOP, [8](#)

M11, [10](#)

plot.epiNEM, [10](#)
plot.epiScreen, [11](#)
plot.epiSim, [12](#)

sameith_GO, [12](#)
sameith_string, [13](#)
samscreen, [13](#)
sim, [14](#)
SimEpiNEM, [14](#)

wageningen_GO, [15](#)
wageningen_string, [15](#)
wagscreen, [16](#)