

# Package ‘muscle’

October 18, 2017

**Type** Package

**Title** Multiple Sequence Alignment with MUSCLE

**Version** 3.18.0

**Date** 2012-10-05

**Author** Algorithm by Robert C. Edgar. R port by Alex T. Kalinka.

**Maintainer** Alex T. Kalinka <alex.t.kalinka@gmail.com>

**Description** MUSCLE performs multiple sequence alignments of nucleotide or amino acid sequences.

**biocViews** MultipleSequenceAlignment, Alignment, Sequencing, Genetics, SequenceMatching, DataImport

**Depends** Biostrings

**License** Unlimited

**URL** <http://www.drive5.com/muscle/>

**LazyLoad** yes

**LazyData** yes

**NeedsCompilation** yes

## R topics documented:

muscle-package . . . . .	1
muscle . . . . .	2
umax . . . . .	3

<b>Index</b>	<b>5</b>
--------------	----------

---

muscle-package	<i>Multiple Sequence Alignment</i>
----------------	------------------------------------

---

## Description

MUSCLE performs multiple sequence alignments of nucleotide and amino acid sequences.

## Details

Details about the algorithm can be found on the MUSCLE website:  
<http://www.drive5.com/muscle/>

## Author(s)

Algorithm: Robert C. Edgar  
R port: Alex T. Kalinka <[alex.t.kalinka@gmail.com](mailto:alex.t.kalinka@gmail.com)>

## References

Edgar, R.C. (2004) MUSCLE: multiple sequence alignment with high accuracy and high throughput. *Nucleic Acids Res* **32**, 1792-1797.

## See Also

[muscle](#), [umax](#)

## Examples

```
## Align sequences in an XStringSet object.  
## Not run:  
aln <- muscle(stringset = umax)  
  
## End(Not run)
```

---

muscle

*Multiple Sequence Alignment*

---

## Description

MUSCLE performs multiple sequence alignments of nucleotide or amino acid sequences.

## Usage

```
muscle(stringset, quiet = FALSE, ...)
```

## Arguments

stringset	An object of class <code>XStringSet</code> : <code>DNAStrngSet</code> , <code>RNAStrngSet</code> , or <code>AAStringSet</code> .
quiet	Logical, whether to prevent printing of the progress of the algorithm to the screen. Defaults to FALSE.
...	Arguments (options and flags) for the MUSCLE algorithm (see Details).

## Details

Arguments for the MUSCLE algorithm are either options or flags. Options take a variety of values, but flags are always logicals (TRUE or FALSE). All options and flags are explained in detail on the MUSCLE website: [http://www.drive5.com/muscle/muscle\\_userguide3.8.html](http://www.drive5.com/muscle/muscle_userguide3.8.html)

**Value**

Output is an object of class `MultipleAlignment`: `DNAMultipleAlignment`, `RNAMultipleAlignment`, or `AAMultipleAlignment`.

**Note**

For further details see the MUSCLE website: <http://www.drive5.com/muscle/>

**Author(s)**

Algorithm by Robert C. Edgar. Ported into R by Alex T. Kalinka <[alex.t.kalinka@gmail.com](mailto:alex.t.kalinka@gmail.com)>

**References**

Edgar, R.C. (2004) MUSCLE: multiple sequence alignment with high accuracy and high throughput. *Nucleic Acids Res* **32**, 1792-1797.

**See Also**

[umax](#)

**Examples**

```
## Align sequences in an XStringSet object.
aln <- muscle(stringset = umax)

## Switch on the diags flag.
aln <- muscle(stringset = umax, diags = TRUE)
```

---

umax

*Unaligned MAX sequences*

---

**Description**

Unaligned DNA sequences of the MAX gene for 31 mammalian species.

**Usage**

```
umax
```

**Format**

An object of class `DNAMultipleAlignment`.

**Value**

An object of class `DNAMultipleAlignment`.

**Source**

<http://www.ensembl.org/index.html>

**References**

Wagner, AJ et al. (1992) Expression, regulation, and chromosomal localization of the Max gene. *Proc Natl Acad Sci USA* **89**: 3111-3115.

# Index

## \*Topic **datasets**

umax, [3](#)

AAMultipleAlignment, [3](#)

AAStringSet, [2](#)

DNAMultipleAlignment, [3](#)

DNAStrngSet, [2](#), [3](#)

MultipleAlignment, [3](#)

muscle, [2](#), [2](#)

muscle-package, [1](#)

RNAMultipleAlignment, [3](#)

RNAStrngSet, [2](#)

umax, [2](#), [3](#), [3](#)

XStringSet, [2](#)