

Package 'PWMEnrich.Dmelanogaster.background'

April 12, 2018

Maintainer Robert Stojnic <robert.stojnic@gmail.com>

License GPL-3

Title D. melanogaster background for PWMEnrich

Type Package

LazyLoad yes

Author Robert Stojnic

Description PWMEnrich pre-compiled background objects for Drosophila melanogaster and MotifDb D. melanogaster motifs.

Version 4.12.0

biocViews Drosophila_melanogaster_Data

Date 2015-09-30

Depends methods, PWMEnrich

NeedsCompilation no

R topics documented:

PWMEnrich.Dmelanogaster.background-package	1
Index	3

PWMEnrich.Dmelanogaster.background-package

PWMEnrich.Dmelanogaster.background package overview

Description

This package provides a set of pre-compiled genomic background files for the PWMEnrich package and D. melanogaster. The backgrounds were pre-compiled using unique promoters of Drosophila melanogaster.

- MotifDb.Dmel.PFM - a list of 740 position frequency matrices (PFMs) from MotifDb
- MotifDb.Dmel - the corresponding PWMs generated by using the background frequencies of A,C,G,T in a set of 10031 2kb promoters in D. Melanogaster.

- `PWMLogn.dm3.MotifDb.Dmel` - pre-compiled threshold-free lognormal background for JASPAR insects PWMs. The lognormal distribution is fitted to 1kb fragments of 10031 2kb *Drosophila Melanogaster* (dm3) promoters. For each gene one promoter is taken (from the first transcript).
- `PWMCutoff4.dm3.MotifDb.Dmel`, `PWMCutoff5.dm3.MotifDb.Dmel` - pre-compiled Z-score background with cutoff of 4 and 5 (base e) for JASPAR insects PWMs. The number of hits above the score cutoff is counted in 10031 2kb *Drosophila Melanogaster* (dm3) promoters. For each gene one promoter is taken (from the first transcript).
- `PWMPvalueCutoff1e2.dm3.MotifDb.Dmel`, `PPWMPvalueCutoff1e3.dm3.MotifDb.Dmel`, `PPWMPvalueCutoff1e4.dm3.MotifDb.Dmel` - pre-compiled Z-score background with P-value cutoff of 0.01, 0.001, and 0.0001 for JASPAR insects PWMs. The number of hits with smaller P-value than cutoff is counted in 10031 2kb *Drosophila Melanogaster* (dm3) promoters. For each gene one promoter is taken (from the first transcript).

Usage

```
data(MotifDb.Dmel.PFM)
data(MotifDb.Dmel)
data(PWMLogn.dm3.MotifDb.Dmel)
data(PWMCutoff4.dm3.MotifDb.Dmel)
data(PWMCutoff5.dm3.MotifDb.Dmel)
data(PWMPvalueCutoff1e2.dm3.MotifDb.Dmel)
data(PWMPvalueCutoff1e3.dm3.MotifDb.Dmel)
data(PWMPvalueCutoff1e4.dm3.MotifDb.Dmel)
```

Details

All of these objects were created with the appropriate functions available in the `PWMEnrich` package (see Section 'See also'). We recommend using these functions to generate backgrounds for a custom set of background sequences and/or DNA motifs.

This package also contains the 2kb upstream sequences for *Drosophila* genes (`dm3.upstream2000`) which were removed from the `BSgenome.Drosophila.UCSC.dm3` package starting from Bioconductor version 3.0.

Author(s)

Robert Stojnic
 Cambridge Systems Biology Centre
 University of Cambridge, UK
 Maintainer: Robert Stojnic <robert.stojnic@gmail.com>

See Also

[makeBackground](#), [makePWMLognBackground](#), [makePWCutoffBackground](#), [makePWMEmpiricalBackground](#).

Examples

```
data(PWMLogn.dm3.MotifDb.Dmel)

res = motifEnrichment(DNAString("TGCATCAAGTGTGTAGTGCATGAATGC"), PWMLogn.dm3.MotifDb.Dmel)

head(motifRankingForGroup(res))
```

Index

*Topic **package**

PWMErich.Dmelanogaster.background-package,
[1](#)

dm3.upstream2000
(PWMErich.Dmelanogaster.background-package),
[1](#)

makeBackground, [2](#)
makePWMCutoffBackground, [2](#)
makePWMEmpiricalBackground, [2](#)
makePWMLognBackground, [2](#)

MotifDb.Dmel
(PWMErich.Dmelanogaster.background-package),
[1](#)

PWMCutoff4.dm3.MotifDb.Dmel
(PWMErich.Dmelanogaster.background-package),
[1](#)

PWMCutoff5.dm3.MotifDb.Dmel
(PWMErich.Dmelanogaster.background-package),
[1](#)

PWMErich.Dmelanogaster.background
(PWMErich.Dmelanogaster.background-package),
[1](#)

PWMErich.Dmelanogaster.background-package,
[1](#)

PWMLogn.dm3.MotifDb.Dmel
(PWMErich.Dmelanogaster.background-package),
[1](#)

PWMPvalueCutoff1e2.dm3.MotifDb.Dmel
(PWMErich.Dmelanogaster.background-package),
[1](#)

PWMPvalueCutoff1e3.dm3.MotifDb.Dmel
(PWMErich.Dmelanogaster.background-package),
[1](#)

PWMPvalueCutoff1e4.dm3.MotifDb.Dmel
(PWMErich.Dmelanogaster.background-package),
[1](#)