

Package ‘hipathia’

April 16, 2019

Title HiPathia: High-throughput Pathway Analysis

Version 1.4.1

Description Hipathia is a method for the computation of signal transduction along signaling pathways from transcriptomic data. The method is based on an iterative algorithm which is able to compute the signal intensity passing through the nodes of a network by taking into account the level of expression of each gene and the intensity of the signal arriving to it. It also provides a new approach to functional analysis allowing to compute the signal arriving to the functions annotated to each pathway.

Depends R (>= 3.5), igraph (>= 1.0.1), AnnotationHub(>= 2.6.5), MultiAssayExperiment(>= 1.4.9), SummarizedExperiment(>= 1.8.1)

License GPL-2

Encoding UTF-8

LazyData true

Imports coin, stats, limma, grDevices, utils, graphics, preprocessCore, servr, DelayedArray, matrixStats, methods, S4Vectors

RoxygenNote 6.0.1

Suggests BiocStyle, knitr, rmarkdown, testthat

VignetteBuilder knitr

biocViews Pathways, GraphAndNetwork, GeneExpression, GeneSignaling, GO

git_url <https://git.bioconductor.org/packages/hipathia>

git_branch RELEASE_3_8

git_last_commit 6296d69

git_last_commit_date 2019-02-06

Date/Publication 2019-04-15

Author Marta R. Hidalgo [aut, cre],
José Carbonell-Caballero [ctb],
Francisco Salavert [ctb],
Alicia Amadoz [ctb],
Çankut Cubuk [ctb],
Joaquin Dopazo [ctb]

Maintainer Marta R. Hidalgo <marta.hidalgo@outlook.es>

R topics documented:

annotate_paths	3
brca	3
brca_data	4
brca_design	5
comp	5
create_report	6
do_pca	7
do_wilcoxon	7
exp_data	8
get_highest_sig_ancestor	9
get_paths_data	9
get_pathways_annotations	10
get_pathways_list	11
get_pathways_summary	11
get_pathway_functions	12
get_path_names	13
go_vals	13
heatmap_plot	14
hhead	15
hipathia	16
igraphs_upgrade	17
is_accepted_species	17
load_annotfuns	18
load_annots	18
load_entrez_hgnc	19
load_gobp_frame	19
load_gobp_net	19
load_mgi	20
load_pathways	20
load_pseudo_mgi	21
load_xref	21
multiple_pca_plot	22
node_color_per_de	23
normalize_data	24
normalize_paths	25
paths_to_go_ancestor	26
pathway_comparison_plot	27
path_vals	28
pca_plot	28
quantify_terms	29
results	30
save_results	31
top_pathways	31
translate_data	32
translate_matrix	33
visualize_report	33

annotate_paths *Annotates functions to pathways*

Description

Annotates functions from a database to each pathway

Usage

```
annotate_paths(metainfo, dbannot)
```

Arguments

metainfo	Pathways object
dbannot	Either a string indicating which precomputed annotation to use ("uniprot" for Uniprot Keywords or "GO" for Gene Ontology terms), or a dataframe with the annotation of the genes to the functions. First column are gene symbols, second column the functions.

Value

Object of annotations from pathways to functions

```
#@examples #pathways <- load_pathways(species = "hsa", pathways_list = c("hsa03320", #"hsa04012"))
#annotate_paths(pathways, "GO")
#@export
```

brca *BRCA gene expression dataset as SummarizedExperiment*

Description

A dataset containing a matrix with the Gene expression of 40 samples from the BRCA-US project from The Cancer Genome Atlas (TCGA), and their experimental design, containing 20 "Tumor" samples 20 "Normal" samples.

Usage

```
data(brca)
```

Format

SummarizedExperiment. The assay is a matrix with 40 columns and 18638 rows. Row names are Entrez IDs and column names are the TCGA identifiers of the samples. The colData() is a data.frame with 1 column and 40 rows, including the experimental design of the 40 samples from the BRCA-US project from TCGA. Field group is the type of sample, either "Tumor" or "Normal".

Details

The gene expression matrix includes 40 samples. The data has been log-transformed and normalized with TMM.

Value

SummarizedExperiment including a matrix with 40 columns and 18638 rows. Row names are Entrez IDs and column names are the TCGA identifiers of the samples.

Source

<https://cancergenome.nih.gov/>

brca_data

BRCA gene expression dataset

Description

Gene expression of 40 samples from the BRCA-US project from The Cancer Genome Atlas (TCGA).

Usage

```
data(brca_data)
```

Format

Matrix with 40 columns and 18638 rows. Row names are Entrez IDs and column names are the TCGA identifiers of the samples.

Details

Gene expression matrix with 40 samples taken from the BRCA-US project from The Cancer Genome Atlas (TCGA). The data has been log-transformed and normalized with TMM.

Value

Matrix with 40 columns and 18638 rows. Row names are Entrez IDs and column names are the TCGA identifiers of the samples.

Source

<https://cancergenome.nih.gov/>

brca_design	<i>BRCA experimental design</i>
-------------	---------------------------------

Description

Experimental design of the gene expression matrix `brca_data` with 40 samples taken from the BRCA-US project from The Cancer Genome Atlas (TCGA). 20 samples are "Tumor" samples and 20 samples are "Normal" samples.

Usage

```
data(brca_design)
```

Format

Dataframe with 1 column and 40 rows, including the experimental design of the 40 samples from the BRCA-US project from TCGA. Field `group` is the type of sample, either "Tumor" or "Normal".

Value

Dataframe with 1 column and 40 rows, including the experimental design of the 40 samples from the BRCA-US project from TCGA. Field `group` is the type of sample, either "Tumor" or "Normal".

Source

<https://cancergenome.nih.gov/>

comp	<i>Wilcoxon comparison of pathways object</i>
------	---

Description

Comparison object returned by `hipathia::do_wilcoxon` function, after calling `comp <- do_wilcoxon(path_vals, sa, "Normal")` `path_names <- get_path_names(pathways, rownames(comp))` `comp <- cbind(path_names, comp)`

Usage

```
data(comp)
```

Format

Table with 1868 rows and 5 columns

Value

Pathway comparison result

create_report	<i>Create visualization HTML</i>
---------------	----------------------------------

Description

Saves the results of a Wilcoxon comparison for the Hipathia pathway values into a folder, and creates a HTML from which to visualize the results on top of the pathways. The results are stored into the specified folder. If this folder does not exist, it will be created. The parent folder must exist.

Usage

```
create_report(comp, metainfo, output_folder = NULL, path = NULL,
  node_colors = NULL, group_by = "pathway", conf = 0.05,
  verbose = FALSE)
```

Arguments

comp	Comparison object as given by the <code>do_wilcoxon</code> function
metainfo	Pathways object as returned by the <code>load_pathways</code> function
output_folder	Name of the folder in which the report will be stored.
path	Absolute path to the parent directory in which 'output_folder' will be saved. If it is not provided, it will be created in a temp folder.
node_colors	List of colors with which to paint the nodes of the pathways, as returned by the <code>node_color_per_de</code> function. Default is white.
group_by	How to group the subpathways to be visualized. By default they are grouped by the pathway to which they belong. Available groupings include "uniprot", to group subpathways by their annotated Uniprot functions, "GO", to group subpathways by their annotated GO terms, and "genes", to group subpathways by the genes they include. Default is set to "pathway".
conf	Level of significance. By default 0.05.
verbose	Boolean, whether to show details about the results of the execution

Value

Saves the results and creates a report to visualize them through a server in the specified `output_folder`. Returns the folder where the report has been stored.

Examples

```
data(comp)
pathways <- load_pathways(species = "hsa", pathways_list = c("hsa03320",
  "hsa04012"))
report <- create_report(comp, pathways, "save_results")

## Not run:
data(results)
data(brca)
sample_group <- colData(brca)[,1]
colors_de <- node_color_per_de(results, pathways,
  sample_group, "Tumor", "Normal")
```

```
report_colors <- create_report(comp, pathways, "save_results",
node_colors = colors_de)

## End(Not run)
```

do_pca *Performs a Principal Components Analysis*

Description

Performs a Principal Components Analysis

Usage

```
do_pca(data, sel_assay = 1, cor = FALSE)
```

Arguments

data	SummarizedExperiment or matrix of values to be analyzed. Samples must be represented in the columns.
sel_assay	Character or integer, indicating the assay to be normalized in the Summarized-Experiment. Default is 1.
cor	A logical value indicating whether the calculation should use the correlation matrix or the covariance matrix. (The correlation matrix can only be used if there are no constant variables.)

Value

do_pca returns a list with class `princomp`.

Examples

```
data(path_vals)
pca_model <- do_pca(path_vals[seq_len(ncol(path_vals)),])
```

do_wilcoxon *Apply Wilcoxon test*

Description

Performs a Wilcoxon test for the values in `sel_vals` comparing conditions `g1` and `g2`

Usage

```
do_wilcoxon(data, group, g1, g2, paired = FALSE, adjust = TRUE,
sel_assay = 1, order = FALSE)
```

Arguments

data	Either a SummarizedExperiment object or a matrix, containing the values. Columns represent samples.
group	Either a character indicating the name of the column in colData including the classes to compare, or a character vector with the class to which each sample belongs. Samples must be ordered as in data
g1	String, label of the first group to be compared
g2	String, label of the second group to be compared
paired	Boolean, whether the samples to be compared are paired. If TRUE, function wilcoxsign_test from package coin is used. If FALSE, function wilcox.test from package stats is used.
adjust	Boolean, whether to adjust the p.value with Benjamini-Hochberg FDR method
sel_assay	Character or integer, indicating the assay to be normalized in the SummarizedExperiment. Default is 1.
order	Boolean, whether to order the results table by the FDRp.value column. Default is FALSE.

Value

Dataframe with the result of the comparison

Examples

```
data(path_vals)
data(brca_design)
sample_group <- brca_design[colnames(path_vals), "group"]
comp <- do_wilcoxon(path_vals, sample_group, g1 = "Tumor", g2 = "Normal")
```

exp_data

Normalized BRCA gene expression dataset

Description

Experimental design matrix once expression matrix brca_data has been translated to Entrez genes with translate_matrix and normalized using normalize_data.

Usage

```
data(exp_data)
```

Format

Matrix with 40 columns and 3184 rows. Row names are Entrez IDs and column names are the TCGA identifiers of the samples.

Details

To create the data, the following functions have been called: trans_data <- translate_matrix(brca_data, "hsa")
exp_data <- normalize_data(trans_data)

Value

Matrix with 40 columns and 3184 rows. Row names are Entrez IDs and column names are the TCGA identifiers of the samples.

```
get_highest_sig_ancestor
```

Get highest common GO ancestor of GO annotations

Description

Get highest common GO ancestor of GO annotations

Usage

```
get_highest_sig_ancestor(go_terms, go_comp, metainfo, unique = TRUE,
  pval = 0.05)
```

Arguments

go_terms	GO terms for which the highest common ancestors are to be looked for.
go_comp	Wilcoxon comparison of the matrix of GO values as returned by do_wilcoxon.
metainfo	Pathways object
unique	Boolean, whether to return only one highest significant GO ancestor or all of them. By default, TRUE.
pval	P-value cut-off. Default values is set to 0.05.

Value

highest common ancestors
#@export

```
get_paths_data
```

Gets the object of subpathway activation values

Description

This function returns the object with the levels of activation of each subpathway for each sample. Rows represent the subpathways and columns represent the samples. Each cell is the value of activation of a subpathway in a sample.

Rownames are the IDs of the subpathways. In order to transform IDs into readable names, use get_path_names.

Effector subpathways are subgraphs of a pathway including all the paths leading to an effector protein. Effector proteins are defined as final nodes in the graph. Each effector protein (final node) in a pathway defines its own effector subpathway as the nodes and edges in a path leading to it.

Decomposed subpathways are subgraphs of a pathway including all the paths starting in a receptor protein and ending in an effector protein. Receptor proteins are defined as initial nodes and effector proteins are defined as final nodes in the graph. Each effector subpathway can be decomposed in as many decomposed subpathways as initial nodes it includes.

Usage

```
get_paths_data(results, matrix = FALSE)
```

Arguments

results	Results object as returned by hipathia.
matrix	Boolean, if TRUE the function returns a matrix object, if FALSE (as default) returns a SummarizedExperiment object.

Value

Object, either a SummarizedExperiment or a matrix, with the levels of activation of each decomposed subpathway for each sample.

Examples

```
data(results)
path_vals <- get_paths_data(results)
```

```
get_pathways_annotatons
```

Get Pathways functional annotations

Description

Get functional annotation of the pathways, either for a particular annotation or a stored one.

Usage

```
get_pathways_annotatons(pathway_names, metainfo, dbannot, collapse = FALSE)
```

Arguments

pathway_names	Character vector of the names of the pathways
metainfo	Pathways object
dbannot	Either a string indicating which precomputed annotation to use ("uniprot" for Uniprot Keywords or "GO" for Gene Ontology terms), or a dataframe with the annotation of the genes to the functions. First column are gene symbols, second column the functions.
collapse	Boolean, whether to collapse all functions of the same path in a single character string.

Value

2-columns matrix with the annotations of each pathway ID in the annotation dbannot.

Examples

```
pathways <- load_pathways(species = "hsa", pathways_list = c("hsa03320",
"hsa04012"))
pathway_names <- c("P-hsa03320-37", "P-hsa03320-61", "P-hsa03320-46",
"P-hsa03320-57", "P-hsa03320-64", "P-hsa03320-47", "P-hsa03320-65")
## Not run: get_pathways_annotiations(pathway_names, pathways, "GO")
get_pathways_annotiations(pathway_names, pathways, "uniprot")
```

get_pathways_list *Lists the IDs of the pathways in a pathways object*

Description

Lists the IDs of the pathways included in the pathways object metainfo

Usage

```
get_pathways_list(metainfo)
```

Arguments

metainfo Pathways object

Value

List of the pathway IDs included in the pathways object

Examples

```
pathways <- load_pathways(species = "hsa", pathways_list = c("hsa03320",
"hsa04012"))
pathways_list <- get_pathways_list(pathways)
```

get_pathways_summary *Compute pathway summary*

Description

Computes a summary of the results, summarizing the number and proportion of up- and down-regulated subpathways in each pathway.

Usage

```
get_pathways_summary(comp, metainfo, conf = 0.05)
```

Arguments

comp Comparison data frame as returned by the do_wilcoxon function.
metainfo Pathways object
conf Level of significance of the comparison for the adjusted p-value. Default is 0.05.

Value

Table with the summarized information for each of the pathways. Rows are the analyzed pathways. Columns are: * num_total_paths Number of total subpathways in which each pathway is decomposed. * num_significant_paths Number of significant subpathways in the provided comparison. * percent_significant_paths Percentage of significant subpathways from the total number of subpathways in a pathway. * num_up_paths Number of significant up-regulated subpathways in the provided comparison. * percent_up_paths Percentage of significant up-regulated subpathways from the total number of subpathways in a pathway. * num_down_paths Number of significant down-regulated subpathways in the provided comparison. * percent_down_paths Percentage of significant down-regulated subpathways from the total number of subpathways in a pathway.

Examples

```
data(comp)
pathways <- load_pathways(species = "hsa", pathways_list = c("hsa03320",
"hsa04012"))
get_pathways_summary(comp, pathways)
```

get_pathway_functions *Returns functions related to a pathway*

Description

Returns functions related to a pathway

Usage

```
get_pathway_functions(pathigraph, dbannot, entrez2hgnc, use_last_nodes = TRUE,
unique = TRUE)
```

Arguments

pathigraph	Pathway object
dbannot	Dataframe with the annotation of the genes to the functions. First column are gene symbols, second column the functions.
entrez2hgnc	Relation between Entrez and HGNC genes.
use_last_nodes	Boolean, whether to annotate functions to the last nodes of the pathways or not. If FALSE, functions will refer to all the nodes of the pathway.
unique	Boolean, whether to return the first function for each path.

Value

List of annotations from pathways to functions

get_path_names	<i>Tranlates path IDs to path names</i>
----------------	---

Description

Translates the subpathway IDs to readable and comprehensible names.

For effector subpathways, the names of the subpathways are encoded as "pathway: effector_protein", where "pathway" is the pathway to which the subpathway belongs and "effector_protein" is the name of the last node in the subpathway.

For decomposed subpathways, the names of the subpathways are encoded as "pathway: receptor_protein - effector_protein", where "pathway" is the pathway to which the subpathway belongs, "receptor_protein" is the name of the initial node of the subpathway and "effector_protein" is the name of the last node in the subpathway.

Usage

```
get_path_names(metainfo, names, maxchar = NULL)
```

Arguments

metainfo	Pathways object
names	Character vector with the subpathway IDs to be translated
maxchar	Integer, describes the number of maximum characters to be shown. By default no filter is applied.

Value

A character vector including the readable names of the subpathways IDs, in the same order as provided.

Examples

```
data(path_vals)
pathways <- load_pathways(species = "hsa", pathways_list = c("hsa03320",
"hsa04012"))
translated_names <- get_path_names(pathways, rownames(path_vals))
```

go_vals	<i>Gene Ontology matrix of the BRCA gene expression dataset</i>
---------	---

Description

Matrix of Gene Ontology terms activation values for the BRCA dataset. This matrix is computed from the Results object returned by the hipathia function by means of the quantify_terms function.

Usage

```
data(go_vals)
```

Format

Matrix with 40 columns and 1654 rows. Row names are Gene Ontology terms and column names are the TCGA identifiers of the samples.

Details

```
go_vals <- quantify_terms(results, pathways, "GO")
```

Value

Matrix with 40 columns and 1654 rows. Row names are Gene Ontology terms and column names are the TCGA identifiers of the samples.

heatmap_plot	<i>Plots subpathways heatmap</i>
--------------	----------------------------------

Description

Plots a heatmap with the values of the subpathways.

Usage

```
heatmap_plot(data, group = NULL, sel_assay = 1, colors = "classic",
  sample_clust = TRUE, variable_clust = FALSE, labRow = NULL,
  labCol = NULL, sample_colors = NULL, scale = TRUE, save_png = NULL,
  legend = TRUE, legend_xy = "topright", pch = 15, main = NULL)
```

Arguments

data	Either a SummarizedExperiment or a matrix with the values to be plotted. Rows are features and columns are samples.
group	Either a character indicating the name of the column in colData including the classes to plot, or a character vector with the class to which each sample belongs. Samples must be ordered as in data. By default, all samples will be assigned to the same class.
sel_assay	Character or integer, indicating the assay to be normalized in the Summarized-Experiment. Default is 1.
colors	Either a character vector with colors or a key name indicating the color scheme to be used in the heatmap. If a character vector is provided, it is recommended to provide at least 3 colors. Three different predefined color schemes may be selected by providing a key name. Options are: * classic Blue for lower values, white for medium values, red for higher values. * hipathia Hipathia predefined color scheme: Green for lower values, white for medium values, orange for higher values. * redgreen Green for lower values, black for medium values, red for higher values. By default classic color scheme is applied.
sample_clust	Boolean, whether to cluster samples (columns). By default TRUE.
variable_clust	Boolean, whether to cluster variables (rows). By default FALSE. If TRUE, rows with 0 variance are removed.

labRow, labCol	Character vectors with row and column labels to be used. By default rownames(data) or colnames(data) are used, respectively.
sample_colors	Named character vector of colors. The names of the colors must be the classes in group. Each sample will be assigned the color corresponding to its class, taken from the group vector. By default a color will be assigned automatically to each class.
scale	Boolean, whether to scale each row to the interval [0,1]. Default is TRUE.
save_png	Path to the file where the image as PNG will be saved. By default, the image is not saved.
legend	Boolean, whether to display a legend.
legend_xy	Position for the legend, in case legend is TRUE.
pch	Graphical parameter from par() function.
main	Main title of the image

Value

Heatmap of the values of the subpathways

Examples

```
data(brca_design)
data(path_vals)
sample_group <- brca_design[colnames(path_vals), "group"]
heatmap_plot(path_vals, group = sample_group)
heatmap_plot(path_vals, group = sample_group, colors = "hipathia",
variable_clust = TRUE)
```

hhead	<i>Head function for SummarizedExperiment, data.frames and matrix objects</i>
-------	---

Description

Shows the first n rows and the first n columns of a matrix, in case the matrix has more than $n+5$ rows or columns. Otherwise, it shows all the rows or columns, respectively.

Usage

```
hhead(mat, n = 5, sel_assay = 1)
```

Arguments

mat	Object to be shown
n	Number of rows and columns
sel_assay	Character or integer, indicating the assay to be translated in the SummarizedExperiment. Default is 1.

Value

Matrix with as much as n rows and n columns.

Examples

```
mat <- matrix(rnorm(100), ncol = 10)
hhead(mat)
hhead(mat, 3)
hhead(mat, 7)
```

hipathia	<i>Computes the level of activation of the subpathways for each of the samples</i>
----------	--

Description

```
#@importFrom igraph
```

Usage

```
hipathia(genes_vals, metainfo, sel_assay = 1, decompose = FALSE,
         maxnum = 100, verbose = TRUE, tol = 1e-06, test = TRUE)
```

Arguments

genes_vals	A SummarizedExperiment or matrix with the normalized expression values of the genes. Rows represent genes and columns represent samples. Rownames() must be accepted gene IDs.
metainfo	Pathways object
sel_assay	Character or integer, indicating the assay to be processed in the SummarizedExperiment. Only applied if genes_vals is a SummarizedExperiment. Default is 1.
decompose	Boolean, whether to compute the values for the decomposed subpathways. By default, effector subpathways are computed.
maxnum	Number of maximum iterations when iterating the signal through the loops into the pathways
verbose	Boolean, whether to show details about the results of the execution of hipathia
tol	Tolerance for the difference between two iterations when iterating the signal through the loops into the pathways
test	Boolean, whether to test the input objects. Default is TRUE.

Value

A MultiAssayExperiment object with the level of activation of the subpathways from the pathways in pathigraphs for the experiment with expression values in genes_vals.

Examples

```

data(exp_data)
pathways <- load_pathways(species = "hsa", pathways_list = c("hsa03320",
"hsa04012"))
results <- hipathia(exp_data, pathways, verbose = TRUE)
## Not run: results <- hipathia(exp_data, pathways, decompose = TRUE,
verbose = FALSE)
## End(Not run)

```

igraphs_upgrade	<i>Upgrade igraphs to current version</i>
-----------------	---

Description

Upgrades the igraph objects in metainfo object to the corresponding version of the igraph package.

Usage

```
igraphs_upgrade(metainfo)
```

Arguments

metainfo Pathways object

Value

The pathways object with the upgraded igraph objects

is_accepted_species	<i>Checks whether a species is accepted</i>
---------------------	---

Description

Checks whether a species is accepted

Usage

```
is_accepted_species(species)
```

Arguments

species Species of the samples.
#@examples #is_accepted_species("hsa") #is_accepted_species("fca")

Value

Boolean, whether species is accepted or not.

load_annotfuns	<i>Loads annotations object</i>
----------------	---------------------------------

Description

Loads annotations object

Usage

```
load_annotfuns(db, species)
```

Arguments

db	Database to be used. Either "GO" or "uniprot".
species	Species of the samples. #@examples #load_annotfuns("GO", "hsa") #load_annotfuns("uniprot", "hsa")

Value

Annotations object

load_annots	<i>Loads functional annotations to genes</i>
-------------	--

Description

Loads functional annotations from HGNC to the selected database.

Usage

```
load_annots(db, species)
```

Arguments

db	Database to be used. Either "GO" or "uniprot".
species	Species of the samples. #@examples #load_annots("GO", "hsa")

Value

Functional annotations from HGNC to the selected database.

load_entrez_hgnc	<i>Loads table of translation from HGNC to Entrez</i>
------------------	---

Description

Loads table of translation from HGNC to Entrez

Usage

```
load_entrez_hgnc(species)
```

Arguments

species	Species of the samples. #@examples #load_entrez_hgnc("hsa")
---------	--

Value

Table of translation from HGNC to Entrez

load_gobp_frame	<i>Loads GO graph information</i>
-----------------	-----------------------------------

Description

```
#@examples #load_gobp_frame()
```

Usage

```
load_gobp_frame()
```

Value

GO graph information

load_gobp_net	<i>Loads GO graph</i>
---------------	-----------------------

Description

```
#@examples #load_gobp_net()
```

Usage

```
load_gobp_net()
```

Value

GO graph

load_mgi	<i>Loads object with graph information</i>
----------	--

Description

Loads object with graph information

Usage

```
load_mgi(species)
```

Arguments

species	Species of the samples. #@examples #load_mgi("hsa")
---------	--

Value

Graph information object

load_pathways	<i>Loads the pathways object.</i>
---------------	-----------------------------------

Description

Loads the pathways object, which includes information about the pathways to be analyzed.

Usage

```
load_pathways(species, pathways_list = NULL)
```

Arguments

species	Species of the samples.
pathways_list	Vector of the IDs of the pathways to load. By default all available pathways are load.

Details

The object of pathways includes information about the pathways and the subpathways which will be analyzed. This object must be provided to some of the functions (like `hipathia` or `quantify_terms`) in the package. These functions will analyze all the pathways included in this object. By default, all available pathways are load. In order to restrict the analysis to a predefined set of pathways, specify the set of pathways to load with the parameter `pathways_list`.

Value

An pathways object including * `species` Species to which the pathways are related. * `pathigraphs` List of Pathigraph objects. Each Pathigraph contains the necessary information of a pathway for it to be analyzed with `Hipathia`. * `all_genes` List of all the genes included in the selection of pathways stored in `pathigraphs`. * `eff_norm` Vector of normalization values for effector subpathways. * `path_norm` Vector of normalization values for decomposed subpathways.

Examples

```
## Not run: pathways <- load_pathways("hsa") # Loads all pathways for human
pathways <- load_pathways("mmu", c("mmu03320", "mmu04024", "mmu05200"))
# Loads pathways 03320, 04024 and 05200 for mouse
```

load_pseudo_mgi	<i>Loads object with pseudo graph information</i>
-----------------	---

Description

Loads object with pseudo graph information

Usage

```
load_pseudo_mgi(species, group_by)
```

Arguments

species	Species of the samples.
group_by	How to group the subpathways to be visualized. By default they are grouped by the pathway to which they belong. Available groupings include "uniprot", to group subpathways by their annotated Uniprot functions, "GO", to group subpathways by their annotated GO terms, and "genes", to group subpathways by the genes they include. #@examples #load_pseudo_mgi("hsa", "uniprot")

Value

Pseudo graph information object

load_xref	<i>Loads table of references</i>
-----------	----------------------------------

Description

Loads table of references

Usage

```
load_xref(species)
```

Arguments

species	Species of the samples. #@examples #load_xref("hsa")
---------	---

Value

Table of references

multiple_pca_plot *Plots multiple components of a PCA*

Description

Plots multiple components of a PCA analysis computed with `do_pca`

Usage

```
multiple_pca_plot(fit, group = NULL, sample_colors = NULL,
  comps = seq_len(3), plot_variance = FALSE, legend = TRUE, cex = 2,
  pch = 20, main = "Multiple PCA plot", save_png = NULL)
```

Arguments

<code>fit</code>	princomp object as returned by <code>do_pca</code>
<code>group</code>	Vector with the group to which each sample belongs. The samples must be ordered as in <code>path_vals</code> . By default, all samples will be assigned to the same class.
<code>sample_colors</code>	Named character vector of colors. The names of the colors must be the classes in <code>group</code> . Each sample will be assigned the color corresponding to its class, taken from the group vector. By default a color will be assigned automatically to each class.
<code>comps</code>	Vector with the components to be plot
<code>plot_variance</code>	Logical, whether to plot the cumulative variance.
<code>legend</code>	Boolean, whether to plot a legend in the plot. Default is TRUE.
<code>cex</code>	Graphical parameter from <code>par()</code> function.
<code>pch</code>	Graphical parameter from <code>par()</code> function.
<code>main</code>	Main title of the image
<code>save_png</code>	Path to the file where the image as PNG will be saved. By default, the image is not saved.

Value

Plots multiple components of a PCA

Examples

```
data(path_vals)
sample_group <- brca_design[colnames(path_vals), "group"]
pca_model <- do_pca(path_vals[seq_len(ncol(path_vals)),])
multiple_pca_plot(pca_model, sample_group, cex = 3, plot_variance = TRUE)
```

node_color_per_de *Colors of the nodes by its differential expression*

Description

Performs a differential expression on the nodes and computes the colors of the nodes depending on it_ Significant up- and down-regulated nodes are depicted with the selected color, with a gradient towards the non-significant color depending on the value of the p-value. Smaller p-values give rise to purer colors than higher p-values.

Usage

```
node_color_per_de(results, metainfo, group, g1, g2, group_by = "pathway",
  colors = "classic", conf = 0.05)
```

Arguments

results	Object of results as provided by the hipathia function_
metainfo	Object of pathways_
group	Character indicating the column in which the group variable is stored, in case the object provided to hipathia was a SummarizedExperiment, or a vector with the class to which each sample belongs. Samples must be ordered as in results.
g1	String, label of the first group to be compared
g2	String, label of the second group to be compared
group_by	How to group the subpathways to be visualized. By default they are grouped by the pathway to which they belong. Available groupings include "uniprot", to group subpathways by their annotated Uniprot functions, "GO", to group subpathways by their annotated GO terms, and "genes", to group subpathways by the genes they include. Default is set to "pathway".
colors	Either a character vector with 3 colors (indicating, in this order, down-regulation, non-significance and up-regulation colors) or a key name indicating the color scheme to be used. Options are:
conf	Level of significance of the comparison for the adjusted p-value

Value

List of color vectors, named by the pathways to which they belong. The color vectors represent the differential expression of the nodes in each pathway.

Slots

classic ColorBrewer blue, white and colorBrewer red.

hipathia Hipathia predefined color scheme: Green, white and orange. By default classic color scheme is applied.

Examples

```

data(results)
data(brca)
pathways <- load_pathways(species = "hsa", pathways_list = c("hsa03320",
"hsa04012"))
sample_group <- colData(brca)[,1]
colors_de <- node_color_per_de(results, pathways,
sample_group, "Tumor", "Normal")

```

normalize_data	<i>Normalize expression data from a SummarizedExperiment or matrix to be used in hipathia</i>
----------------	---

Description

Transforms the rank of the SummarizedExperiment or matrix of gene expression to [0,1] in order to be processed by hipathia. The transformation may be performed in two different ways. If `percentil = FALSE`, the transformation is a re-scaling of the rank of the matrix. If `percentil = TRUE`, the transformation is performed assigning to each cell its percentil in the corresponding distribution. This option is recommended for distributions with very long tails.

Usage

```

normalize_data(data, sel_assay = 1, by_quantiles = FALSE, by_gene = FALSE,
percentil = FALSE, truncation_percentil = NULL)

```

Arguments

<code>data</code>	Either a SummarizedExperiment or a matrix of gene expression.
<code>sel_assay</code>	Character or integer, indicating the assay to be normalized in the Summarized-Experiment. Default is 1.
<code>by_quantiles</code>	Boolean, whether to normalize the data by quantiles. Default is FALSE.
<code>by_gene</code>	Boolean, whether to transform the rank of each row of the matrix to [0,1]. Default is FALSE.
<code>percentil</code>	Boolean, whether to take as value the percentil of each sample in the corresponding distribution.
<code>truncation_percentil</code>	Real number p in $[0,1]$. When provided, values beyond percentil p are truncated to the value of percentil p , and values beyond $1-p$ are truncated to percentil $1-p$. By default no truncation is performed.

Details

This transformation may be applied either to the whole matrix (by setting `by_gene = FALSE`), which we strongly recommend, or to each of the rows (by setting `by_gene = TRUE`), allowing each gene to have its own scale.

A previous quantiles normalization may be applied by setting `by_quantiles = TRUE`. This is recommended for noisy data.

For distributions with extreme outlayer values, a percentil p may be given to the parameter `truncation_percentil`. When provided, values beyond percentil p are truncated to the value of percentil p , and values beyond $1-p$ are truncated to percentil $1-p$. This step is performed before any other tranformation. By default no truncation is performed.

Value

Matrix of gene expression whose values are in $[0,1]$.

Examples

```
data("brca_data")
trans_data <- translate_data(brca_data, "hsa")
exp_data <- normalize_data(trans_data)
exp_data <- normalize_data(trans_data, by_quantiles = TRUE,
truncation_percentil=0.95)
```

normalize_paths	<i>Normalize the pathway matrix by rows</i>
-----------------	---

Description

Due to the nature of the Hipathia method, the length of a pathway may influence its signal rank. In order to compare signal values among subpathways, we strongly recommend to normalize the matrix with this normalization.

Usage

```
normalize_paths(path_vals, metainfo)
```

Arguments

path_vals	Matrix of the pathway values
metainfo	Pathways object

Details

This function removes the bias caused by the length of the subpathways by dividing by the value obtained from running the method with a basal value of 0.5 at each node.

Value

Matrix of normalized pathway values

Examples

```
data(path_vals)
pathways <- load_pathways(species = "hsa", pathways_list = c("hsa03320",
"hsa04012"))
path_normalized <- normalize_paths(path_vals, pathways)
```

paths_to_go_ancestor *Create path results table with highest significant GO ancestors*

Description

Create table of results with the comparison of the paths together with the GO functional annotation and the highest significant GO ancestor (HSGOA).

Usage

```
paths_to_go_ancestor(pathways, comp_paths, comp_go, pval = 0.05)
```

Arguments

pathways	Pathways object
comp_paths	Wilcoxon comparison of the matrix of pathways values as returned by do_wilcoxon.
comp_go	Wilcoxon comparison of the matrix of GO values as returned by do_wilcoxon.
pval	P-value cut-off. Default values is set to 0.05.

Details

The table returns in each row: the name of a pathway and its Wilcoxon comparison information (direction, adjusted p-value), the GO term to which the path is related (not necessarily unique), the Wilcoxon comparison information for this GO (direction, adjusted p-value), the HSGOA of this GO and its Wilcoxon comparison information (direction, adjusted p-value).

The HSGOA is computed as the GO term with minimum level from all the significant (with respect to value pval) ancestors of a GO. The level of a GO term is computed as the number of nodes in the shortest path from this GO term to the term "GO:0008150". The ancestors of a node are defined as all the nodes from which a path can be defined from the ancestor to the node.

Value

Table of comparisons with Highest common ancestors

Examples

```
data(comp)
data(go_vals)
data(brca_design)
data(path_vals)
sample_group <- brca_design[colnames(path_vals),"group"]
comp_go <- do_wilcoxon(go_vals, sample_group, g1 = "Tumor", g2 = "Normal")
## Not run: pathways <- load_pathways(species = "hsa", pathways_list =
c("hsa03320", "hsa04012"))
table <- paths_to_go_ancestor(pathways, comp, comp_go)
## End(Not run)
```

 pathway_comparison_plot

Plots pathway with colored significant paths

Description

Plots the layout of a pathway, coloring the significant subpathways in different colors depending on whether they are significantly up- or down-regulated. Nodes may be also colored providing a suitable list of colors for each node. Function `node_color_per_de` assigns colors to the nodes depending on their differential expression.

Usage

```
pathway_comparison_plot(comp, metainfo, pathway, conf = 0.05,
  node_colors = NULL, colors = "classic")
```

Arguments

<code>comp</code>	Comparison data frame as returned by the <code>do_wilcox</code> function.
<code>metainfo</code>	Pathways object.
<code>pathway</code>	Name of the pathway to be plotted.
<code>conf</code>	Level of significance of the comparison for the adjusted p-value. Default is 0.05.
<code>node_colors</code>	List, named by the pathway name, including the color of each node for each pathway.
<code>colors</code>	Either a character vector with 3 colors (indicating, in this order, down-regulation, non-significance and up-regulation colors) or a key name indicating the color scheme to be used. Options are:

Value

Image in which a pathway is plotted. Edges are colored so that the UP- and DOWN-activated subpathways are identified.

Slots

`classic` ColorBrewer blue, white and colorBrewer red.

`hipathia` Hipathia predefined color scheme: Green, white and orange. By default classic color scheme is applied.

Examples

```
data(comp)
pathways <- load_pathways(species = "hsa", pathways_list = c("hsa03320",
  "hsa04012"))
pathway_comparison_plot(comp, metainfo = pathways, pathway = "hsa03320")

## Not run:
data(results)
data(brca)
sample_group <- colData(brca)[,1]
```

```

colors_de <- node_color_per_de(results, pathways,
sample_group, "Tumor", "Normal")
pathway_comparison_plot(comp, metainfo = pathways, pathway = "hsa04012",
node_colors = colors_de)

## End(Not run)

```

path_vals

Pathways matrix of the BRCA gene expression dataset

Description

Matrix of pathway activation values for the BRCA dataset. This matrix is extracted from the Results object returned by the hipathia function by means of the get_paths_matrix function.

Usage

```
data(path_vals)
```

Format

Matrix with 40 columns and 1868 rows. Row names are Pathway IDs and column names are the TCGA identifiers of the samples.

Details

```
path_vals <- get_paths_matrix(results)
```

Value

Matrix with 40 columns and 1868 rows. Row names are Pathway IDs and column names are the TCGA identifiers of the samples.

pca_plot

Plots two components of a PCA

Description

Plots two components of a PCA computed with do_pca

Usage

```

pca_plot(fit, group = NULL, sample_colors = NULL, cp1 = 1, cp2 = 2,
legend = TRUE, legend_xy = "bottomleft", cex = 2, pch = 20,
mgp = c(3, 1, 0), main = "PCA plot", save_png = NULL)

```

Arguments

fit	princomp object as returned by do_pca
group	Vector with the group to which each sample belongs. The samples must be ordered as in rownames(fit\$scores). By default, all samples will be assigned to the same class.
sample_colors	Named character vector of colors. The names of the colors must be the classes in group. Each sample will be assigned the color corresponding to its class, taken from the group vector. By default a color will be assigned automatically to each class.
cp1	Integer, number of the component in the X-axis. Default is 1, the first component.
cp2	Integer, number of the component in the Y-axis. Default is 2, the second component.
legend	Boolean, whether to plot a legend in the plot. Default is TRUE.
legend_xy	Situation of the legend in the plot. Available options are: "bottomright", "bottom", "bottomleft", "left", "topleft", "top", "topright", "right" and "center".
cex	Graphical parameter from par() function.
pch	Graphical parameter from par() function.
mgp	Graphical parameter from par() function.
main	Title of the graphics
save_png	Path to the file where the image as PNG will be saved. By default, the image is not saved.

Value

Plots two components of a PCA

Examples

```
data(path_vals)
sample_group <- brca_design[colnames(path_vals),"group"]
pca_model <- do_pca(path_vals[seq_len(ncol(path_vals)),])
pca_plot(pca_model, sample_group)
```

quantify_terms	<i>Computes the level of activation of the functions related to the previously computed subpathways</i>
----------------	---

Description

Computes the level of activation of the functions related to the previously computed subpathways

Usage

```
quantify_terms(results, metaginfo, dbannot, out_matrix = FALSE,
  normalize = TRUE)
```

Arguments

<code>results</code>	List of results as returned by the <code>hipathia</code> function
<code>metainfo</code>	Pathways object
<code>dbannot</code>	Either a string indicating which precomputed annotation to use ("uniprot" for Uniprot Keywords or "GO" for Gene Ontology terms), or a dataframe with the annotation of the genes to the functions. First column are gene symbols, second column the functions.
<code>out_matrix</code>	Boolean, whether the output object should be a matrix object. Default is FALSE, returning a SummarizedExperiment object.
<code>normalize</code>	Boolean, whether to normalize the matrix of pathway values with <code>normalize_paths</code> before quantifying the signal. Due to the nature of the Hipathia method, in which the length of each pathway may alter its signal rank, we strongly recommend to perform this normalization. This normalization removes the bias. Default is set to TRUE.

Value

Matrix with the level of activation of the functions in `dbannot`

Examples

```
data(results)
pathways <- load_pathways(species = "hsa", pathways_list = c("hsa03320",
"hsa04012"))
go_values <- quantify_terms(results, pathways, "GO")
uniprot_values <- quantify_terms(results, pathways, "uniprot")
```

`results`

Results object

Description

Results object returned by `hipathia::hipathia` function, after calling `results <- hipathia(exp_data, pathways,`

Usage

```
data(results)
```

Format

Object of results, including pathways information.

Value

Object of results, including pathways information.

save_results	<i>Save results to folder</i>
--------------	-------------------------------

Description

Saves results to a folder. In particular, it saves the matrix of subpathway values, a table with the results of the provided comparison, the accuracy of the results and the .SIF and attributes of the pathways.

Usage

```
save_results(results, comp, metainfo, output_folder = NULL, path = NULL)
```

Arguments

results	Results object as returned by the hipathia function.
comp	Comparison as returned by the do_wilcoxon function.
metainfo	Pathways object
output_folder	Name of the folder in which the results will be stored.
path	Absolute path to the parent directory in which 'output_folder' will be saved. If it is not provided, it will be created in a temp folder.

Value

Creates a folder in disk in which all the information to browse the pathway results is stored.

Examples

```
data(results)
data(comp)
pathways <- load_pathways(species = "hsa", pathways_list = c("hsa03320",
"hsa04012"))
save_results(results, comp, pathways, "output_results")
```

top_pathways	<i>Computes pathway significance</i>
--------------	--------------------------------------

Description

Performs a test for each pathway checking if the number of significant paths is significant, compared to not having any of the paths as significant.

Usage

```
top_pathways(comp)
```

Arguments

comp	Comparison data frame as returned by the do_wilcoxon function.
------	--

Value

Table with the names of the pathways and their p-value for the Fisher test comparing the proportion of significant subpaths vs. 0.

Examples

```
data(comp)
top_pathways(comp)
```

translate_data	<i>Translation of the rownames IDs of a SummarizedExperiment to Entrez IDs.</i>
----------------	---

Description

Translates the IDs in the rownames of a SummarizedExperiment to Entrez IDs. For accepted IDs to be transformed see the DOCUMENTATION.

Usage

```
translate_data(data, species, sel_assay = 1, verbose = TRUE)
```

Arguments

data	Either a SummarizedExperiment object or a matrix of gene expression.
species	Species of the samples.
sel_assay	Character or integer, indicating the assay to be translated in the SummarizedExperiment. Default is 1.
verbose	Boolean, whether to show details about the results of the execution.

Value

Either a SummarizedExperiment or a matrix (depending on the input type) of gene expression with Entrez IDs as rownames.

Examples

```
data("brca_data")
trans_data <- translate_data(brca_data, "hsa")
```

translate_matrix	<i>Translation of the rownames IDs of a matrix to Entrez IDs.</i>
------------------	---

Description

Translates the IDs in the rownames of a matrix to Entrez IDs. For accepted IDs to be transformed see the DOCUMENTATION.

Usage

```
translate_matrix(exp, species, verbose = TRUE)
```

Arguments

exp	Matrix of gene expression.
species	Species of the samples.
verbose	Boolean, whether to show details about the results of the execution.

Value

Matrix of gene expression with Entrez IDs as rownames.

visualize_report	<i>Visualize a HiPathia report</i>
------------------	------------------------------------

Description

Visualize a HiPathia report

Usage

```
visualize_report(output_folder, port = 4000)
```

Arguments

output_folder	Folder in which results to visualize are stored
port	Port to use

Value

The instructions to visualize a HiPathia report in a web browser

Examples

```
data(comp)
pathways <- load_pathways(species = "hsa", pathways_list = c("hsa03320",
"hsa04012"))
report <- create_report(comp, pathways, "save_results")
visualize_report(report)

## Not run:
data(results)
data(brca)
sample_group <- colData(brca)[,1]
colors_de <- node_color_per_de(results, pathways,
sample_group, "Tumor", "Normal")
report <- create_report(comp, pathways, "save_results",
node_colors = colors_de)
visualize_report(report)
visualize_report(report, port = 5000)

## End(Not run)
```

Index

*Topic **datasets**

- brca, [3](#)
 - brca_data, [4](#)
 - brca_design, [5](#)
 - comp, [5](#)
 - exp_data, [8](#)
 - go_vals, [13](#)
 - path_vals, [28](#)
 - results, [30](#)
- annotate_paths, [3](#)
- brca, [3](#)
- brca_data, [4](#)
- brca_design, [5](#)
- comp, [5](#)
- create_report, [6](#)
- do_pca, [7](#)
- do_wilcoxon, [7](#)
- exp_data, [8](#)
- get_highest_sig_ancestor, [9](#)
- get_path_names, [13](#)
- get_paths_data, [9](#)
- get_pathway_functions, [12](#)
- get_pathways_annotations, [10](#)
- get_pathways_list, [11](#)
- get_pathways_summary, [11](#)
- go_vals, [13](#)
- heatmap_plot, [14](#)
- hhead, [15](#)
- hipathia, [16](#)
- igraphs_upgrade, [17](#)
- is_accepted_species, [17](#)
- load_annotfuns, [18](#)
- load_annots, [18](#)
- load_entrez_hgnc, [19](#)
- load_gobp_frame, [19](#)
- load_gobp_net, [19](#)
- load_mgi, [20](#)
- load_pathways, [20](#)
- load_pseudo_mgi, [21](#)
- load_xref, [21](#)
- multiple_pca_plot, [22](#)
- node_color_per_de, [23](#)
- normalize_data, [24](#)
- normalize_paths, [25](#)
- path_vals, [28](#)
- paths_to_go_ancestor, [26](#)
- pathway_comparison_plot, [27](#)
- pca_plot, [28](#)
- quantify_terms, [29](#)
- results, [30](#)
- save_results, [31](#)
- top_pathways, [31](#)
- translate_data, [32](#)
- translate_matrix, [33](#)
- visualize_report, [33](#)