

Package ‘interactiveDisplayBase’

October 16, 2019

Type Package

Title Base package for enabling powerful shiny web displays of
Bioconductor objects

Version 1.22.0

Date 2014-09-09

Author Shawn Balcome, Marc Carlson

Maintainer Shawn Balcome <balc0022@umn.edu>

Imports shiny

Depends R (>= 2.10), methods, BiocGenerics

Suggests knitr

Enhances rstudioapi

Description The interactiveDisplayBase package contains the the basic
methods needed to generate interactive Shiny based display
methods for Bioconductor objects.

License Artistic-2.0

Collate interactiveDisplayBase.R dataframe.R dot_runApp.R zzz.R

VignetteBuilder knitr

biocViews GO, GeneExpression, Microarray, Sequencing, Classification,
Network, QualityControl, Visualization, Visualization,
Genetics, DataRepresentation, GUI, AnnotationData

git_url <https://git.bioconductor.org/packages/interactiveDisplayBase>

git_branch RELEASE_3_9

git_last_commit 4ce3cde

git_last_commit_date 2019-05-02

Date/Publication 2019-10-15

R topics documented:

.runApp	2
display	3
Index	4

`.runApp`*Run a shiny app, capturing results to the R session*

Description

This utility function launches a shiny visualization application, either in the RStudio viewer pane (if run under RStudio) or in the browser.

Usage

```
.runApp(app, ...)
```

Arguments

<code>app</code>	The shiny application definition, see <code>?shiny::runApp</code> .
<code>...</code>	additional arguments passed to <code>shiny::runApp()</code> .

Value

The return value of `shiny::runApp`.

Author(s)

Martin Morgan

Examples

```
if (interactive()) {
  require(shiny)

  app <- list(
    ui = fluidPage(
      title="Who Am I?",
      sidebarLayout(
        position="left",
        sidebarPanel(
          h1("Your name"),
          textInput("your_name", "Your name?", "Anonymous"),
          actionButton("done", "Done")),
        mainPanel(
          "Hi", textOutput("your_name", inline=TRUE))
      )),
    server = function(input, output) {
      output$your_name <- renderText(input$your_name)
      observe({
        if (input$done > 0)
          isolate(stopApp(returnValue = input$your_name))
      })
    })
}
```

```
    .runApp(app)
  }
```

display*display: Open a Shiny application for a Bioconductor object*

Description

This opens a shiny visualization application in the browser based on the submitted object.

Usage

```
display(object, ...)
```

Arguments

<code>object</code>	data object to display
<code>...</code>	additional arguments passed to methods; currently unused.

Value

Usually some variation of the initial input object, but it may be altered by the display widget (subset for example).

Author(s)

Shawn Balcome and Marc Carlson

See Also

<http://bioconductor.org/packages/2.13/bioc/html/interactiveDisplayBase.html>

Examples

```
if(interactive()) {

  ## draw a data.frame
  display(mtcars)

  ## subset a data.frame:
  mtcars2 <- display(mtcars)

}
```

Index

*Topic **manip**

.runApp, [2](#)

*Topic **methods**

display, [3](#)

.runApp, [2](#)

display, [3](#)

display,ANY-method (display), [3](#)

display,data.frame-method (display), [3](#)

display,missing-method (display), [3](#)