

# The sceUpstr support in package harbChIP

HJB/VJC

May 20, 2021

## Contents

<b>1</b>	<b>Introduction</b>	<b>1</b>
<b>2</b>	<b>Building the sceUpstr object</b>	<b>1</b>
<b>3</b>	<b>Checking a finding of Harbison et al.</b>	<b>2</b>

## 1 Introduction

The intent of this package is to allow code like the following:

```
> library(harbChIP)
> data(sceUpstr)
> sceUpstr

upstreamSeqs instance, organism sce
There are 6674 entries
first keys:
[1] "YAL001C" "YAL002W" "YAL003W" "YAL004W" "YAL005C"

> getUpstream("YAL001C", sceUpstr)

$YAL001C
500-letter DNASTring object
seq: CTGTACCACTATAATAATTTATCTTGATCGTATTAT...AGGACGTTTGGTTGAAGCCAAGCCACAAGAAAA
```

## 2 Building the sceUpstr object

Upstream sequences of length 500bp were obtained from the SGD website:  
[www.yeastgenome.org](http://www.yeastgenome.org) -> Download Data -> FTP  
[sequence/genomic\\_sequence/orf\\_dna/archive/utr5\\_sc\\_500.20040206.fasta.gz](http://www.yeastgenome.org/sequence/genomic_sequence/orf_dna/archive/utr5_sc_500.20040206.fasta.gz)

```
> fname = system.file("extdata/utr5_sc_500_20040206.fasta", package="sceUpstr")
> utr5 = readFASTA(fname)
> sceUpstr = buildUpstreamSeqs2(utr5)
> save(sceUpstr, file="sceUpstr.rda")
```

### **3 Checking a finding of Harbison et al.**

It is asserted in Fig 1 B of the paper that GGCGCTA is specifically bound by Snt2. We will examine the frequency of this heptamer in upstream regions and relate to the binding ratio distribution.