

# Package ‘Prize’

April 16, 2019

**Type** Package

**Title** Prize: an R package for prioritization estimation based on analytic hierarchy process

**Version** 1.12.1

**Date** 2016-12-13

**Author** Daryanaz Dargahi <daryanazdargahi@gmail.com>

**Maintainer** Daryanaz Dargahi <daryanazdargahi@gmail.com>

**Description** The high throughput studies often produce large amounts of numerous genes and proteins of interest. While it is difficult to study and validate all of them. Analytic Hierarchy Process (AHP) offers a novel approach to narrowing down long lists of candidates by prioritizing them based on how well they meet the research goal. AHP is a mathematical technique for organizing and analyzing complex decisions where multiple criteria are involved. The technique structures problems into a hierarchy of elements, and helps to specify numerical weights representing the relative importance of each element. Numerical weight or priority derived from each element allows users to find alternatives that best suit their goal and their understanding of the problem.

**License** Artistic-2.0

**Imports** diagram, stringr, ggplot2, reshape2, grDevices, matrixcalc, stats, gplots, methods, utils, graphics

**Suggests** RUnit, BiocGenerics

**biocViews** ImmunoOncology, Software, MultipleComparison, GeneExpression, CellBiology, RNASeq

**git\_url** <https://git.bioconductor.org/packages/Prize>

**git\_branch** RELEASE\_3\_8

**git\_last\_commit** 489f702

**git\_last\_commit\_date** 2019-01-04

**Date/Publication** 2019-04-15

## R topics documented:

Prize-package . . . . . 3

aggreg.judgement-data	4
ahmatrix	5
ahmatrixObj-class	6
ahp	6
ahplot	7
ahpObj-class	8
ahp_matrix	8
ahp_plot	9
ahp_weights	9
AIJ	10
AIP	10
ariAggreg-class	11
CI	11
crplot	12
dplot	13
epitope.PCM-data	14
epitopeLength.PCM-data	14
epitopeNum.PCM-data	14
epitope_num_rating-data	15
epitope_size_rating-data	15
freq.PCM-data	15
freq_exp_rating-data	16
gaggregate	16
GCR	17
genes.list-data	18
geoAggreg-class	18
ICR	19
ind1-data	19
ind2-data	20
ind3-data	20
ind4-data	20
IP	21
normal.PCM-data	21
normal_exp_rating-data	22
number-data	22
numEpitope_alternative_category-data	22
pipeline	23
pipelineObj-class	24
rainbowplot	24
rainbow_plot	25
rating	26
ratingObj-class	27
RM	27
saaty_inconsistency	28
simulation	29
tumor.PCM-data	30
tumor_exp_rating-data	30
weight	30
weight_plot	31
wplot	32

Prize-package

*Prize: an R package for prioritization estimation based on analytic hierarchy process*

## Description

The Prize package is a decision analysis tool based on Analytic Hierarchy Process (AHP), which provides a logical framework to rank and prioritize a group of alternatives. Once the decision makers have their list of available options (alternatives) and defined their criteria for prioritization, the Prize package allows aggregation of individual judgements against each criterion into a group judgement, then use these judgements to calculate final ahp weight for ranking. The Prize package also provides visualizarion tools to illustrate the problem hierarchy, the criteria weights and final ranking.

## Author(s)

Daryanaz Dargahi <daryanazdargahi@gmail.com>

## References

Saaty, T. L. (1977) A scaling methods for priorities in hierarchical structure. Journal of Mathematical Psychology, 15, 234-281.

T.L. Saaty. The Analytic Hierarchy Process, Planning, Piority Setting, Re- source Allocation. McGraw-Hill, New york, 1980.

E. Forman and K. Peniwati. Aggregating individual judgments and priorities with the analytic hierarchy process. European Journal of Operational Research, 108(1):165-169, 1998.

J.C. Gower. Some distance properties of latent root and vector methods used in multivariate analysis. Biometrika, 53(3/4):pp. 325-338, 1966.

## Examples

```
#####
## aggregation of individual opinions
#####
mat = matrix(nrow = 4, ncol = 1, data = NA)
mat[,1] = c(system.file('extdata','ind1.tsv',package = 'Prize'),
            system.file('extdata','ind2.tsv',package = 'Prize'),
            system.file('extdata','ind3.tsv',package = 'Prize'),
            system.file('extdata','ind4.tsv',package = 'Prize'))
rownames(mat) = c('ind1','ind2','ind3', 'ind4')
colnames(mat) = c('individual_judgement')

# non-weighted AIJ
res = gaggregate(srcfile = mat, method = 'geometric', simulation = 500)

#####
## Estimating idealised prioritise
## Rating AHP
#####
category_pcm = read.delim(system.file('extdata','number.tsv', package = 'Prize')
                          , sep = '\t', header = TRUE, row.names = 1)
alt_mat = read.delim(system.file('extdata','numEpitope_alternative_category.tsv',
```

```

        package = 'Prize'), sep = '\t', header = FALSE)
rate = rating(category_pcm, alt_mat, simulation = 500)

#####
## Prioritization estimation using AHP
#####
mat <- matrix(nrow = 7, ncol = 3, data = NA)
mat[,1] <- c('0', '1', '2', '3', '4', '4.1', '4.2')
mat[,2] <- c('Prioritization_of_DE_genes', 'Tumor_expression', 'Normal_expression',
             'Frequency', 'Epitopes', 'Number_of_epitopes', 'Size_of_epitopes')
mat[,3] <- c(system.file('extdata', 'aggreg.judgement.tsv', package = 'Prize'),
             system.file('extdata', 'tumor.PCM.tsv', package = 'Prize'),
             system.file('extdata', 'normal.PCM.tsv', package = 'Prize'),
             system.file('extdata', 'freq.PCM.tsv', package = 'Prize'),
             system.file('extdata', 'epitope.PCM.tsv', package = 'Prize'),
             system.file('extdata', 'epitopeNum.PCM.tsv', package = 'Prize'),
             system.file('extdata', 'epitopeLength.PCM.tsv', package = 'Prize'))

# prioritization pipeline
prioritization <- pipeline(mat, model = 'relative', simulation = 500)

#####
## visualizaion
#####
# visualizing individual opinion consistency ratio
crplot(ICR(res), angle = 45)

# visualizing the distance among individual opinion and aggregated group judgment
dplot(IP(res))

# visualizing problem hierarchy
ahplot(ahp_plot(prioritization), fontsize = 0.7, cradx = 0.11 ,sradx = 0.12,
       cirx= 0.18, ciry = 0.07, dist = 0.06)

# visualizing prioritized alternatives
rainbowplot(rainbow_plot(prioritization)$criteria_rainbowplot, xcex = 3)
rainbowplot(rainbow_plot(prioritization)$subcriteria_rainbowplot, xcex = 3)

# visualizing criteria/subcriteria score
wplot(weight_plot(prioritization)$criteria_wplot, type = 'pie',
       fontsize = 7, pcex = 3)
wplot(weight_plot(prioritization)$criteria_wplot, type = 'bar',
       fontsize = 7, pcex = 3, xlab = 'Weight', ylab = 'Criteria')

```

---

aggreg.judgement-data *A pairwise comparison matrix (PCM)*

---

## Description

Aggreg.judgement includes a PCM computed from aggregation of decision makers opinions. The PCM includes 4 criteria to prioritize a set of genes of interest according to their potential to serve as a tumor marker/therapeutic target. The criteria include: Tumor\_expression, Normal\_expression, Frequency, and Epitopes.

**Author(s)**

Daryanaz Dargahi

**References**

T.L. Saaty. The Analytic Hierarchy Process, Planning, Priority Setting, Resource Allocation. McGraw-Hill, New York, 1980. E. Forman and K. Peniwati. Aggregating individual judgments and priorities with the analytic hierarchy process. European Journal of Operational Research, 1998.

---

ahmatrix

*ahmatrix*

---

**Description**

Converting a triangular matrix into a square pairwise comparison matrix (PCM) where the diagonal values are equal to 1 and  $a[i,j] = 1/a[j,i]$ .

**Usage**

```
ahmatrix(x)
```

**Arguments**

`x` a numeric triangular matrix, where empty elements are specified with NA.

**Value**

An S4 object including a PCM.

**Author(s)**

Daryanaz Dargahi

**Examples**

```
mat <- matrix(nrow = 3, ncol = 3, data = NA)
mat[1,2] <- 5
mat[1,3] <- 2
mat[2,3] <- 7

res <- ahmatrix(mat)
```

---

ahmatrixObj-class	<i>Class</i> ahmatrixObj
-------------------	--------------------------

---

**Description**

An object that stores a pairwise comparison matrix.

**Objects from the Class**

Objects can be created by calls of the form `new("ahmatrixObj", ...)`.

**Slots**

`ahp_matrix`: A pairwise comparison matrix.

**Author(s)**

Daryanaz Dargahi <daryanazdargahi@gmail.com>

---

ahp

*ahp***Description**

Computing AHP weights as well as Satty's inconsistency.

**Usage**

```
ahp(x, simulation = 500)
```

**Arguments**

<code>x</code>	a pairwise comparison matrix (PCM) with diagonal values equal 1 and $a[i,j] = 1/a[j,i]$ .
<code>simulation</code>	the simulation size in order to compute Satty's inconsistency. The default value is 500.

**Value**

An S4 object including a numeric vector of AHP weights and Satty's inconsistency.

**Author(s)**

Daryanaz Dargahi

**References**

T.L. Saaty. A scaling method for priorities in hierarchical structures. *Journal of Mathematical Psychology*, 15(3):234-281, 1977.

T.L. Saaty. *The Analytic Hierarchy Process, Planning, Priority Setting, Resource Allocation*. McGraw-Hill, New York, 1980.

**Examples**

```
mat <- matrix(c(1,2,5, 1/2,1,3, 1/5,1/3,1), nrow = 3, ncol = 3, byrow = TRUE)
res <- ahp(mat, simulation = 500)
```

---

ahplot

*ahplot*


---

**Description**

Plotting the problem hierarchy, showing the relationships between goal, criteria, and subcriteria.

**Usage**

```
ahplot(srcfile, fontsize = 0.5, cradx = 0.07, crady = 0.05,
       sradx = 0.05, srady = 0.05, cirx = 0.1, ciry = 0.05, gcol = "green",
       ccol = "yellow", scol = "orange", lcol = "black", dist = 0.05,
       digit = 3, main = NULL)
```

**Arguments**

srcfile	a character matrix, where the first column specifies the hierarchy order. The second and third columns include the ID of decision elements and ahp weights (optional), respectively (See the example below).
fontsize	the font size of characters.
cradx, crady	the horizontal and vertical radius of the criteria box, respectively.
sradx, srady	the horizontal and vertical radius of the subcriteria box, respectively.
cirx, ciry	the horizontal and vertical radius of the goal
gcol, ccol, scol	the filling color of the goal, criteria, and subcriteria boxes, respectively.
lcol	the line color surrounding the goal, criteria, and subcriteria boxes.
dist	the distance between the weights and the tree edges.
digit	the number of digits after decimal point to be shown on the arrows.
main	a character string as the plot title

**Value**

An object created by 'diagram'.

**Author(s)**

Daryanaz Dargahi

**Examples**

```
mat <- matrix(nrow = 7, ncol = 2, data = NA)
mat[,1] <- c('0', '1', '2', '3', '4', '4.1', '4.2')
mat[,2] <- c('Prioritization_of_DE_genes', 'Tumor_expression', 'Normal_expression',
'Frequency', 'Epitopes', 'Number_of_epitopes', 'Size_of_epitopes')

# plotting a problem hierarchy
ahplot(mat, fontsize = 0.7, cradx = 0.11 ,sradx = 0.12, cirx= 0.18, ciry = 0.07)

# plotting a problem hierarchy with AHP weights shown on the edges of the graph
mat <- cbind(mat, c(1, 0.470, 0.341, 0.117, 0.073, 0.009, 0.064))
ahplot(mat, fontsize = 0.7, cradx = 0.11 ,sradx = 0.12, cirx= 0.18, ciry = 0.07)
```

---

ahpObj-class	<i>Class ahpObj</i>
--------------	---------------------

---

**Description**

An object that stores AHP priorities and consistency ratio.

**Objects from the Class**

Objects can be created by calls of the form `new("ahpObj", ...)`.

**Slots**

**weight:** A vector of AHP priorities.  
**saaty\_inconsistency:** The consistency ratio.

**Author(s)**

Daryanaz Dargahi <daryanazdargahi@gmail.com>

---

ahp_matrix	<i>AHP matrix slot</i>
------------	------------------------

---

**Description**

ahp\_matrix is a slot of ahmatrixObj class. It consists of a square pairwise comparison matrix.

**Author(s)**

Daryanaz Dargahi <daryanazdargahi@gmail.com>

**Examples**

```
mat <- matrix(nrow = 3, ncol = 3, data = NA)
mat[1,2] <- 5
mat[1,3] <- 2
mat[2,3] <- 7
res <- ahmatrix(mat)
ahp_matrix(res)
```



ahp\_plot

*AHP plot slot***Description**

ahp\_plot is a slot of pipelineObj class. It consists of a matrix of problem hierarchy.

**Author(s)**

Daryanaz Dargahi <daryanazdargahi@gmail.com>

**Examples**

```
mat <- matrix(nrow = 7, ncol = 3, data = NA)
mat[,1] <- c('0', '1', '2', '3', '4', '4.1', '4.2')
mat[,2] <- c('Prioritization_of_DE_genes', 'Tumor_expression', 'Normal_expression',
            'Frequency', 'Epitopes', 'Number_of_epitopes', 'Size_of_epitopes')
mat[,3] <- c(system.file('extdata', 'aggreg.judgement.tsv', package = 'Prize'),
            system.file('extdata', 'tumor.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'normal.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'freq.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'epitope.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'epitopeNum.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'epitopeLength.PCM.tsv', package = 'Prize'))

result <- pipeline(mat, model = 'relative', simulation = 500)
ahp_plot(result)
```

ahp\_weights

*AHP weights slot***Description**

ahp\_weights is a slot of pipelineObj class. It consists of a list of matrices representing AHP priorities for all decision elements

**Author(s)**

Daryanaz Dargahi <daryanazdargahi@gmail.com>

**Examples**

```
mat <- matrix(nrow = 7, ncol = 3, data = NA)
mat[,1] <- c('0', '1', '2', '3', '4', '4.1', '4.2')
mat[,2] <- c('Prioritization_of_DE_genes', 'Tumor_expression', 'Normal_expression',
            'Frequency', 'Epitopes', 'Number_of_epitopes', 'Size_of_epitopes')
mat[,3] <- c(system.file('extdata', 'aggreg.judgement.tsv', package = 'Prize'),
            system.file('extdata', 'tumor.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'normal.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'freq.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'epitope.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'epitopeNum.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'epitopeLength.PCM.tsv', package = 'Prize'))
```

```

system.file('extdata','epitopeLength.PCM.tsv',package = 'Prize'))

result <- pipeline(mat, model = 'relative', simulation = 500)
ahp_weights(result)

```

---

AII

*Aggregated individual judgements (AIJ) slot*


---

### Description

AIJ (Aggregated individual judgements) is a slot of `geoAggreg` class. It consists of a matrix of aggregated group judgements (a pairwise comparison matrix).

### Author(s)

Daryanaz Dargahi <daryanazdargahi@gmail.com>

### Examples

```

mat <- matrix(nrow = 4, ncol = 1, data = NA)
mat[,1] <- c(system.file('extdata','ind1.tsv',package = 'Prize'),
            system.file('extdata','ind2.tsv',package = 'Prize'),
            system.file('extdata','ind3.tsv',package = 'Prize'),
            system.file('extdata','ind4.tsv',package = 'Prize'))
rownames(mat) <- c('ind1','ind2','ind3', 'ind4')
colnames(mat) <- c('individual_judgement')

# non-weighted aggregation
res <- gaggregate(srcfile = mat, method = 'geometric', simulation = 500)
AIJ(res)

```

---

AIP

*Aggregated individual priorities (AIP) slot*


---

### Description

AIP (Aggregated individual priorities) is a slot of `ariAggreg` class. It consists of a vector of aggregated group priorities.

### Author(s)

Daryanaz Dargahi <daryanazdargahi@gmail.com>

**Examples**

```

mat <- matrix(nrow = 4, ncol = 1, data = NA)
mat[,1] <- c(system.file('extdata','ind1.tsv',package = 'Prize'),
            system.file('extdata','ind2.tsv',package = 'Prize'),
            system.file('extdata','ind3.tsv',package = 'Prize'),
            system.file('extdata','ind4.tsv',package = 'Prize'))
rownames(mat) <- c('ind1','ind2','ind3', 'ind4')
colnames(mat) <- c('individual_judgement')

# non-weighted aggregation
res <- gaggregate(srcfile = mat, method = 'arithmetic', simulation = 500)
AIP(res)

```

---

ariAggreg-class	<i>Class</i> ariAggreg
-----------------	------------------------

---

**Description**

An object that stores the aggregated group priorities as well as consistency ratio of the individual judgements.

**Objects from the Class**

Objects can be created by calls of the form `new("ariAggreg", ...)`.

**Slots**

**AIP:** A vector of aggregated group priorities.

**ICR:** A vector of individuals judgements consistency ratio.

**IP:** A matrix of individual and aggregated group AHP priorities.

**Author(s)**

Daryanaz Dargahi <daryanazdargahi@gmail.com>

---

CI	<i>Consistency index (CI) slot</i>
----	------------------------------------

---

**Description**

CI (Consistency index) is a slot of geoAggreg class. It consists of a vector of the individuals consistency index.

**Author(s)**

Daryanaz Dargahi <daryanazdargahi@gmail.com>

**Examples**

```

mat <- matrix(nrow = 4, ncol = 1, data = NA)
mat[,1] <- c(system.file('extdata','ind1.tsv',package = 'Prize'),
             system.file('extdata','ind2.tsv',package = 'Prize'),
             system.file('extdata','ind3.tsv',package = 'Prize'),
             system.file('extdata','ind4.tsv',package = 'Prize'))
rownames(mat) <- c('ind1','ind2','ind3', 'ind4')
colnames(mat) <- c('individual_judgement')

# non-weighted aggregation
res <- gaggregate(srcfile = mat, method = 'geometric', simulation = 500)
CI(res)

```

---

crplot

*crplot*


---

**Description**

Plotting the consistency ratio (CR) of individual judgements. According to Satty, a pairwise comparison matrix is considered to be consistent if CR is equal or less than 0.1. Therefore, CRs equal to or less than 0.1 are colored in green (Pass) and CRs greater than 0.1 are colored in red (Failed).

**Usage**

```

crplot(srcfile, fontsize = 15, xcex = 10, ycex = 10, angle = 90,
       xlab = "ID", ylab = "ICR", main = NULL)

```

**Arguments**

srcfile	a numeric vector of individual CR
fontsize	the font size of plot title, x and y axis labels. The default value is 15.
xcex,ycex	the font size of x and y axis, respectively. The default values is 10.
angle	the angle of the labels on x axis
xlab,ylab	the label to be shown on the x and y axis, respectively.
main	the plot title

**Value**

An object created by 'ggplot'.

**Author(s)**

Daryanaz Dargahi

**Examples**

```

data <- c(0.1132, 0.0142, 0.0324, 0.10075, 0.0883)
names(data) <- c('individual_1','individual_2','individual_3','individual_4','individual_5')
crplot(data, fontsize = 15, xcex = 10, ycex = 10, xlab = 'ID', ylab = 'ICR', main = 'Individuals consistency ratio')

```

---

dplot	<i>dplot</i>
-------	--------------

---

### Description

Computing and plotting the distance between individuals and group judgement. Distances are computed using classical multidimensional scaling (MDS) approach.

### Usage

```
dplot(srcfile, fontsize = 15, xcex = 10, ycex = 10, lcex = 5,
      hjust = 0.5, vjust = 1, xlab = "Coordinate 1", ylab = "Coordinate 2",
      main = NULL)
```

### Arguments

srcfile	a numeric matrix of individual and group priorities.
fontsize	the font size of the plot title, and x and y axis labels. The default value is 15.
xcex,ycex	the font size of the x and y axis, respectively. The default values is 10.
lcex	the font size of point labels in dplot
hjust,vjust	the horizontal and vertical justification of point labels, respectively.
xlab,ylab	the label of the x and y axis, respectively.
main	the plot title

### Value

An object created by 'ggplot'.

### Author(s)

Daryanaz Dargahi

### References

J.C. Gower. Some distance properties of latent root and vector methods used in multivariate analysis. *Biometrika*, 53(3/4):pp. 325-338, 1966.

### Examples

```
mat <- matrix(nrow = 5, ncol = 4, data = NA)
rownames(mat) <- c('Ind1','Ind2','Ind3', 'Ind4' , 'Group judgement')
colnames(mat) <- c('Tumor_expression', 'Normal_expression', 'Frequency', 'Epitopes')
mat[1,] <- c(0.4915181, 0.3058879, 0.12487821, 0.07771583)
mat[2,] <- c(0.3060687, 0.4949012, 0.12868606, 0.07034399)
mat[3,] <- c(0.4627138, 0.3271881, 0.13574662, 0.07435149)
mat[4,] <- c(0.6208484, 0.2414021, 0.07368481, 0.06406465)
mat[5,] <- c(0.4697298, 0.3406738, 0.11600194, 0.07359445)

dplot(mat, xlab = 'Coordinate 1', ylab = 'Coordinate 2', main = 'Distance plot')
```

---

epitope.PCM-data      *A pairwise comparison matrix (PCM)*

---

**Description**

epitope.PCM is a criteria with two subcriteria in the prioritization of a set of genes of interest. This file includes a PCM of the two subcriteria including number of epitopes and size of epitopes. The pairwise comparisons are performed according to the Saaty's fundamental scale.

**Author(s)**

Daryanaz Dargahi

---

epitopeLength.PCM-data      *A pairwise comparison matrix (PCM)*

---

**Description**

EpitopeLength.PCM is a subcriteria (of the Epitope criterion) in the prioritization of a set of genes of interest. This file includes a PCM of the genes with respect to size (length) of epitopes according to the UniProt annotation (uniprot.org). The pairwise comparisons are performed according to the Saaty's fundamental scale.

**Author(s)**

Daryanaz Dargahi

**References**

T.L. Saaty. The Analytic Hierarchy Process, Planning, Priority Setting, Resource Allocation. McGraw-Hill, New York, 1980.

---

epitopeNum.PCM-data      *A pairwise comparison matrix (PCM)*

---

**Description**

EpitopeNum.PCM is a subcriteria (of the Epitope criterion) in the prioritization of a set of genes of interest. This file includes a PCM of the genes with respect to the number of epitopes according to the UniProt annotation (uniprot.org). The pairwise comparisons are performed according to the Saaty's fundamental scale.

**Author(s)**

Daryanaz Dargahi

**References**

T.L. Saaty. The Analytic Hierarchy Process, Planning, Priority Setting, Resource Allocation. McGraw-Hill, New York, 1980.

---

epitope\_num\_rating-data

*Rating categories and idealised priorities*

---

**Description**

The rating categories and computed idealised priorities of alternatives (genes) with respect to their number of epitopes. This matrix is computed by the rating() function.

**Author(s)**

Daryanaz Dargahi

---

epitope\_size\_rating-data

*Rating categories and idealised priorities*

---

**Description**

The rating categories and computed idealised priorities of alternatives (genes) with respect to their epitope size. This matrix is computed by the rating() function.

**Author(s)**

Daryanaz Dargahi

---

freq.PCM-data

*A pairwise comparison matrix (PCM)*

---

**Description**

Freq.PCM is a criteria (with no subcriteria) in the prioritization of a set of genes of interest. This file includes a PCM of the genes with respect to their expression frequency in tumor tissue. The pairwise comparisons are performed according to the Saaty's fundamental scale.

**Author(s)**

Daryanaz Dargahi

**References**

T.L. Saaty. The Analytic Hierarchy Process, Planning, Priority Setting, Resource Allocation. McGraw-Hill, New York, 1980.

---

freq\_exp\_rating-data    *Rating categories and idealised priorities*

---

### Description

The rating categories and computed idealised priorities of alternatives (genes) with respect to their expression frequency in tumor tissue. This matrix is computed by the `rating()` function.

### Author(s)

Daryanaz Dargahi

---

gaggregate                      *gaggregate*

---

### Description

Aggregating individual judgments (pairwise comparison matrices - PCMs) into a group judgement or group priority.

### Usage

```
gaggregate(srcfile, method = "geometric", simulation = 500)
```

### Arguments

<code>srcfile</code>	a matrix with one or two columns. Column one (required) includes the path (location) to each individual pairwise comparison matrix and column two (optional) includes the individual weights. The matrix rowname is individuals identifier.
<code>method</code>	two methods are available for aggregation of individual opinions, (1) arithmetic, which compute the arithmetic mean of individual priorities, (2) geometric, which computes the geometric mean of individual PCMs. If individuals are assigned with a weight, the weighted arithmetic/geometric mean will be computed. The default method is 'geometric'.
<code>simulation</code>	simulation size for computation of Satty's inconsistency. The default value is 500.

### Value

An S4 object including group PCM/prioritise;

If geometric mean is used, the returning object includes: aggregated group PCM (AIJ), group consistency ratio (GCR), individual consistency ratios (ICR), consensus index (CI), and priority matrix (IP).

If arithmetic mean is used, the returning object includes: aggregated group priority (AIP), individual consistency ratios (ICR), and priority matrix (IP).



**Author(s)**

Daryanaz Dargahi

**References**

E. Forman and K. Peniwati. Aggregating individual judgments and priorities with the analytic hierarchy process. *European Journal of Operational Research*, 108(1):165-169, 1998.

**Examples**

```
mat <- matrix(nrow = 4, ncol = 1, data = NA)
mat[,1] <- c(system.file('extdata', 'ind1.tsv', package = 'Prize'),
            system.file('extdata', 'ind2.tsv', package = 'Prize'),
            system.file('extdata', 'ind3.tsv', package = 'Prize'),
            system.file('extdata', 'ind4.tsv', package = 'Prize'))
rownames(mat) <- c('ind1', 'ind2', 'ind3', 'ind4')
colnames(mat) <- c('individual_judgement')

# non-weighted aggregation
res <- gaggregate(srcfile = mat, method = 'geometric', simulation = 500)

# weighted aggregation
# Decision makers are assigned with a priority value based on their specialization and perspectives.
mat <- cbind(mat, c(0.35, 0.25, 0.15, 0.25))
colnames(mat)[2] <- 'individual_weight'

res <- gaggregate(srcfile = mat, method = 'geometric', simulation = 500)
```

---

GCR

*Group consistency ratio (GCR) slot*

---

**Description**

GCR (Group consistency ratio) is a slot of geoAggreg class. It consists of the consistency ratio of the aggregated group judgement.

**Author(s)**

Daryanaz Dargahi <daryanazdargahi@gmail.com>

**Examples**

```
mat <- matrix(nrow = 4, ncol = 1, data = NA)
mat[,1] <- c(system.file('extdata', 'ind1.tsv', package = 'Prize'),
            system.file('extdata', 'ind2.tsv', package = 'Prize'),
            system.file('extdata', 'ind3.tsv', package = 'Prize'),
            system.file('extdata', 'ind4.tsv', package = 'Prize'))
rownames(mat) <- c('ind1', 'ind2', 'ind3', 'ind4')
colnames(mat) <- c('individual_judgement')

# non-weighted aggregation
res <- gaggregate(srcfile = mat, method = 'geometric', simulation = 500)
GCR(res)
```

genes.list-data      *A pairwise comparison matrix (PCM)*

---

**Description**

A matrix of genes to prioritize based on their tumor and normal expression, frequency of expression in tumor tissue, and number and size of epitopes.

**Author(s)**

Daryanaz Dargahi

---

geoAggreg-class      *Class geoAggreg*

---

**Description**

An object that stores the aggregated group judgements as well as consistency ratio of the individuals and group judgements.

**Objects from the Class**

Objects can be created by calls of the form `new("geoAggreg", ...)`.

**Slots**

**AIJ:** A matrix of aggregated group judgements (a pairwise comparison matrix).

**GCR:** The consistency ratio of the aggregated group judgement.

**CI:** A vector of the individuals consistency index.

**ICR:** A vector of individuals judgements consistency ratio.

**IP:** A matrix of individual and aggregated group AHP priorities.

**Author(s)**

Daryanaz Dargahi <daryanazdargahi@gmail.com>

ICR

*Individual consistency ratio (ICR) slot***Description**

Individual consistency ratio (ICR) is a slot of `geoAggreg` and `ariAggreg` classes. It consists of a vector of individuals judgements consistency ratio.

**Author(s)**

Daryanaz Dargahi <daryanazdargahi@gmail.com>

**Examples**

```
mat <- matrix(nrow = 4, ncol = 1, data = NA)
mat[,1] <- c(system.file('extdata','ind1.tsv',package = 'Prize'),
            system.file('extdata','ind2.tsv',package = 'Prize'),
            system.file('extdata','ind3.tsv',package = 'Prize'),
            system.file('extdata','ind4.tsv',package = 'Prize'))
rownames(mat) <- c('ind1','ind2','ind3', 'ind4')
colnames(mat) <- c('individual_judgement')

# Aggregation of individual judgements
res <- gaggregate(srcfile = mat, method = 'geometric', simulation = 500)
ICR(res)

# Aggregation of individual priorities
res <- gaggregate(srcfile = mat, method = 'arithmetic', simulation = 500)
ICR(res)
```

ind1-data

*An individual judgement matrix***Description**

A numeric square matrix generated based on Saaty's fundamental scale. This matrix includes judgements of a decision maker.

**Author(s)**

Daryanaz Dargahi

**References**

T.L. Saaty. The Analytic Hierarchy Process, Planning, Priority Setting, Resource Allocation. McGraw-Hill, New York, 1980.

---

ind2-data                      *An individual judgement matrix*

---

**Description**

A numeric square matrix generated based on Saaty's fundamental scale. This matrix includes judgements of a decision maker.

**Author(s)**

Daryanaz Dargahi

**References**

T.L. Saaty. The Analytic Hierarchy Process, Planning, Priority Setting, Resource Allocation. McGraw-Hill, New York, 1980.

---

ind3-data                      *An individual judgement matrix*

---

**Description**

A numeric square matrix generated based on Saaty's fundamental scale. This matrix includes judgements of a decision maker.

**Author(s)**

Daryanaz Dargahi

**References**

T.L. Saaty. The Analytic Hierarchy Process, Planning, Priority Setting, Resource Allocation. McGraw-Hill, New York, 1980.

---

ind4-data                      *An individual judgement matrix*

---

**Description**

A numeric square matrix generated based on Saaty's fundamental scale. This matrix includes judgements of a decision maker.

**Author(s)**

Daryanaz Dargahi

**References**

T.L. Saaty. The Analytic Hierarchy Process, Planning, Priority Setting, Resource Allocation. McGraw-Hill, New York, 1980.

**Description**

IP (Individual priority) is a slot of `geoAggreg` and `ariAggreg` classes. It consists of a matrix of individual and aggregated group AHP priorities.

**Author(s)**

Daryanaz Dargahi <daryanazdargahi@gmail.com>

**Examples**

```
mat <- matrix(nrow = 4, ncol = 1, data = NA)
mat[,1] <- c(system.file('extdata', 'ind1.tsv', package = 'Prize'),
            system.file('extdata', 'ind2.tsv', package = 'Prize'),
            system.file('extdata', 'ind3.tsv', package = 'Prize'),
            system.file('extdata', 'ind4.tsv', package = 'Prize'))
rownames(mat) <- c('ind1', 'ind2', 'ind3', 'ind4')
colnames(mat) <- c('individual_judgement')

# Aggregation of individual judgements
res <- gaggregate(srcfile = mat, method = 'geometric', simulation = 500)
IP(res)

# Aggregation of individual priorities
res <- gaggregate(srcfile = mat, method = 'arithmetic', simulation = 500)
IP(res)
```

---

normal.PCM-data

*A pairwise comparison matrix (PCM)*

---

**Description**

Normal.PCM is a criteria (with no subcriteria) in the prioritization of a set of genes of interest. This file includes a PCM of the genes with respect to their expression level in healthy (normal) tissues. The pairwise comparisons are performed according to the Saaty's fundamental scale.

**Author(s)**

Daryanaz Dargahi

**References**

T.L. Saaty. The Analytic Hierarchy Process, Planning, Priority Setting, Resource Allocation. McGraw-Hill, New York, 1980.

---

normal\_exp\_rating-data

*Rating categories and idealised priorities*

---

### **Description**

The rating categories and computed idealised priorities of alternatives (genes) with respect to their expression in healthy (normal) tissues. This matrix is computed by the rating() function.

### **Author(s)**

Daryanaz Dargahi

---

number-data

*A pairwise comparison matrix (PCM)*

---

### **Description**

Number is a PCM of the categories defined for the number of epitopes subcriteria. The categories include: Single and Multiple. The pairwise comparisons are performed according to the Saaty's fundamental scale.

### **Author(s)**

Daryanaz Dargahi

### **References**

T.L. Saaty. The Analytic Hierarchy Process, Planning, Priority Setting, Resource Allocation. McGraw-Hill, New York, 1980.

---

numEpitope\_alternative\_category-data

*A pairwise comparison matrix (PCM)*

---

### **Description**

A matrix assigning each alternative (gene) to a category with respect to their number of epitopes. The categories include: Single and Multiple.

### **Author(s)**

Daryanaz Dargahi

---

pipeline

*pipeline*

---

### Description

a pipeline for prioritization estimation using analytic hierarchy process (AHP), which supports both relative and rating AHP models.

### Usage

```
pipeline(srcfile, model, simulation = 500)
```

### Arguments

srcfile	a character matrix, where the first column specifies the hierarchy order, the second column includes elements IDs, and the third column includes the path to the PCM/priority matrices (See the example below).
model	the AHP computation model. Choose from relative and rating models. If using the relative model pairwise comparison matrices must be provided for the evaluation of alternatives. However, if using the raing model, rating matrices must be provided for the evaluation of alternatives.
simulation	simulation size for computation of Saaty's inconsistency

### Value

An S4 object including the ahp wight and consistancy measures, and data structures to visualize with ahplot(), rainbowplot(), and wplot().

### Author(s)

Daryanaz Dargahi

### Examples

```
mat <- matrix(nrow = 7, ncol = 3, data = NA)
mat[,1] <- c('0', '1', '2', '3', '4', '4.1', '4.2')
mat[,2] <- c('Prioritization_of_DE_genes', 'Tumor_expression', 'Normal_expression',
            'Frequency', 'Epitopes', 'Number_of_epitopes', 'Size_of_epitopes')
mat[,3] <- c(system.file('extdata', 'aggreg.judgement.tsv', package = 'Prize'),
            system.file('extdata', 'tumor.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'normal.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'freq.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'epitope.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'epitopeNum.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'epitopeLength.PCM.tsv', package = 'Prize'))

result <- pipeline(mat, model = 'relative', simulation = 500)
```

---

pipelineObj-class	Class pipelineObj
-------------------	-------------------

---

### Description

An object that stores the problem hierarchy as well as AHP priorities.

### Objects from the Class

Objects can be created by calls of the form `new("pipelineObj", ...)`.

### Slots

`ahp_plot`: A matrix of problem hierarchy.

`weight_plot`: A list of matrices representing AHP priorities at the criteria and subcriteria level.

`rainbow_plot`: A list of matrices representing final AHP ranking of alternatives at the criteria and subcriteria level.

`ahp_weights`: A list of matrices representing AHP priorities for all decision elements.

`simulation`: A numeric value of the simulation size.

`saaty_inconsistency`: A list of Saaty inconsistency ratios.

### Author(s)

Daryanaz Dargahi <daryanazdargahi@gmail.com>

---

rainbowplot	<i>rainbowplot</i>
-------------	--------------------

---

### Description

Plotting prioritized alternatives in a color-coded barplot, where a color is assigned to each criteria/subcriteria.

### Usage

```
rainbowplot(srcfile, range = NULL, fontsize = 10, xcex = 4, ycex = 8,
  color = "rainbow", xlab = "Total priority score", ylab = "Alternative",
  digit = 3, dist = 0.02, main = NULL)
```

### Arguments

<code>srcfile</code>	a numeric matrix with alternatives on the rows and criteria/subcriteria on the columns. alternative's AHP weights for each criteria, and the sum of each row on the last column (see example below).
<code>range</code>	specifies which alternatives to plot. Either provide a range (e.g. 1:5) or a vector of numbers (e.g. <code>c(2,5,12,20)</code> ). if range is NULL then all alternatives will be plotted. The default value is NULL.



fontsize	the font size of the plot title, x and y axis labels, and legend. The default value is 10.
xcex	the font size of the labels on the bars. The default values is 4.
ycex	the font size of the y axis. The default values is 8.
color	the color palette to fill bars. Either provide a vector of n colors, where n is the number of criteria/subcriteria, or choose from the following palettes 'rainbow, heat, terrain, topo, cm'. The default value is rainbow.
xlab,ylab	the label of the x and y axis, respectively.
digit	the number of digits after decimal point to be shown on the bars. The default value is 3.
dist	the distance between the bar and its lable. The default value is 0.02.
main	the plot title

**Value**

An object created by 'ggplot'.

**Author(s)**

Daryanaz Dargahi

**Examples**

```
mat <- matrix(c(0.007,0.289,0.033,0.118,0.447, 0.015,0.155,0.015,0.088,0.275, 0.048,0.078,0.007,0.044,0.177,
               nrow = 4, ncol = 5, byrow = TRUE, dimnames = list(c('CA9', 'MUC16', 'CD70', 'MUC1'), c('Tumor_expre
rainbowplot(mat, range = NULL, xlab = 'Total priority score' , ylab = 'Alternative', dist = 0.04)
```

---

rainbow\_plot

*Rainbow plot slot*

---

**Description**

rainbow\_plot is a slot of pipelineObj class. It consists of a list of matrices representing final AHP ranking of alternatives at the criteria and subcriteria level.

**Author(s)**

Daryanaz Dargahi <daryanazdargahi@gmail.com>

**Examples**

```
mat <- matrix(nrow = 7, ncol = 3, data = NA)
mat[,1] <- c('0', '1', '2', '3', '4', '4.1', '4.2')
mat[,2] <- c('Prioritization_of_DE_genes', 'Tumor_expression', 'Normal_expression',
             'Frequency', 'Epitopes', 'Number_of_epitopes', 'Size_of_epitopes')
mat[,3] <- c(system.file('extdata', 'aggreg.judgement.tsv', package = 'Prize'),
             system.file('extdata', 'tumor.PCM.tsv', package = 'Prize'),
             system.file('extdata', 'normal.PCM.tsv', package = 'Prize'),
             system.file('extdata', 'freq.PCM.tsv', package = 'Prize'),
             system.file('extdata', 'epitope.PCM.tsv', package = 'Prize'),
             system.file('extdata', 'epitopeNum.PCM.tsv', package = 'Prize'),
```

```

system.file('extdata','epitopeLength.PCM.tsv',package = 'Prize'))

result <- pipeline(mat, model = 'relative', simulation = 500)
rainbow_plot(result)

```

---

rating	<i>rating</i>
--------	---------------

---

### Description

Estimates idealised priorities of alternatives (the rating AHP model).

### Usage

```
rating(scale, alternative, NA_category = NULL, simulation = 500)
```

### Arguments

scale	a pairwise comparison matrix (PCM) of rating categories.
alternative	a N by 2 character matrix, where N is the number of alternatives. The matrix includes alternatives on column #1 and the rating category they belong to on column #2.
NA_category	a character string or vector which specifies categories with the value of zero. Since zero is not achievable by PCM matrix.
simulation	simulation size for computation of Saaty's inconsistency

### Value

An S4 object including the raw and normalized ahp priorities, Satty's inconsistency, and rating matrix.

### Author(s)

Daryanaz Dargahi

### References

T.L. Saaty. Rank from comparisons and from ratings in the analytic hierarchy/network processes. European Journal of Operational Research, 168(2):557-570, January 2006.

T.L. Saaty. The Analytic Hierarchy Process, Planning, Piority Setting, Resource Allocation. McGraw-Hill, New york, 1980.

### Examples

```

mat <- matrix(nrow = 4, ncol = 4, data = NA)

# The category PCM matrix
rownames(mat) <- c('excellent', 'good', 'fair', 'poor')
colnames(mat) <- c('excellent', 'good', 'fair', 'poor')
mat[1,] <- c(1,2,4,6)
mat[2,] <- c(NA,1,2,4)
mat[3,] <- c(NA,NA,1,2)

```

```

mat[4,] <- c(NA,NA,NA,1)

# The alternative matrix
alt <- matrix(nrow = 5, ncol = 2, data = NA)
alt[,1] <- c("Andy", "Emily", "Nina", "Alex", "Jack")
alt[,2] <- c("good", "poor", "good", "fair", "excellent")

result <- rating(mat, alt, simulation = 500)

# Specifying a category with value of zero
alt <- rbind(alt, c('shannon', 'Not_available'))

result <- rating(mat, alt, NA_category = 'Not_available', simulation = 500)

```

---

ratingObj-class	<i>Class ratingObj</i>
-----------------	------------------------

---

### Description

An object that stores the idealised priorities of alternatives (The rating AHP model).

### Objects from the Class

Objects can be created by calls of the form `new("ratingObj", ...)`.

### Slots

**weight:** A matrix of rating categories and their AHP and idealised prioritise.

**saaty\_inconsistency:** The consistency ratio of the categories pairwise comparison matrix.

**RM:** A matrix of alternatives with their scale category and idealised prioritise.

### Author(s)

Daryanaz Dargahi <daryanazdargahi@gmail.com>

---

RM	<i>Rating matrix (RM) slot</i>
----	--------------------------------

---

### Description

RM (Rating matrix) is a slot of ratingObj class. It consists of a matrix of alternatives with their scale category and idealised prioritise.

### Author(s)

Daryanaz Dargahi <daryanazdargahi@gmail.com>

**Examples**

```

mat <- matrix(nrow = 4, ncol = 4, data = NA)

# Category PCM matrix
rownames(mat) <- c('excellent','good','fair','poor')
colnames(mat) <- c('excellent','good','fair','poor')
mat[1,] <- c(1,2,4,6)
mat[2,] <- c(NA,1,2,4)
mat[3,] <- c(NA,NA,1,2)
mat[4,] <- c(NA,NA,NA,1)

# Alternative matrix
alt <- matrix(nrow = 5, ncol = 2, data = NA)
alt[,1] <- c("Andy", "Emily", "Nina", "Alex", "Jack")
alt[,2] <- c("good", "poor", "good", "fair", "excellent")

result <- rating(mat, alt, simulation = 500)
RM(result)

```

---

saaty\_inconsistency     *Saaty inconsistency slot*

---

**Description**

saaty\_inconsistency is a slot of ahpObj, pipelineObj, and ratingObj classes. It consists of Saarty's consistency ratio of a pairwise comparison matrix.

**Author(s)**

Daryanaz Dargahi <daryanazdargahi@gmail.com>

**Examples**

```

# ahp()
mat <- matrix(c(1,2,5, 1/2,1,3, 1/5,1/3,1), nrow = 3, ncol = 3, byrow = TRUE)
res <- ahp(mat, simulation = 500)
saaty_inconsistency(res)

# pipeline()
mat <- matrix(nrow = 7, ncol = 3, data = NA)
mat[,1] <- c('0', '1', '2', '3', '4', '4.1', '4.2')
mat[,2] <- c('Prioritization_of_DE_genes', 'Tumor_expression', 'Normal_expression',
            'Frequency', 'Epitopes', 'Number_of_epitopes', 'Size_of_epitopes')
mat[,3] <- c(system.file('extdata', 'aggreg.judgement.tsv', package = 'Prize'),
            system.file('extdata', 'tumor.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'normal.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'freq.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'epitope.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'epitopeNum.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'epitopeLength.PCM.tsv', package = 'Prize'))

result <- pipeline(mat, model = 'relative', simulation = 500)
saaty_inconsistency(result)

```

```

# rating()
mat <- matrix(nrow = 4, ncol = 4, data = NA)
## Category PCM matrix
rownames(mat) <- c('excellent','good','fair','poor')
colnames(mat) <- c('excellent','good','fair','poor')
mat[1,] <- c(1,2,4,6)
mat[2,] <- c(NA,1,2,4)
mat[3,] <- c(NA,NA,1,2)
mat[4,] <- c(NA,NA,NA,1)
## Alternative matrix
alt <- matrix(nrow = 5, ncol = 2, data = NA)
alt[,1] <- c("Andy", "Emily", "Nina", "Alex", "Jack")
alt[,2] <- c("good", "poor", "good", "fair", "excellent")

result <- rating(mat, alt, simulation = 500)
saaty_inconsistency(result)

```

---

simulation

*Simulation slot*


---

## Description

simulation is a slot of pipelineObj class. It consists of a numeric value of the simulation size (used in order to estimate Saaty's consistency ratio).

## Author(s)

Daryanaz Dargahi <daryanazdargahi@gmail.com>

## Examples

```

mat <- matrix(nrow = 7, ncol = 3, data = NA)
mat[,1] <- c('0', '1', '2', '3', '4', '4.1', '4.2')
mat[,2] <- c('Prioritization_of_DE_genes', 'Tumor_expression', 'Normal_expression',
            'Frequency', 'Epitopes', 'Number_of_epitopes', 'Size_of_epitopes')
mat[,3] <- c(system.file('extdata', 'aggreg.judgement.tsv', package = 'Prize'),
            system.file('extdata', 'tumor.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'normal.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'freq.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'epitope.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'epitopeNum.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'epitopeLength.PCM.tsv', package = 'Prize'))

result <- pipeline(mat, model = 'relative', simulation = 500)
simulation(result)

```

---

tumor.PCM-data	<i>A pairwise comparison matrix (PCM)</i>
----------------	---

---

### Description

Tumor.PCM is a criteria (with no subcriteria) in the prioritization of a set of genes of interest. This file includes a PCM of the genes with respect to their expression level in tumor tissue. The pairwise comparisons are performed according to the Saaty's fundamental scale.

### Author(s)

Daryanaz Dargahi

### References

T.L. Saaty. The Analytic Hierarchy Process, Planning, Priority Setting, Resource Allocation. McGraw-Hill, New York, 1980.

---

tumor_exp_rating-data	<i>Rating categories and idealised priorities</i>
-----------------------	---

---

### Description

The rating categories and computed idealised priorities of alternatives (genes) with respect to their expression in tumor tissue. This matrix is computed by the rating() function.

### Author(s)

Daryanaz Dargahi

---

weight	<i>Weight slot</i>
--------	--------------------

---

### Description

weight is a slot of ahpObj and ratingObj classes. It consists of computed AHP weights from a pairwise comparison matrix.

### Author(s)

Daryanaz Dargahi <daryanazdargahi@gmail.com>

**Examples**

```

# ahp()
mat <- matrix(c(1,2,5, 1/2,1,3, 1/5,1/3,1), nrow = 3, ncol = 3, byrow = TRUE)
res <- ahp(mat, simulation = 500)
weight(res)

# rating()
mat <- matrix(nrow = 4, ncol = 4, data = NA)

## Category PCM matrix
rownames(mat) <- c('excellent','good','fair','poor')
colnames(mat) <- c('excellent','good','fair','poor')
mat[1,] <- c(1,2,4,6)
mat[2,] <- c(NA,1,2,4)
mat[3,] <- c(NA,NA,1,2)
mat[4,] <- c(NA,NA,NA,1)
## Alternative matrix
alt <- matrix(nrow = 5, ncol = 2, data = NA)
alt[,1] <- c("Andy", "Emily", "Nina", "Alex", "Jack")
alt[,2] <- c("good", "poor", "good", "fair", "excellent")

result <- rating(mat, alt, simulation = 500)
weight(result)

```

weight\_plot

*Weight plot slot***Description**

weight\_plot is a slot of pipelineObj class. It consists of a list of matrices representing AHP priorities at the criteria and subcriteria level.

**Author(s)**

Daryanaz Dargahi <daryanazdargahi@gmail.com>

**Examples**

```

mat <- matrix(nrow = 7, ncol = 3, data = NA)
mat[,1] <- c('0', '1', '2', '3', '4', '4.1', '4.2')
mat[,2] <- c('Prioritization_of_DE_genes', 'Tumor_expression', 'Normal_expression',
            'Frequency', 'Epitopes', 'Number_of_epitopes', 'Size_of_epitopes')
mat[,3] <- c(system.file('extdata', 'aggreg.judgement.tsv', package = 'Prize'),
            system.file('extdata', 'tumor.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'normal.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'freq.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'epitope.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'epitopeNum.PCM.tsv', package = 'Prize'),
            system.file('extdata', 'epitopeLength.PCM.tsv', package = 'Prize'))

result <- pipeline(mat, model = 'relative', simulation = 500)
weight_plot(result)

```

wplot

*Wplot***Description**

Plotting the criteria/subcriteria ahp weights in a bar/pie plot.

**Usage**

```
wplot(srcfile, color = "rainbow", fontsize = 15, xcex = 10, ycex = 10,
      pcex = 5, digit = 2, xlab = NULL, ylab = NULL, type = "bar",
      main = NULL)
```

**Arguments**

srcfile	a matrix, where the first column includes criteria/subcriteria ID and the second includes the ahp weights.
color	the color palette to fill bars. Either provide a vector of n colors, where n is the number of criteria, or choose from the following palettes 'rainbow, heat, terrain, topo, cm'. The default value is rainbow.
fontsize	the font size of the plot title, and x and y axis labels. The default value is 15.
xcex, ycex	the font size of the x and y axis, respectively. The default values is 10.
pcex	the font size of the labels inside pie chart
digit	the number of digits after decimal point to be shown on the x axis.
xlab, ylab	the label of the x and y axis, respectively.
type	wplot offers two plot types; bar and pie plots. Default value is bar.
main	the plot title

**Value**

An object created by 'ggplot'.

**Author(s)**

Daryanaz Dargahi

**Examples**

```
mat <- matrix(nrow = 4, ncol = 2, data = NA)
mat[,1] <- c('Tumor_expression', 'Normal_expression', 'Frequency', 'Epitope')
mat[,2] <- c(0.470, 0.341, 0.116, 0.073)

wplot(mat, xlab = 'Weight', ylab = 'Criteria', type = 'bar')
wplot(mat, type = 'pie')
```



# Index

- \*Topic **Analytic Hierarchy Process**
  - Prize-package, 3
- \*Topic **Group decision making**
  - Prize-package, 3
- \*Topic **Prioritization**
  - Prize-package, 3
  
- aggreg.judgement
  - (aggreg.judgement-data), 4
- aggreg.judgement-data, 4
- aggregJudgement
  - (aggreg.judgement-data), 4
- ahmatrix, 5
- ahmatrixObj (ahmatrixObj-class), 6
- ahmatrixObj, ANY-method
  - (ahmatrixObj-class), 6
- ahmatrixObj-class, 6
- ahp, 6
- ahp\_matrix, 8
- ahp\_matrix, ANY-method (ahp\_matrix), 8
- ahp\_plot, 9
- ahp\_plot, ANY-method (ahp\_plot), 9
- ahp\_weights, 9
- ahp\_weights, ANY-method (ahp\_weights), 9
- ahplot, 7
- ahpmatrix (ahp\_matrix), 8
- ahpObj (ahpObj-class), 8
- ahpObj, ANY-method (ahpObj-class), 8
- ahpObj-class, 8
- ahpplot (ahp\_plot), 9
- ahpweights (ahp\_weights), 9
- AIJ, 10
- Aij (AIJ), 10
- aij (AIJ), 10
- AIJ, ANY-method (AIJ), 10
- AIP, 10
- Aip (AIP), 10
- aip (AIP), 10
- AIP, ANY-method (AIP), 10
- ariAggreg (ariAggreg-class), 11
- ariAggreg, ANY-method
  - (ariAggreg-class), 11
- ariAggreg-class, 11
  
- CI, 11
- Ci (CI), 11
- ci (CI), 11
- CI, ANY-method (CI), 11
- crplot, 12
  
- dplot, 13
  
- epitope.PCM (epitope.PCM-data), 14
- epitope.PCM-data, 14
- epitope\_num\_rating
  - (epitope\_num\_rating-data), 15
- epitope\_num\_rating-data, 15
- epitope\_size\_rating
  - (epitope\_size\_rating-data), 15
- epitope\_size\_rating-data, 15
- epitopeLength.PCM
  - (epitopeLength.PCM-data), 14
- epitopeLength.PCM-data, 14
- epitopeLengthPCM
  - (epitopeLength.PCM-data), 14
- epitopeNum.PCM (epitopeNum.PCM-data), 14
- epitopeNum.PCM-data, 14
- epitopeNumPCM (epitopeNum.PCM-data), 14
- epitopeNumRating
  - (epitope\_num\_rating-data), 15
- epitopePCM (epitope.PCM-data), 14
- epitopeSizeRating
  - (epitope\_size\_rating-data), 15
  
- freq.PCM (freq.PCM-data), 15
- freq.PCM-data, 15
- freq\_exp\_rating (freq\_exp\_rating-data), 16
- freq\_exp\_rating-data, 16
- freqExpRating (freq\_exp\_rating-data), 16
- freqPCM (freq.PCM-data), 15
  
- gaggregate, 16
- GCR, 17
- Gcr (GCR), 17
- gcr (GCR), 17
- GCR, ANY-method (GCR), 17
- genes.list (genes.list-data), 18

- genes.list-data, 18
- genesList (genes.list-data), 18
- geoAggreg (geoAggreg-class), 18
- geoAggreg, ANY-method  
(geoAggreg-class), 18
- geoAggreg-class, 18
- ICR, 19
- Icr (ICR), 19
- icr (ICR), 19
- ICR, ANY-method (ICR), 19
- ind1 (ind1-data), 19
- ind1-data, 19
- ind2 (ind2-data), 20
- ind2-data, 20
- ind3 (ind3-data), 20
- ind3-data, 20
- ind4 (ind4-data), 20
- ind4-data, 20
- IP, 21
- Ip (IP), 21
- ip (IP), 21
- IP, ANY-method (IP), 21
- normal.PCM (normal.PCM-data), 21
- normal.PCM-data, 21
- normal\_exp\_rating  
(normal\_exp\_rating-data), 22
- normal\_exp\_rating-data, 22
- normalExpRating  
(normal\_exp\_rating-data), 22
- normalPCM (normal.PCM-data), 21
- number (number-data), 22
- number-data, 22
- numEpitope\_alternative\_category  
(numEpitope\_alternative\_category-data),  
22
- numEpitope\_alternative\_category-data,  
22
- numEpitopeAlternativeCategory  
(numEpitope\_alternative\_category-data),  
22
- pipeline, 23
- pipelineObj (pipelineObj-class), 24
- pipelineObj, ANY-method  
(pipelineObj-class), 24
- pipelineObj-class, 24
- Prize (Prize-package), 3
- Prize-package, 3
- rainbow\_plot, 25
- rainbow\_plot, ANY-method (rainbow\_plot),  
25
- rainbowplot, 24
- rating, 26
- ratingObj (ratingObj-class), 27
- ratingObj, ANY-method  
(ratingObj-class), 27
- ratingObj-class, 27
- RM, 27
- Rm (RM), 27
- rm (RM), 27
- RM, ANY-method (RM), 27
- saaty\_inconsistency, 28
- saaty\_inconsistency, ANY-method  
(saaty\_inconsistency), 28
- saatyinconsistency  
(saaty\_inconsistency), 28
- simulation, 29
- simulation, ANY-method (simulation), 29
- tumor.PCM (tumor.PCM-data), 30
- tumor.PCM-data, 30
- tumor\_exp\_rating  
(tumor\_exp\_rating-data), 30
- tumor\_exp\_rating-data, 30
- tumorExpRating (tumor\_exp\_rating-data),  
30
- tumorPCM (tumor.PCM-data), 30
- weight, 30
- weight, ANY-method (weight), 30
- weight\_plot, 31
- weight\_plot, ANY-method (weight\_plot), 31
- wplot, 32